

## Canon i-SENSYS LBP352x 1200 x 1200 DPI A4

**Marchio :** Canon

**Famiglia del prodotto:** i-SENSYS

**Codice prodotto:** 0562C008

**Nome del prodotto :** LBP352x



1200 x 1200 dpi, duplex, A4, UFR II, PCL5e, PCL6, USB 2.0, LAN, 415 x 529 x 438 mm, 26.2 kg  
 Canon i-SENSYS LBP352x. Tecnologia di stampa: Laser. Numero di cartucce di stampa: 1, Ciclo massimo di funzionamento: 280000 pagine per mese. Risoluzione massima: 1200 x 1200 DPI. Massimo formato carta serie ISO A: A4. Velocità di stampa (nero, qualità normale, A4/US Letter): 62 ppm, Stampa fronte/retro. Tipologia display: LCD, Colore del prodotto: Nero, Bianco

Printing		Network	
Duplex printing mode	Auto	Wi-Fi *	✗
Colour *	✗	Ethernet LAN *	✓
Print technology *	Laser	Web-based management	✓
Duplex printing *	✓	Mobile printing technologies	Apple AirPrint, Canon PRINT Business, Google Cloud Print, Mopria Print Service
Maximum resolution *	1200 x 1200 DPI	<b>Performance</b>	
Print speed (black, normal quality, A4/US Letter) *	62 ppm	Internal memory *	1024 MB
Duplex print speed (black, normal quality, A4/US Letter)	41.4 ppm	Built-in processor	✓
Warm-up time	29 s	Processor frequency	528 MHz
Time to first page (black, normal)	7 s	Sound pressure level (printing)	71 dB
Print margins (top, bottom, right, left)	5 mm	<b>Design</b>	
Secure printing	✓	Product colour *	Black, White
<b>Features</b>		Built-in display *	✓
Maximum duty cycle *	280000 pages per month	Display	LCD
Recommended duty cycle	5000 - 20000 pages per month	Display number of lines	5 lines
Number of print cartridges *	1	<b>Power</b>	
Page description languages *	PCL 5e, PCL 6, URF	Power consumption (printing) *	850 W
<b>Input &amp; output capacity</b>		Power consumption (max)	1650 W
Total number of input trays *	1	Power consumption (standby)	19 W
Total input capacity *	500 sheets	Power consumption (off)	0.17 W
Total output capacity *	500 sheets	Energy Star Typical Electricity Consumption (TEC)	2.8 kWh/week
Paper input type	Cassette, Paper tray	AC input voltage	220 - 240 V
Multi-Purpose tray	✓	AC input frequency	50 - 60 Hz
Multi-Purpose tray input capacity	100 sheets		
Maximum number of input trays	4		
<b>Paper handling</b>			
Maximum ISO A-series paper size *	A4		
Paper tray media types *	Envelopes, Heavy paper, Labels, Plain paper		
ISO A-series sizes (A0...A9) *	A4, A5, A6		
ISO B-series sizes (B0...B9)	B5, B6		
Envelopes sizes	10, C5, DL, Monarch		
Custom media width	148 - 216 mm		
Custom media length	210 - 356 mm		
Paper tray media weight	60 - 120 g/m <sup>2</sup>		
Multi-Purpose Tray media weight	60 - 199 g/m <sup>2</sup>		
Duplex media weight	60 - 120 g/m <sup>2</sup>		
<b>Ports &amp; interfaces</b>			
Standard interfaces	Ethernet, USB 2.0		
Direct printing *	✓		
USB 2.0 ports quantity	1		

System requirements	
Windows operating systems supported	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64
Mac operating systems supported	Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Linux operating systems supported	✓
Server operating systems supported	Windows Server 2003, Windows Server 2003 R2, Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2
Operational conditions	
Operating temperature (T-T)	10 - 30 °C
Operating relative humidity (H-H)	20 - 80%
Weight & dimensions	
Width	415 mm
Depth	529 mm
Height	438 mm
Weight	26.2 kg
Logistics data	
Harmonized System (HS) code	84433210
Other features	
Power LED	✓
Print resolution	600 x 600 DPI



4549292051421

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-APR-2025. Prints or copies of Information are only valid on the printed Publication date