# Lenovo

# Google Meet Series one Room Kits by Lenovo Gen 2 20YW0006IX

### **Product**

Google Meet Series One Room Kits Gen 2(Small Kit)

### Region

WE

### Country/Region

Italy

### Machine Type

20YW

### TopSeller

TopSeller

### **Processor**

Intel Core i7-10510U (4C / 8T, 1.8 / 4.9GHz, 8MB)

### Graphics

Integrated Intel UHD Graphics

### Chipset

Intel SoC Platform

### Memory

2x 4GB SO-DIMM DDR4-3200

### Storage

128GB SSD M.2 2280 SATA6Gb/s

### Display

None

### Touchscreen

2-point Multi-touch

### Remote Control

Remote Control, Charcoal

### Camera

Smart Camera, Black

### Microphone

None

### Speakers

1x Smart Audio Bar, Charcoal

### Ethernet

Integrated 100/1000M

### WLAN + Bluetooth

Intel AX201 11ax, 2x2 + BT5.0

### Case Color

Charcoal

### **Power Supply**

240W adapter

### Operating System

Chrome OS

### Base Warranty

3-year Premier Support

### Included Upgrade

3Y Premier Support Courier/CCI Upgrade from 3Y Courier/CCI (5WS0T24669)

### EAN/UPC/JAN

0196118441740

## End of Support

2028-04-07

### Announce Date

2021-12-13

# WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



### https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.
© Lenovo, 2022. All rights reserved.



# Google Meet Series One Room Kits by Lenovo Gen 2 Platform Specifications

| Room Kit Options                            |   |   |                |                               |                                     | 1                        | Smart Camera  |
|---|---|---|----------------|-------------------------------|-------------------------------------|--------------------------|---|
| noon kii Options                            |   | Small Room Kit                          | Medium Roo     | edium Room Kit Large Room Kit |                                     | Image                    | 12 MP 1/2.3" CMOS sensor, up to 1080p@30fps video capture, f/2.8 aperture   |
| 1   | Compute System  | 1x                                      | 1x             |                               | 1x                                  | Optics                   | Ultra-wide angle glass optics, 120° horizontal field of view  |
| 1   | Camera  | Smart Camera                            | Smart Came     | 2ra C                         | mart Camera XL                      | Microphone               | Omnidirectional microphone  |
| 1   |   |   |                |                               |                                     | Ports                    | 1x RJ-45 Ethernet (PoE, connect to Compute System)  |
| 1   | Audio Bar   | Smart Audio Bar                         | Smart Audio    |                               | mart Audio Bar +<br>dd-on Audio Bar | Mounting                 | Wall mount kit, TV mount kit, and magnetic dock   |
| 1   | <u> </u>  | <b>D</b>                                | <b>-</b> · -   |                               |                                     | Dimensions               | (LxWxH) 84 x 107 x 42 mm  |
| 1   | Controller  | Remote Control                          | Touch Contro   | roller T                      | ouch Controller                     |                          | Audio Bar   |
| 1   | Mic Pod   | None                                    | 1x             |                               | 2x                                  |                          | Smart Audio Bar   |
| Color                                       | Chalk or Charcoal   |   |                |                               |                                     | Speaker                  | 20W RMS power, 80Hz-24kHz frequency response  |
| Base Warranty                               | 3-year Lenovo Premier Support warranty  |   |                |                               |                                     | Microphone               | 8 element, linear beamforming array, 100Hz-24kHz pickup, optimal pickup range of  |
|   | Compute System  |   |                |                               |                                     | i                        | up to 4m  |
| Processor                                   | 10th Gen Intel Core™ i7 Processor   |   |                |                               |                                     | Noise Control            | AEC, ANC, and TrueVoice™ multi-channel noise cancellation (via onboard Google   |
|   | Processor Co  | ores / Frequency<br>nreads Base/Max(GHz |                | emory Supp<br>(Up to)         | oort Integrated<br>Graphics         | Ports                    | Edge TPUs)  1x USB-C with USB 2.0 UAC (only for audio out)  |
|   | Core i7-10510U  | 4 / 8 1.8G / 4.9G                       | 8 MB [         | 8 MB DDR4-2666                |                                     | 4                        | 1x stereo analog RCA output (for assistive listening devices) 1x RJ-45 Ethernet (PoE, connect to Compute System)  |
| TPU   | Two Google Edge T   | PUs via M.2 slot, pro                   | vides AI and r | machine le                    | arning capability                   | ]                        | 2x RJ-45 Daisy Chain Ports (PoE like, connect to Add-on Audio Bar and Mic Pod)  |
|   | to maximize audio and video quality   |   |                |                               |                                     | Mounting                 | Wall mount kit  |
| ,   | 8GB DDR4-3200*  |   |                |                               |                                     | Dimensions               | (LxWxH) 95 x 705 x 133 mm   |
|   | * Installed memory run at 2666MHz due to capability of processor  |   |                |                               | UI                                  | -                        | Add-on Audio Bar  |
|   | 128GB M.2 2280 SSD  |   |                |                               |                                     | Speaker                  | 20W RMS power, 80Hz-24kHz frequency response  |
| Front Ports*                                | Intel SoC (System on Chip) platform  None   |   |                |                               |                                     | Microphone               | 8 element, linear beamforming array, 100Hz-24kHz pickup, optimal pickup range of up to 4m   |
|   | 3x USB 3.2 Gen 1, 1x USB-C 3.2 Gen 1, 1x HDMI-in 2.0, 2x HDMI-out 2.0 with CEC, 5x RJ-45 Ethernet (one uplink port for internet connection, four downlink ports for IP-based peripherals), 1x power connector, 1x headphone / microphone combo jack (3.5mm)   |   |                |                               |                                     | Ports                    | 1x RJ-45 Daisy Chain Port (PoE like, connect to Smart Audio Bar)  |
|   |   |   |                |                               |                                     | Mounting                 | Wall mount kit  |
|   |   |   |                |                               | an theoretical asses                | Dimensions               | (LxWxH) 95 x 705 x 133 mm   |
|   | * Depending on many factors, actual data transfer speed may be lower than theoretical speed  Realtek ALC5682I-VD-CGT  |   |                |                               |                                     |                          | Controller  |
|   | 11ax Wi-Fi + BT 5.2, M.2 Card, Intel Wi-Fi 6 AX201 (2.4GHz / 5GHz), 2x2 Bluetooth 5.2 wireless, integrated in Wi-Fi + Bluetooth combo adapter Gigabit ethernet, Realtek RTL8111H (1x RJ-45, uplink) + Intel Ethernet Controller I350-AM4 (4x RJ-45, downlink) |   |                |                               |                                     | -                        | Touch Controller  |
| Bluetooth<br>Ethernet                       |   |   |                |                               |                                     | Display Multi-touch      | 10.1" (1280x800), wide viewing angle (Horizontal/Vertical: +/- 89°), 350 nits, 16:10 aspect ratio, 800:1 contrast ratio, smudge resistant, Supports 2-point touch                                     |
|   | 240 watts adapter, 100V - 240V  |   |                |                               |                                     | Sensors                  | Color sensor, orientation sensor  |
|   | Wall mount kit and table stand, magnetically attach to Compute System   |   |                |                               |                                     | Ports                    | 1x RJ-45 Ethernet (PoE, connect to Compute System)  |
|   | (LxWxH) 135 x 284 x 29 mm   |   |                |                               | <i>y</i>                            | Mounting                 | Wall mount kit  |
| Operating System                            |   |   |                |                               |                                     | Dimensions               | (LxWxH) 164 x 245 x 91 mm   |
| , 3 = jetem                                 |   | Camera                                  |                |                               |                                     |                          | Remote Control  |
|   |   | Smart Camera X                          | L              |                               |                                     | Remote                   | 2.4 RF remote   |
| Image                                       | 20.30 MP 1" CMOS sensor, up to 1080p@30fps video capture, f/2.9 aperture, automatically support digital PTZ (Pan / Tilt / Zoom) via Google Al   |   |                |                               | :/2.9 aperture,                     | Keypad  Battery and Dock | 10 function keys on front (Navi keys, Microphone on/off, Menu, End, Volume up/down keys), QWERTY keyboard on rear (38 keys)  Embedded rechargeable lithium ion battery with USB-powered charging dock |
|   | Wide angle glass optics, 95° horizontal field of view   |   |                |                               |                                     | Dimensions               | (LxWxH) 130 x 45 x 14 mm  |
| <u> </u>                                    | Omnidirectional microphone  |   |                |                               |                                     |                          | Mic Pod   |
|   | 1x RJ-45 Ethernet (PoE, connect to Compute System)  |   |                |                               |                                     | Microphone               | 8 element, circular beamforming array, 100Hz-24kHz pickup, optimal pickup range   |
|   | Wall mount kit, TV mount kit, and magnetic dock   |   |                |                               |                                     | i '                      | of up to 2m   |
|   | (LxWxH) 84 x 122 x 52 mm  |   |                |                               |                                     | Ports                    | 2x ÅJ-45 Daisy Chain ports (PoE like, one input connects to Smart Audio Bar or previous Mic Pod, one output port connects to next Mic Pod) *Daisy Chain supports up to 4 mic pods                     |
|   |   |   |                |                               |                                     | Dimensions               | (LxWxH) 95 x 95 x 30 mm   |
| See footnotes for more detailed information |   |   |                |                               |                                     |                          | Lenovo, December 2020   |

