

Philips V Line 241V8AW/00 Monitor PC 60,5 cm (23.8") 1920 x 1080 Pixel Full HD LCD Bianco

Marchio : Philips

Famiglia del prodotto: V Line **Codice prodotto:** 241V8AW/00

Nome del prodotto :
241V8AW/00

Monitor 241V8AW Monitor LCD

Philips V Line 241V8AW/00 Monitor PC 60,5 cm (23.8") 1920 x 1080 Pixel Full HD LCD Bianco:

Il monitor Philips V-Line con ampio angolo di visualizzazione offre una visione oltre ogni limite, una qualità elevata e funzioni essenziali. La sincronizzazione adattiva assicura una visualizzazione video fluida. Caratteristiche quali antiriflesso, modalità LowBlue e immagini prive di sfarfallio non affaticano gli occhi.

Philips V Line 241V8AW/00. Dimensioni diagonale schermo: 60,5 cm (23.8"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Altoparlanti incorporati. Montaggio standard VESA. Colore del prodotto: Bianco



Display

Display diagonal *	60.5 cm (23.8")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Backlight type	W-LED
Touchscreen *	✗
Display brightness (typical)	250 cd/m ²
Response time *	4 ms
Anti-glare screen	✓
Screen shape *	Flat
Contrast ratio (typical) *	1000:1
Dynamic contrast ratio marketing name	Mega Infinity DCR
Maximum refresh rate *	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.275 x 0.275 mm
Pixel density	93 ppi
Horizontal scan range	30 - 85 kHz
Vertical scan range	48 - 75 Hz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Sync-on-green (SOG)	✓
Display diagonal (metric)	60.5 cm
DDC/CI	✓
Haze rate	25%

Ergonomics

Height adjustment *	✗
Tilt adjustment	✓
Tilt angle range	-5 - 20°
On Screen Display (OSD)	✓
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Number of OSD languages	20
Plug and Play	✓
LED indicators	Operation, Stand-by

Power

Energy efficiency class (SDR) *	E
Energy efficiency class (HDR) *	Not available
Energy consumption (SDR) per 1000 hours *	18 kWh
Power consumption (typical) *	21.64 W
Power consumption (standby) *	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m

Display		Operational conditions	
Surface hardness	3H	Non-operating altitude	3658 - 12192 m
Colour gamut standard	sRGB	Weight & dimensions	
Display sRGB	✓	Width (with stand)	540 mm
Performance		Depth (with stand)	220 mm
NVIDIA G-SYNC *	✗	Height (with stand)	416 mm
AMD FreeSync *	✗	Weight (with stand)	2.87 kg
VESA Adaptive Sync support	✓	Width (without stand)	540 mm
Component video sync	Separate sync, Sync-on-green (SOG)	Depth (without stand)	51 mm
Flicker-free technology	✓	Height (without stand)	322 mm
Low Blue Light technology	✓	Weight (without stand)	2.49 kg
Multimedia		Packaging data	
Number of speakers	2	Package width	608 mm
RMS rated power	4 W	Package depth	121 mm
Built-in speaker(s) *	✓	Package height	415 mm
Built-in camera *	✗	Package weight	4.22 kg
Design		Packaging content	
Market positioning *	Home	Stand included	✓
Product colour *	White	Cables included	AC, HDMI
Ports & interfaces		Manual	✓
Built-in USB hub *	✗	Sustainability	
VGA (D-Sub) ports quantity	1	Sustainability compliance	✓
HDMI *	✓	Other features	
HDMI ports quantity	1	Compatible operating systems	Mac OS X Windows 11/10/8.1/8
HDMI version	1.4	Exterior finish type	Textured
Audio output	✓	Picture enhancement	SmartImage
PC Audio in	✓	Recyclable packaging material	100%
HDCP	✓	Regulatory Approvals	CB; CE Mark; EAC; FCC; ICES-003; TUV Ergo; TUV/GS
HDCP version	1.4	Heavy metals free	Hg (mercury)
Ergonomics		EasyRead mode	✓
VESA mounting *	✓	LowBlue mode	✓
Panel mounting interface	100 x 100 mm	Compliance certificates	CB, CE, Federal Communications Commission (FCC), RoHS, cTUVus
Cable lock slot *	✓	Mean time between failures (MTBF)	30000 h
Cable lock slot type	Kensington		



8712581804343

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-DEC-2024. Prints or copies of Information are only valid on the printed Publication date