

Philips Serie 1000 24E1N1300AE/00 Monitor PC 60,5 cm (23.8") 1920 x 1080 Pixel Full HD LCD Nero

Marchio : Philips

Famiglia del prodotto: Serie 1000

Codice prodotto: 24E1N1300AE/00

Nome del prodotto :
24E1N1300AE/00

Monitor 24E1N1300AE Display LCD Full HD

[Philips Serie 1000 24E1N1300AE/00 Monitor PC 60,5 cm \(23.8"\) 1920 x 1080 Pixel Full HD LCD Nero:](#)

Questo monitor è stato realizzato per farti restare sempre connesso. Grazie a funzioni come USB-C 3.2 con alimentazione, gli utenti possono caricare il proprio dispositivo collegato e lavorare senza problemi con un solo cavo. Inoltre, il cavo singolo rende lo spazio di lavoro pulito.

Philips Serie 1000 24E1N1300AE/00. Dimensioni diagonale schermo: 60,5 cm (23.8"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Altoparlanti incorporati. Hub USB integrato. Montaggio standard VESA, Regolazione altezza. Colore del prodotto: Nero



Display		Ports & interfaces	
Display diagonal *	60.5 cm (23.8")	HDCP version	1.4
Display resolution *	1920 x 1080 pixels	Ergonomics	
HD type *	Full HD	VESA mounting *	✓
Native aspect ratio *	16:9	Panel mounting interface	100 x 100 mm
Display technology *	LCD	Cable lock slot *	✓
Panel type *	IPS	Cable lock slot type	Kensington
Backlight type	W-LED	Height adjustment *	✓
Touchscreen *	✗	Adjustable height (max)	10 cm
Display brightness (typical)	250 cd/m ²	Tilt adjustment	✓
Response time *	4 ms	Tilt angle range	-5 - 20°
Response time measurement type	GTG (Gray to Gray)	On Screen Display (OSD)	✓
Response time (MPRT)	1 ms	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Anti-glare screen	✓	Plug and Play	✓
Screen shape *	Flat	LED indicators	Operation, Stand-by
Contrast ratio (typical) *	1300:1	Power	
Dynamic contrast ratio marketing name	Mega Infinity DCR	Energy efficiency class (SDR) *	E
Maximum refresh rate *	100 Hz	Power consumption (typical) *	18.3 W
Viewing angle, horizontal	178°	Power consumption (standby) *	0.5 W
Viewing angle, vertical	178°	Power consumption (off)	0.3 W
Display number of colours *	16.7 million colours	AC input voltage	100 - 240 V
Response time (fast)	1 ms	AC input frequency	50/60 Hz
Pixel pitch	0.2745 x 0.2745 mm	Power supply type	Internal
Pixel density	92.56 ppi		
Horizontal scan range	30 - 115 kHz		
Vertical scan range	48 - 100 Hz		
Viewable size, horizontal	52.7 cm		
Viewable size, vertical	29.6 cm		
Display diagonal (metric)	60.5 cm		

Display		Operational conditions	
DDC/CI	✓	Operating temperature (T-T)	0 - 40 °C
Haze rate	25%	Storage temperature (T-T)	-20 - 60 °C
Surface hardness	3H	Operating relative humidity (H-H)	20 - 80%
Display sRGB	✓	Operating altitude	0 - 3658 m
Performance		Non-operating altitude	0 - 12192 m
NVIDIA G-SYNC *	✗	Weight & dimensions	
AMD FreeSync *	✗	Width (with stand)	542 mm
VESA Adaptive Sync support	✓	Depth (with stand)	187 mm
Component video sync	Separate sync	Height (with stand)	442 mm
Flicker-free technology	✓	Weight (with stand)	4.68 kg
Low Blue Light technology	✓	Width (without stand)	542 mm
Multimedia		Depth (without stand)	45 mm
Number of speakers	2	Height (without stand)	316 mm
Built-in speaker(s) *	✓	Weight (without stand)	3.06 kg
Built-in camera *	✗	Packaging data	
Design		Package width	730 mm
Product colour *	Black	Package depth	141 mm
Ports & interfaces		Package height	391 mm
Built-in USB hub *	✓	Package weight	6.97 kg
USB Type-A downstream ports quantity	2	Packaging content	
USB Type-C downstream ports quantity	1	Stand included	✓
USB Power Delivery (USB PD)	✓	Cables included	HDMI, Power, USB Type-C
USB Power Delivery up to	65 W	Manual	✓
HDMI *	✓	Sustainability	
HDMI ports quantity	1	Doesn't contain	Mercury, PVC/BFR
HDMI version	1.4	Other features	
Audio output	✓	Exterior finish type	Textured
HDCP	✓	Picture enhancement	SmartImage game
		Recyclable packaging material	100%
		Regulatory Approvals	CB; CE Mark; TUV/ISO9241-307; TUV-BAUART; EAC; FCC; ICES-003; VCCI
		EasyRead mode	✓
		LowBlue mode	✓
		Mean time between failures (MTBF)	50000 h



8712581804268

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.