

PHILIPS

Philips Evnia 24M2N3200S/00 Monitor PC 60,5 cm (23.8") 1920 x 1080 Pixel Full HD LCD Nero

Marchio : Philips

Famiglia del prodotto: Evnia

Codice prodotto:
24M2N3200S/00

Nome del prodotto :
24M2N3200S/00



Fast IPS Gaming monitor 24M2N3200S Monitor da gaming Full HD

Philips Evnia 24M2N3200S/00 Monitor PC 60,5 cm (23.8") 1920 x 1080 Pixel Full HD LCD Nero:

Questo velocissimo monitor IPS consente di giocare con precisione e rapidità a una frequenza di 180 Hz. Inoltre, grazie alle immagini nitide di qualità HDR e alla garanzia di una risoluzione Full HD, offre un'eccellente esperienza di gioco a 360 gradi.

Philips Evnia 24M2N3200S/00. Dimensioni diagonale schermo: 60,5 cm (23.8"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Altoparlanti incorporati. Montaggio standard VESA. Colore del prodotto: Nero

Display		Ports & interfaces	
Display diagonal *	60.5 cm (23.8")	HDCP version	1.4/2.2
Display resolution *	1920 x 1080 pixels	Ergonomics	
HD type *	Full HD	VESA mounting *	✓
Native aspect ratio *	16:9	Panel mounting interface	100 x 100 mm
Display technology *	LCD	Cable lock slot *	✓
Panel type *	IPS	Cable lock slot type	Kensington
LED backlight	✓	Tilt adjustment	✓
Backlight type	W-LED	Tilt angle range	-5 - 20°
Touchscreen *	✗	On Screen Display (OSD)	✓
Display brightness (typical)	300 cd/m ²	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Anti-glare screen	✓	Plug and Play	✓
Screen shape *	Flat	LED indicators	Operation, Stand-by
Contrast ratio (typical) *	1000:1	Power	
Dynamic contrast ratio marketing name	Mega Infinity DCR	Power consumption (typical) *	18.7 W
Maximum refresh rate *	180 Hz	Power consumption (standby) *	0.5 W
Viewing angle, horizontal	178°	Power consumption (off)	0.3 W
Viewing angle, vertical	178°	AC input voltage	100 - 240 V
Display number of colours *	16.7 million colours	AC input frequency	50/60 Hz
Response time (fast)	0.5 ms	Power supply type	Internal
SmartResponse	1 ms	Operational conditions	
Pixel pitch	0.2745 x 0.2745 mm	Operating temperature (T-T)	0 - 40 °C
Pixel density	93 ppi	Storage temperature (T-T)	-20 - 60 °C
Horizontal scan range	30 - 200 kHz	Operating relative humidity (H-H)	20 - 80%
Vertical scan range	48 - 180 Hz	Operating altitude	0 - 3658 m
Viewable size, horizontal	52.7 cm	Non-operating altitude	3658 - 12192 m
Viewable size, vertical	29.6 cm		
Display diagonal (metric)	60.5 cm		
High Dynamic Range (HDR) supported	✓		

Display		Weight & dimensions	
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)	Width (with stand)	540 mm
DDC/CI	✓	Depth (with stand)	195 mm
Haze rate	25%	Height (with stand)	433 mm
Surface hardness	3H	Weight (with stand)	3.38 kg
Colour gamut standard	DCI-P3	Width (without stand)	540 mm
Colour gamut	93%	Depth (without stand)	55 mm
sRGB coverage (typical)	126%	Height (without stand)	325 mm
NTSC coverage (typical)	113%	Weight (without stand)	2.77 kg
Adobe RGB coverage	110%	Packaging data	
Display sRGB	✓	Package width	610 mm
Performance		Package depth	126 mm
Component video sync	Separate sync	Package height	395 mm
Flicker-free technology	✓	Package weight	5.51 kg
Low Blue Light technology	✓	Packaging content	
Multimedia		Stand included	✓
Number of speakers	2	Cables included	AC, DisplayPort, HDMI
RMS rated power	4 W	Manual	✓
Built-in speaker(s) *	✓	Sustainability	
Built-in camera *	✗	Sustainability compliance	✓
Design		Other features	
Market positioning *	Gaming	Low input lag	✓
Product colour *	Black	Compatible operating systems	Mac OS X Windows 10 / 11
Colour name	Charcoal	Exterior finish type	Textured
Ports & interfaces		Picture enhancement	SmartImage game
Built-in USB hub *	✗	Recyclable packaging material	100%
HDMI *	✓	Regulatory Approvals CB, TUV/ISO 9241-307, TUV-BAUART, EAC, BSMI, CE marking, UKCA, EMV, FCC, ICES-003, MEPS, PSB, E-standby, KC	
HDMI ports quantity	2	EasyRead mode	✓
HDMI version	2.0	LowBlue mode	✓
DisplayPorts quantity	1	Compliance certificates	RoHS
DisplayPort version	1.4	Mean time between failures (MTBF)	50000 h
Audio output	✓	Recycling data	
HDCP	✓	Post-consumer recycled plastic	85%



8712581805838

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-DEC-2024. Prints or copies of Information are only valid on the printed Publication date