PHILIPS

Philips 273B9/00 LED display 68,6 cm (27") 1920 x 1080 Pixel Full HD LCD Nero

Marchio : Philips

Codice prodotto: 273B9/00

Nome del prodotto : 273B9/00

273B9 Monitor LCD con USB-C

Philips 273B9/00 LED display 68,6 cm (27") 1920 x 1080 Pixel Full HD LCD Nero:

Il monitor Philips B-Line con docking USB-C evita l'ingombro dei cavi. Visualizza le immagini in qualità Full HD e ricarica il tuo laptop, tutto con un singolo cavo USB-C. La base SmartErgo, le immagini prive di sfarfallio e l'impostazione LowBlue Mode sono ideali per lavorare senza affaticare gli occhi. Philips 273B9/00. Dimensioni diagonale schermo: 68,6 cm (27"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Superficie display: Opaco, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Altoparlanti incorporati. Montaggio standard VESA, Regolazione altezza. Colore del prodotto: Nero





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time * Display surface Anti-glare screen Screen shape * Supported graphics resolutions Supported video modes Aspect ratio Contrast ratio (typical) * Contrast ratio (dynamic) Dynamic contrast ratio marketing name	68.6 cm (27") 1920 x 1080 pixels Full HD 16:9 LCD IPS W-LED × 250 cd/m ² 4 ms Matt ✓ Flat 1920 x 1080 (HD 1080) 1080p 16:9 1000:1 5000000:1 SmartContrast	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot angle Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD) On Screen Display (OSD) languages Number of OSD languages Plug and Play	 100 x 100 mm Kensington Kensington 15 cm -90 - 90° -175 - 175° -5 - 30° Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian 21
Maximum refresh rate *	75 Hz	LED indicators	Operation, Stand-by
Viewing angle, horizontal	178°	Power	
Viewing angle, vertical Display number of colours * Pixel pitch Pixel density Horizontal scan range Vertical scan range Viewable size, horizontal	178° 16.7 million colours 0.3114 x 0.3114 mm 82 ppi 30 - 85 kHz 48 - 75 Hz 59.8 cm	Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (off) Power consumption (PowerSave)	E 21 kWh 16.5 W 0.5 W 0 W 13.5 W

DisplayPermPermWeakle size, vertical33.6 (m)Aling valage10 - 24.9 VDigital vertical frequency30.8 5 kileAling valage50.60 NzDigital vertical frequency48.5 GEncry efficiency scaleA to GDisplay digonal interici.68.6 (m)Encry efficiency scaleA to GSarface handres378.6Operating temperature (F1)0.40 °CColor gamal, standradi885.8Operating temperature (F1)0.40 °CColor gamal, standradi885.8Storage temperature (F1)0.40 °CColor gamal, standradi98.6Storage temperature (F1)0.40 °CColor gamal, standradi98.6Storage temperature (F1)0.40 °CSafe to energy forgical98.6Storage temperature (F1)0.40 °CSafe to energy forgical98.6Storage temperature (F1)0.40 °CDisplay stilla78.6Storage temperature (F1)0.40 °CSafe to energy forgical98.6Storage temperature (F1)0.40 °CDisplay stilla78.6Storage temperature (F1)0.40 °CSafe to energy forgical98.6Storage temperature (F1)0.40 °CNilla CoSNC*XWeage temperature (F1)0.40 °CSafe to energy forgical98.6Storage temperature (F1)0.40 °CSafe to energy forgicalStorage temperature (F1)0.40 °C0.40 °CSafe to energy forgicalStorage temperature (F1)0.40 °C0.40 °CSafe to energy forgicalStorage temperature (F1)				
DiplicationSole of Safe and Sa	Display		Power	
Diplay digonal (methic)43.75 kindPower supply diplayInternalDisplay digonal (methic)27%Singregan Product Registry for Display diagonal (methic)37.865Haze rate25%Operating temperature (TT)0.40 °CColour gamut standardRIGBOperating temperature (TT)0.40 °CColour gamut standard876Operating temperature (TT)0.40 °CColour gamut standard76%Operating distude0.20 60°CSKG coverage (typica)76%Operating distude0.20 60°CNDK Coverage (typica)76%Operating distude0.20 60°CDisplay sKG76%Operating distude0.20 60°CCoverage (typica)76%Operating distude0.20 60°CNDK Coverage (typica)76%Operating distude0.21 292 mCoverage (typica)76%With (with stand)55 mmCompaner uidea syncSparing sync, Syncon-greenHeight (with stand)55 mmCompaner uidea sync70 CPocking distand60 mmNomber of spacefist70 CPocking distand60 mmNomber of spacefist70 CPocking distand50 mmBuiltin spacefist)20 CPocking distand50 mmBuiltin spacefist)20 CPocking distand50 mmBuiltin spacefist)20 CPocking distand50 mmBuiltin spacefist)20 CPocking distand50 mmBuiltin spacefist)810 CPocking distand50 mmBuiltin spacefist)810 C<	Viewable size, vertical	33.6 cm	AC input voltage	100 - 240 V
<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>	Digital horizontal frequency	30 - 85 kHz	AC input frequency	50 - 60 Hz
DCC_ InscriptionProduct Registry of Breny Labeling (Figure) series (Figure) Series (Figure)Signal Schule Series (Figure)Signal Schule SchuleSignal Schule SchuleSignal Schule SchuleSignal Schule SchuleSignal Schule SchuleSignal Schule SchuleSignal Schule <td>Digital vertical frequency</td> <td>48 - 75 Hz</td> <td>Power supply type</td> <td>Internal</td>	Digital vertical frequency	48 - 75 Hz	Power supply type	Internal
Hater Instruct adminSymbolDerroy Labeling (ERREL) codeSymbolSurdac hardness3H3Operation plating tamperature (T-T)0.4 °C °CColour gamut Standard9K3Storage temperature (T-T)0.4 °C °CSGR coverage (typical)9K9Operating tarbies humidity (H+)0.4 °CDiplay SGR coverage (typical)7K9Storage temperature fait-the munidity (H+)0.4 °CDiplay SGR coverage (typical)7K9Operating tarbies humidity (H+)0.4 °CDiplay SGR coverage (typical)7K9Operating tarbies humidity (H+)0.4 °CNVDIA CSYNC*XWidd (with stand)0.4 °CADD FreeSyncSparate SynC. SyncorageeWeight (with stand)0.3 °CComponent video syncSparate SynC. SyncorageeWeight (with stand)0.3 °CNUDE Coverage (typical)YDepth (without stand)0.1 °mRicker-free technologyYDepth (without stand)0.1 °mSindeo DavidPactage depth0.0 °CMinoSindeo DavidYDepth (without stand)0.1 °mSindeo DavidYDepth (without stand)0.1 °mSindeo DavidPactage depth0.0 °CMinoSindeo DavidYDepth (without stand)0.1 °mSindeo DavidYDepth (without stand)0.1 °mSindeo DavidYDepth (without stand)0.1 °mSindeo DavidYDepth (without stand)0.1 °mSindeo DavidYDepth (without stand)0.1 °mSin	Display diagonal (metric)	68.6 cm	Energy efficiency scale	A to G
Hate rate25%Energy Latening Lenkel, YoldsStriker hardnes9HOperational conditionsColour genut9K08Operational conditionsStriker hardnes9K08Operation grader hardnesStriker hardnes9K9Operation grader hardnesStriker hardnes9K9Operation grader hardnesStriker hardnes7K9Stringe relative humidaty (HH)21.48%Striker hardnes7K9Operating affande modily (HH)21.48%Striker hardnes7K9Operating affande modily (HH)21.48%Striker hardnes7K9Operating affande modily (HH)21.48%Striker hardnesXWidh (with string)22.41 mmNUDIA GSYNC*XWidh (with string)22.41 mmABD freeSyncScaratic synce-opera (SGG)Peth (with string)7.03 kgADD freeSyncScaratic synce-opera (SGG)Operative striker61.41 mmComponent video syncScaratic synce-opera (SGG)Operative striker7.03 kgRicker-free technology4Peth (without string)7.03 kgVoribut Euglite technology4Peth (without string)6.01 mmStriker free technology2Peth (without string)6.00 mmBuilt-in speaker(S)*Scaratic synce-opera (SGG)Operative striker7.03 kgNumber of speakersScaratic synce-opera (SGG)Scaratic synce-opera (SGG)Scaratic synce-opera (SGG)Built-in speaker(S)*Scaratic synce-opera (SGG)Scaratic synce-opera (SG	DDC/CI	1		337905
Solar gamut standard Colour gamut Standard96G 96G 1096 1096 1097Operating relative trumer (T-T) 20-60°. 20-80%.<	Haze rate	25%	Energy Labelling (EPREL) code	
Color ganut.76%Storage temperature (T.T.)20 - 60 °C3KGB coverage (typical)96%Operating relative humidity (H+)20 - 80%NFSC coverage (typical)77%Operating relative humidity (H+)20 - 80%Display sRGBOperating relative humidity (H+)20 - 80%PerformanceNon-operating influed0 - 3658 m.ND/DA C-SYNC*XWeight (with stand)614 mmAMD FreeSync *XWeight (with stand)614 mmComponent video syncSeparate sync, Sync-on-green (SOG)Weight (with stand)558 mmVESA Adaptive Sync Sync-on-green (SOG)Veight (with stand)614 mmWeight (with stand)614 mm614 mmLow Bue Light technologyPerchage depth327 mmWeight (with stand)614 mm614 mm614 mmLow Bue Light technologyPerchage depth327 mmWeight (with stand)230 mm327 mmMmBuilt-in speakers2Perchage depth33 NgBuilt-in speakers2Perchage depth230 mmBuilt-in speakers2Perchage depth33 NgBuilt-in speakers2Perchage depth3Built-in speakers2NgNgBuilt-in s	Surface hardness	3H	Operational conditions	
sKGE coverage (typical)98% 00 00 pertaing relative humidity (H)20 00 20 00 00 pertaing altitude20 00 00 00 pertaing altitude20 000 00 pertaing altitude20 000 00 pertaing altitude20 000 pertaing altitude20 <td>Colour gamut standard</td> <td>sRGB</td> <td>Operating temperature (T-T)</td> <td>0 - 40 °C</td>	Colour gamut standard	sRGB	Operating temperature (T-T)	0 - 40 °C
NTSC overage (typical)76%Storage relative humidity (H-M)0 - 80%Display sRGB0 - 60%0 - 80%Display sRGB0 - 12192 mNUDA G-SYNC*XNon-sperating altude0 - 12192 mNUDA G-SYNC*XWidth (with stand)0 - 12192 mADD FreeSync*XWidth (with stand)224 mmComponent vides syncSeparate sync, Sync-on-green(wight (with stand)234 mm(SAA dagtive Sync syncor)GoodDepth (without stand)61 mmLow Blue Light technology-Peckage with61 mmLow Blue Light technology2Peckage with60 mmNumber of speakers2Peckage with60 mmBuilch speakers2Peckage with9.3 kgBuilch speakers2Peckage with per pack1c/(s)FrenceisoBackQuanty per pack1c/(s)Protoce clouv*BackQuanty per pack1c/(s)Protoce clouv*Builder Softman1c/(s)1c/(s)Protoce clouv*BackSundincloud4cProtoce clouv*BackSundincloud4cProtoce clouv*BackSundincloud4cProtoce clouv*BackSundincloud4cProtoce clouv*BackSundinc	Colour gamut	76%	Storage temperature (T-T)	-20 - 60 °C
Display sRd·Operating altitude0- 3658 m 0PerformanceNon-operating altitude0- 3658 m 0WDIA G-SYNC *XWeight dimensions0ADD FreeSync *XDepth (with stand)614 mm 0ADD FreeSync *Segarate sync, Sync on-greenHeight (with stand)538 mm 	sRGB coverage (typical)	98%	Operating relative humidity (H-H)	20 - 80%
PerformanceNan-operating altitude0 - 22192 mNVDIA GSYNC*XWeight of dimensionsAMD FreeSync *XWidth (with stand)54 mmVSBA Adaptive Sync supportSeparate sync, Sync-on-green (SGG)Width (with stand)53 mmComponent video syncSeparate sync, Sync-on-green (SGG)Weight (with stand)61 mmLow Blue Light technology-Weight (with stand)61 mmLow Blue Light technology-Weight (with stand)61 mmLow Blue Light technology-Weight (with stand)61 mmMultimedia-Weight (with stand)61 mmNumber of speakers2Package weight600 mmBuilch speakers(s)Package height462 mmBuilch speakers(s)-Package weight600 mmBuilch speakers(s)NamePackage weight462 mmPoduct colourBlackQuantity per pack1 pc(s)Product colourBlackStand included+Product colourBlackStand included+Portes clourBlackSustainability certificatesMeCinptiBuilt in Speartem ports1Cables included+Number of speartem ports1Stand included+Start setter-Sustainability certificatesNCBORY STAR, TCOStart setter-Sustainability certificatesNCBORY STAR, TCOStart setter-Sustainability certificatesNCBORY STAR, TCOStart setter- <td< td=""><td>NTSC coverage (typical)</td><td>76%</td><td>Storage relative humidity (H-H)</td><td>20 - 80%</td></td<>	NTSC coverage (typical)	76%	Storage relative humidity (H-H)	20 - 80%
Permande Viella 6.s''NC.* X Viella 6.s''NC.* X AMD FreeSync.* × Widh (with stand) 54 arm VESA Adaptive Sync support Separate sync, Sync-on-green (SoG) Depth (with stand) 538 mm Component video sync Separate sync, Sync-on-green (SoG) Width (with stand) 538 mm Component video sync Separate sync, Sync-on-green (SoG) Width (with stand) 518 mm Component video sync Separate sync, Sync-on-green (SoG) Width (with stand) 518 mm Component video sync Video sync Sign mm Sign mm Row Blue Light technology Video sync Sign mm Sign mm RW Stade popt Z Package wideo sync Sign mm RW Stade popt Z Package weight Sign mm Built-In speaker(S)* Z Package weight Sign mm Built-In speaker(S)* Package weight Sign mm Sign mm Portact colour* Black Ancel postioning * Sign mm Sign mm Praneless design X Statin fucked Package weigh	Display sRGB	1	Operating altitude	0 - 3658 m
Number of specific extensionA definition614 mmVESA Adaptive Sync support×Papth (with stand)214 mmComponent vides syncSeparate sync, Sync-on-green (SOG)Height (with stand)7.3 kgFilcker-free technology×Papth (with stand)614 mmLow Blue Light technology×Papth (with stand)614 mmMutimedia-Papth (with stand)614 mmLow Blue Light technology×Papth (without stand)61 mmMutimedia-Papth (without stand)322 mmMutimedia-Weight (without stand)459 kgBuilt-in speakers2Package depth250 mmBuilt-in speakers(s)×Package depth250 mmBuilt-in camera×Package depth250 mmBuilt-in speakers(s)×Package depth30 mmBuilt-in speakersBusinesPackage typeBoxPackage typeBackVariationingBackProtate colourBlackStand included×Portate colourBlackStand included×Porta scienceBlackStand include×Porta scienceStand included×Stand include×Stand i	Performance		Non-operating altitude	0 - 12192 m
AND FreeSync*×Width (with stand)624 mmVESA Adaptive Sync supportSeparate sync, Sync-on-greeDepth (with stand)528 mmComponet video syncSeparate sync, Sync-on-greeWidth (without stand)614 mmComponet video syncSeparate sync, Sync-on-greeWidth (without stand)614 mmElikar-free technologyUmDepth (without stand)614 mmLow Blue Light technologyDepth (without stand)61 mmSynce Synce S	NVIDIA G-SYNC *	×	Weight & dimensions	
VEA Adaptive Sync supportPerth (with stand)24 mmComponent video syncSegarate sync, Sync-on-green (SOC)Height (with stand)58 mmFilcker-free technologyIMelth (without stand)61 mmLow Bue Light technologyIDepth (without stand)61 mmLow Bue Light technologyIDepth (without stand)61 mmMutimediaIWeight (without stand)372 mmMutimediaIWeight (without stand)690 mmNumber of speakers2Package depth690 mmBuilt-in carred2Package depth462 mmBuilt-in carredIPackage height462 mmBuilt-in carredBiakcQuantity pracka1 pc (Sig)Product colourBiackQuantity pracka1 pc (Sig)Product colourBiackStan includedIProtect colourBiackStan includedIProtect colourBiackStan includedIProtect colourBiackStan includedVProtect colourStarpe-C Signific certific ceri			Width (with stand)	614 mm
Begarate sync. Sync.on-green (SOG)Begarate sync. Sync.on-green (SOG)Heijht (with stand)5.8 mmFicker-free technology <td< td=""><td>,</td><td></td><td>Depth (with stand)</td><td>224 mm</td></td<>	,		Depth (with stand)	224 mm
Consident video sync. (SGG)SGGValue (With without stand)(Job RgFlicker-free technology<	VESA Adaptive Sync support			558 mm
Filcker-free technology · · · · · · · · · · · · · · · · · · ·	Component video sync			7.03 kg
Low Blue Light Lechnology	Flicker-free technology		Width (without stand)	614 mm
Height (without stand)372 mmMultimediaWeight (without stand)4,55 kgNumber of speakers2Packaging dataRNS rated power2 WPackage keight690 mmBullt-in camera*XPackage keight452 mmBullt-in speaker(s)*XPackage height452 mmBullt-in camera*XPackage keight9.3 kgDesignVPackage height9.3 kgMarket positioning*BusinessQuantity per pack1.pc(s)Product colour*BlackQuantity per pack1.pc(s)Frameless designXPackaging content		-	Depth (without stand)	61 mm
Number of speakers2Package width640 spRMS rated power2 WPackage width690 mmBuilt-in speaker(s)*4Package width690 mmBuilt-in speaker(s)*×Package width250 mmBuilt-in speaker(s)*XPackage width9.3 kgDesignWarket positioning*BusinessPackage typeBoxMarket positioning*BlackQuantity per pack1 pc(s)Product colour*BlackStand includedProduct colour*BlackStand includedPorts Sect colourBlackStand includedDetachable standCables includedMIN, DisplayPort, USB Type-C, ACFeet colourBlackManualPorts & interfacesBuilt-in USB hub*XSustainability certificatesBuilt-in USB hub*XSustainability certificatesENERGY STAR, TCOUSB type-C downstream ports1Desent containPVC/BFR, MercuryUSB type-C downstream ports1USB Power Delivery revision3.0USB Power Delivery (USB PD)Verture onhancementSnartImageUSB Power Delivery (USB PD)NearcetterCerturesUSB Power Delivery upton65 WRecyclabe packagin gnaterial100%USB Power Delivery upton65 WRegulatory ApprovalsCEN Arit; FCC Class B; SEMKO; CU-EAC; TUV/GS; TUV Ergo; EPA; UKMIAN; ICES-DRIS; ESK, EPA; UKMIAN; ICES-DRIS; ESK, EPA; UKMIAN; ICES-DRIS; ESK, EPA; UKMIAN; ICES-DRIS; ESK, EPA; UKMIAN; ICES-	Low Blue Light technology	•	Height (without stand)	372 mm
RMS rated power 2 W Package width 990 nm Built-in speaker(s)* Package depth 250 nm Built-in camera* Package depth 250 nm Built-in camera* Package height 462 nm Built-in camera* Built-in camera* Backage weight 3 kg Market positioning* Built-in camera* Backage weight 3 kg Product colour* Black Quantity per pack 1 pc(s) Frameless design X Package indige content Frameless design Front bezel colour Black Manual Detachable stand A Sustainability certificates ENERGY STAR, TCO Built-in USB hub* X Sustainability certificates ENERGY STAR, TCO Number of upstream ports 1 Other features Entured USB sporem port type USB Packaging material 10% Social-ABBIR USB power Delivery (USB PD) Package weight 8.0 Socian-Camera USB Power Delivery	Multimedia		Weight (without stand)	4.59 kg
Built-in speaker(s)* Package windth 690 mm Built-in camera* X Package depth 250 mm Built-in camera* X Package windth 462 mm Built-in camera* X Package windth 462 mm Built-in camera* Buisness Package windth 9.3 kg Market positioning * Buisness Quantity per pack 1 pc(s) Product colour Black Quantity per pack 1 pc(s) Frameless design X Stand included / Petcachable stand / Annual / Petcachable stand X Manual / Built-in USB hub* X Sustainability Sustainability certificates ENERGY STAR, TCO Number of upstream ports 1 Sustainability certificates ENERGY STAR, TCO Number of upstream ports 1 Sustainability certificates ENERGY STAR, TCO Number of upstream ports 1 Sustainability certificates ENERGY STAR, TCO Sustainability certificates Sustainability certificates	·		Packaging data	
Bulli-in camera* Yeakage height 250 mm Design Package height 432 mm Market positioning * Business Package keight 432 mm Product colour* Black Package type Box Frameless design X Packaging content Ipcls) Front bezel colour Black Stand included IPDM, DisplayPort, USB Type-C, AC Feet colour Black Manual SmartControl Detachable stand IPOM Section Stand Included IPOM Section Stand Included SmartControl Ditl:in USB hub * X Sustainability certificates SmartControl USB type-C downstream ports 1 Desent contain PVC/BFR, Mercury USB Type-C downstream ports 1 Stand Foreiures Smart Control USB Speer Delivery (USB PD) IPOM Section Stand Stand Instance Smart Control Smart Control USB Power Delivery (USB PD) IPOM Section Stand Stand Instance Smart Control Smart Control USB Power Delivery (USB PD) IPOM Section Stand Stand Instance Smart Control Smart Control <t< td=""><td>RMS rated power</td><td>2 W</td><td>Package width</td><td>690 mm</td></t<>	RMS rated power	2 W	Package width	690 mm
DesignPackage regint92 kage regint	Built-in speaker(s) *	✓	Package depth	250 mm
Market positioning* Business Package type Box Market positioning* Black Quantity per pack 1 pc(s) Frameless design X Packaging content I pc(s) From bezel colour Black Stand included ✓ Detachable stand ✓ Cables included HDMI, DisplayPort, USB Type-C, AC Feet colour Black Manual ✓ Ports & interfaces Bundled software SmartControl Built-in USB hub* X Sustainability certificates ENERGY STAR, TCO SW upstream port type USB Type-C footsingtem ports 1 Desn't contain 9////////////////////////////////////	Built-in camera *	×	Package height	462 mm
Market positioningBusinessPackage typeBoxProduct colourBlackQuantity per pack1 pc(s)Frameless designXPackaging contentFront bezel colourBlackStand includedHDMI, DisplayPort, USB Type-C, ACDetachable stand-Cables includedHDMI, DisplayPort, USB Type-C, ACFeet colourBlackManual-Ports & interfacesBundled softwareSmartControlBuilt-in USB hub*XSustainability certificatesENERGY STAR, TCOBuilt-in USB hub*XSustainability certificatesENERGY STAR, TCOVumber of upstream ports1Doesn't containPVC/BR, MercuryUSB Type-C downstream ports1USB Power Delivery revision3.0USB Type-C DisplayPort Alternat Mode-Exterior finish typeTexturedUSB Power Delivery up to G5 WG5 WRecyclable packaging material100%USB Power Delivery up toG5 WRecyclable packaging material100%USB Power Delivery up toAHeavy metals freeHg (mercury)HDMI orts quantity1Heavy metals freeHg (mercury)HDMI version1.4Compliance certificatesWEEE, RoHSAudio inputCertificationCE Mark, FCC Class B, SEMKO, CU- EAC, TUVGS, TUV Ergo, EPA, UKRAINANI, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CBHDMI ports quantity1LowBlue mode-HDMI version1.4Compliance certificatesWEEE, RoHSAud	Design		Package weight	9.3 kg
Product colour *BlackQuantity per pack1 pc(s)Frameless design×Ackaging contentFrom bezel colourBlackStand included/Detachable standCables includedHDMI, DisplayPort, USB Type-C, ACFeet colourBlackManualPorts & interfacesBundled softwareSmartControlBuilt-in USB hub*×Sustainability certificatesFNERGY STAR, TCOBuilt-in USB hub*×Sustainability certificatesFNERGY STAR, TCOSub upstream port typeUSB Type-C converteram ports1Oesn't containPO/C/BR, MercuryUSB Type-C converteram ports1USB Power Delivery revision3.0USB Type-C biplayPort Alterner Mode-SmartImage0.0USB Power Delivery (USB PD)Picture enhancementSmartImageUSB Power Delivery (USB PD)Picture enhancement3.0USB Power Delivery up to65 WRecyclable packaging material100%USA (D-Sub) ports quantity1Regulatory ApprovalsCE Mark; FCC Class B; SEMKO; CU- RCM, VCCI; PSB; CBHDMI ports quantity1LowBlue mode<	-	Business	Package type	Box
Frameless design×Peckaging contentFront bezel colourBlackStand included✓Detachable stand✓Gables includedHDMI, DisplayPort, USB Type-C, ACFeet colourBlackManual✓Ports cinterfacesBundled softwareSmartControlBuiltin USB hub*×Sustainability certificatesENERGY STAR, TCONumber of upstream ports1Desent containPVC/BFR, MercuryUSB Type-C downstream ports1Other featuresSustainability certificatesShERGY STAR, TCOUSB Type-C DisplayPort Alternate Mode✓Statinability certificatesSoftwareSoftwareUSB Power Delivery (USB PD)✓Other featuresIntervention3.0USB Power Delivery (USB PD)✓Picture enhancementSmartlmageUSB Power Delivery (USB PD)✓Picture enhancementSmartlmageUSB Power Delivery up to65 WRecyclable packaging material100%USA power Delivery up to1Exercior finish typeEd Mark, FCC Class B; SEMKO; CU- EAC; TUV/GS; TUV Ergo; EPA; UKANINAN; (ESC-003; PSE; MEPS; RCH; VCCI; PSE; CBHDMI •✓IIIDisplayPort squantity1IIHDMI ports quantity1IIHDMI ports quantity1IIDisplayPort version1.2Compliance certificatesVEEE, ROHSDisplayPort version1.2Compliance certificatesVEEE, ROHSAddio input✓I			Quantity per pack	1 pc(s)
Detachable stand✓Cables includedHDM, DisplayPort, USB Type-C, ACFeet colourBlackManual✓Ports & interfacesBundled softwareSmartControlBuilt-in USB hub *XSustainabilityENERGY STAR, TCOUSB upstream port typeUSB Type-CSustainability certificatesENERGY STAR, TCONumber of upstream ports1Deesn't containPVC/BR, MercuryUSB Type-C bisplayPort Alternate Mode✓Statinability certificates3.0USB Type-C DisplayPort Alternate Mode✓Picture enhancementSnartfinageUSB Power Delivery (USB PD)✓Picture enhancementSnartfinageUSB Power Delivery up to65 WRecyclable packaging material100%USA (D-Sub) ports quantity1EasyRead mode✓UMII*✓KacyMeanuel freeMeanuel Meanuel			Packaging content	
Feet colour Black Manual Image: Construction of the	Front bezel colour	Black	Stand included	1
Feet colour Black Manual Manual Ports & interfaces Bundled software SmartControl Built-in USB hub* X Sustainability ENERGY STAR, TCO USB upstream port type USB Type-C Sustainability certificates ENERGY STAR, TCO Number of upstream ports 1 Desn't contain PVC/BFR, Mercury USB Type-C downstream ports 1 USB Power Delivery revision 3.0 VSB Type-C downstream ports - USB Power Delivery revision 3.0 USB Power Delivery (USB PD) - Picture enhancement SmartImage USB Power Delivery up to 65 W Recyclable packaging material 100% USA (D-Sub) ports quantity 1 Expression Expression Expression HDMI version 1.4 EasyRead mode - EXpression Fillenencement Fillenencement JosplayPort version 1.4 EasyRead mode - EXpression Fillenencement Fillenencement Fillenencement Fillenencement Fillenencement Fillenenconconcement Filenencement	Detachable stand	1	Cables included	HDMI, DisplayPort, USB Type-C, AC
Ports & interfacesBundled softwareSmartControlBuilt-in USB hub*×SustainabilityENERGY STAR, TCOUSB upstream port typeUSB Type-CSustainability certificatesENERGY STAR, TCONumber of upstream ports1Doesn't containPVC/BFR, MercuryUSB Type-C downstream ports1Other featuresSustainability certificatesENERGY STAR, TCOUSB Type-C downstream ports1Other featuresSustainability certificates3.0USB Pope-C DisplayPort Alternate Mode~StartingeTexturedUSB Power Delivery (USB PD)✓Picture enhancementSmartImageUSB Power Delivery (USB PD)✓Recyclable packaging material100%VGA (D-Sub) ports quantity1Regulatory ApprovalsCE Mark; FCC Class B; SEMKO; CU- EAC; TUV/GS; TUV Ergo; EPA; UKRNINAN; ICES-003; PSE; MEPS; RCM; VCCI (SPS B; CBHDMI version1.4LowBlue mode✓DisplayPort squantity1.2Compliance certificatesWEEE, RoHSAudio input✓AmantCompliance certificatesWEEE, RoHSAudio input1CertificationEt RARK, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS; RCM; VCCI (SPS B; CBHeadphone out *✓CertificationEt RARK, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI (SPS, CBHeadphone out *✓CertificationEt RARK, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI	Feet colour	Black	Manual	
Built-in USB hub*×SustainabilityUSB upstream port typeUSB Type-CSustainability certificatesENERGY STAR, TCONumber of upstream ports1Doesn't containPVC/BFR, MercuryUSB Type-C downstream ports1Other features	Ports & interfaces			SmartControl
Distances into the period by		×	Sustainability	
Number of upstream ports quantity1Doesn't containPVC/BFR, MercuryUSB Type-C downstream ports quantity1Other features3.0USB Type-C DisplayPort Alternate Mode-USB Power Delivery revision3.0USB Power Delivery (USB PD)-Exterior finish typeTexturedUSB Power Delivery (USB PD)-Picture enhancementSmartImageUSB Power Delivery up to65 WRecyclable packaging material100%USP ower Delivery up to65 WRecyclable packaging material100%VGA (D-Sub) ports quantity1CE Mark; FCC Class B; SEMKO; CU- EAC; TUV/GS; TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCC1; PSB; CBHDMI *HDMI ports quantity1LowBlue mode-HDMI version1.4EasyRead mode-DisplayPort version1.2Compliance certificatesWEEE, RoHSAudio input-Mean time between failures (MTBF)70000 hHeadphone out *-CE Mark, FCC Class B, SEMKO; CU- EAC, TUV/GS, TUV Ergo; EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCC1, PSB, CBCE Mark, FCC Class B, SEMKO; CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCC1, PSB, CBHeadphone out *Headphone connectivity3.5 mmCE Mark, FCC Class B, SEMKO; CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCC1, PSB, CB-PC Audio inHDCP <tr< td=""><td></td><td></td><td></td><td>ENERGY STAR TCO</td></tr<>				ENERGY STAR TCO
USB Type-C downstream ports quantity1Other featuresUSB Type-C DisplayPort Alternate ModeUSB Power Delivery revision Exterior finish type3.0USB Power Delivery (USB PD)Exterior finish typeTexturedUSB Power Delivery (USB PD)SmartlmageUSB Power Delivery (USB PD)SmartlmageUSB Power Delivery up to65 WRecyclable packaging material100%USB Power Delivery up to65 WRecyclable packaging material100%UVGA (D-Sub) ports quantity1CE Mark; FCC Class B; SEMKO; CU- EAc; TUV/GS; TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBHDMI *Heavy metals freeHg (mercury)HDMI version1.4EasyRead modeDisplayPorts quantity1LowBlue modeDisplayPort version1.2Compliance certificatesWEEE, RoHSAudio inputMean time between failures (MTBF)70000 hHeadphone out *CertificationUKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CBPC Audio inRecycling dataHDCPPost-consumer recycled plastic85%			,	,
quantityIOther reactivesUSB Type-C DisplayPort Alternate Mode.0.0ModeExterior finish type.0USB Power Delivery (USB PD)USB Power Delivery up to65 WRecyclable packaging material.00%VGA (D-Sub) ports quantity1DVI portXHDMI*HDMI *HDMI *Compliance certificatesHeadphone out *Headphone connecti	1 1			
Body System Display of ArterinateExterior finish typeTexturedModeExterior finish typeTexturedUSB Power Delivery (USB PD)Picture enhancementSmartImageUSB Power Delivery up to65 WRecyclable packaging material100%VGA (D-Sub) ports quantity1CE Mark; FCC Class B; SEMKO; CU-EAC; TUV/GS; TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBHDMI *Heavy metals freeHg (mercury)HDMI version1.4EasyRead modeDisplayPort version1.2Compliance certificatesWEEE, RoHSAudio inputMean time between failures (MTB)70000 hHeadphone out *CertificationCE Mark, FCC Class B, SEMKO, CU-EAC; TUV/GS, TUV Ergo, EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBHeadphone out * </td <td></td> <td>1</td> <td></td> <td>2.0</td>		1		2.0
USB Power Delivery (USB PD)Picture enhancementSmartImageUSB Power Delivery up to65 WRecyclable packaging material100%VGA (D-Sub) ports quantity1Regulatory ApprovalsE Mark; FCC Class B; SEMKO; CU- EAC; TUV/GS; TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBHDMI *Heavy metals freeHg (mercury)HDMI version1.4EasyRead modeDisplayPorts quantity1LowBlue modeDisplayPort version1.2Compliance certificatesWEEE, RoHSAudio inputMean time between failures (MTBF)70000 hHeadphone out *CertificationCE Mark; FCC Class B, SEMKO, CU- EAC; TUV/GS; TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBPC Audio in </td <td></td> <td> Image: A set of the set of the</td> <td>•</td> <td></td>		 Image: A set of the set of the	•	
USB Power Delivery up to65 WRecyclable packaging material100%VGA (D-Sub) ports quantity1Aggulatory ApprovalsCE Mark; FCC Class B; SEMKO; CU-EAC; TUV/GS; TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBHDMI *Heavy metals freeHg (mercury)HDMI version1.4EasyRead modeDisplayPorts quantity1LowBlue modeDisplayPort version1.2Compliance certificatesWEEE, RoHSAudio inputMean time between failures (MTBF)70000 hHeadphone out *CertificationCE Mark, FCC Class B, SEMKO, CU-EAC; TUV/GS, TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBPC Audio in </td <td></td> <td>1</td> <td></td> <td></td>		1		
VGA (D-Sub) ports quantity1Regulatory ApprovalsCE Mark; FCC Class B; SEMKO; CU- EAC; TUV/GS; TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBHDMI *HDMI ports quantity1Heavy metals freeHg (mercury)HDMI version1.4EasyRead modeDisplayPorts quantity1LowBlue modeDisplayPort version1.2Compliance certificatesWEEE, RoHSAudio inputMean time between failures (MTBF)70000 hHeadphone out *CertificationCE Mark, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CBPC Audio inRecycling dataHDCPPost-consumer recycled plastic85%				5
DVI portXRegulatory ApprovalsEAC; TUV/GS; TUV Ergo; EPA; UKRAINIAN; ICES-003; PSE; MEPS; RCM; VCCI; PSB; CBHDMI *HDMI ports quantity1Heavy metals freeHg (mercury)HDMI version1.4EasyRead modeDisplayPorts quantity1LowBlue modeDisplayPort version1.2Compliance certificatesWEEE, RoHSAudio inputMean time between failures (MTBF)70000 hHeadphone out *CertificationCE Mark, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo; EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM; VCCI, PSB, CBPC Audio in </td <td></td> <td></td> <td>Necyclable packaging matchai</td> <td></td>			Necyclable packaging matchai	
HDMI *Image: constraint of the part of th			Regulatory Approvals	
HDMI ports quantity1Heavy metals freeHg (mercury)HDMI version1.4EasyRead modeDisplayPorts quantity1LowBlue modeDisplayPort version1.2Compliance certificatesWEEE, RoHSAudio inputMean time between failures (MTBF)70000 hHeadphone out *CertificationCE Mark, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CBPC Audio inRecycling dataHDCPPost-consumer recycled plastic85%			Negulatory Approvais	
HDMI ports quantity1EasyRead modeImage: Complex ports quantityDisplayPorts quantity1LowBlue modeImage: Complex ports quantityDisplayPort version1.2Compliance certificatesWEEE, RoHSAudio inputImage: Complex port quantityImage: Complex port quantityImage: Complex port quantityHeadphone out *Image: Complex port quantityImage: Complex port quantityImage: Complex port quantityHeadphone out *Image: Complex port quantityImage: Complex port quantityCertificationCertificationHeadphone connectivity3.5 mmCertificationCertificatasKecycling dataPC Audio inImage: Complex port quantityImage: Complex port quantityStore port quantityHDCPImage: Complex port quantityStore port quantityStore port quantityImage: Complex port quantityImage: Complex port quantityStore port quantityPost-consumer recycled plasticStore port quantityStore port quantity		-	Heavy metals from	
DisplayPorts quantity1LowBlue mode✓DisplayPort version1.2Compliance certificatesWEEE, RoHSAudio input✓Mean time between failures (MTBF)70000 hHeadphone out *✓✓CertificationCE Mark, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CBHeadphone connectivity3.5 mmRecycling dataHDCP✓Post-consumer recycled plastic85%			-	
DisplayPort version1.2Compliance certificatesWEEE, RoHSAudio input✓Mean time between failures (MTBF)70000 hHeadphone out *✓CertificationCE Mark, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CBHeadphone connectivity3.5 mmRecycling dataPC Audio in✓Recycling dataHDCP✓Post-consumer recycled plastic85%				-
Audio input✓Mean time between failures (MTBF)70000 hHeadphone out *✓CertificationCE Mark, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CBHeadphone connectivity3.5 mmRecycling dataPC Audio in✓Recycling dataHDCP✓Post-consumer recycled plastic				-
Headphone out * ✓ ✓ Certification CE Mark, FCC Class B, SEMKO, CU- EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CB PC Audio in ✓ Recycling data HDCP ✓ Post-consumer recycled plastic 85%			•	
Headphone outputs 1 Certification EAC, TUV/GS, TUV Ergo, EPA, UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CB PC Audio in ✓ Recycling data HDCP ✓ Post-consumer recycled plastic 85%	·		Mean time between failures (MTBF)	
Headphone outputs I Certification UKRAINIAN, ICES-003, PSE, MEPS, RCM, VCCI, PSB, CB PC Audio in ✓ Recycling data HDCP ✓ Post-consumer recycled plastic 85%	•			
PC Audio in Image: Market Audio and			Certification	
HDCP Post-consumer recycled plastic 85%				RCM, VCCI, PSB, CB
Fost-consumer recycled plastic 65%			Recycling data	
HDCP version 1.4			Post-consumer recycled plastic	85%
	HDCP version	1.4		

Ports & interfaces		Logistics data	
DC-in jack	1	Harmonized System (HS) code	85285210



8712581764197

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.