

Philips Evnia 27M1C5200W/00 Monitor PC 68,6 cm (27") 1920 x 1080 Pixel Full HD LCD Nero

Marchio : Philips

Famiglia del prodotto: Evnia

Codice prodotto:
27M1C5200W/00

Nome del prodotto :
27M1C5200W/00



Curved Gaming Monitor 27M1C5200W Monitor da gaming Full HD

Philips Evnia 27M1C5200W/00 Monitor PC 68,6 cm (27") 1920 x 1080 Pixel Full HD LCD Nero:

Progettato per un'azione di gioco ad alta intensità, questo monitor è dotato di tecnologia Sync, una velocità di aggiornamento rapida di 240 Hz e un tempo di risposta di 0,5 ms per un'esperienza di gaming senza interruzioni. Inoltre, le immagini sono splendide grazie a SmartImage HDR.

Philips Evnia 27M1C5200W/00. Dimensioni diagonale schermo: 68,6 cm (27"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Montaggio standard VESA, Regolazione altezza. Colore del prodotto: Nero



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	VESA mounting *	✓
Display resolution *	1920 x 1080 pixels	Panel mounting interface	100 x 100 mm
HD type *	Full HD	Cable lock slot *	✓
Native aspect ratio *	16:9	Cable lock slot type	Kensington
Display technology *	LCD	Height adjustment *	✓
Panel type *	VA	Adjustable height (max)	13 cm
LED backlight	✓	Swivelling	✓
Backlight type	W-LED	Swivel angle range	-45 - 45°
Touchscreen *	✗	Tilt adjustment	✓
Display brightness (typical)	300 cd/m ²	Tilt angle range	-5 - 20°
Response time *	4 ms	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Response time measurement type	GTG (Gray to Gray)	Plug and Play	✓
Response time (MPRT)	0.5 ms	LED indicators	Operation, Stand-by
Anti-glare screen	✓		
Screen shape *	Curved	Power	
Screen curvature rating	1500R	Energy efficiency class (SDR) *	E
Contrast ratio (typical) *	3000:1	Power consumption (typical) *	23.7 W
Dynamic contrast ratio marketing name	Mega Infinity DCR	Power consumption (standby) *	0.5 W
Maximum refresh rate *	240 Hz	Power consumption (off)	0.3 W
Viewing angle, horizontal	178°	AC input voltage	100 - 240 V
Viewing angle, vertical	178°	AC input frequency	50 - 60 Hz
Display number of colours *	16.7 million colours	Power supply type	Internal
Response time (fast)	0.5 ms	Operational conditions	
Pixel pitch	0.3114 x 0.3114 mm	Operating temperature (T-T)	0 - 40 °C
Pixel density	81.59 ppi	Storage temperature (T-T)	-20 - 60 °C
Horizontal scan range	30 - 255 kHz		
Vertical scan range	48 - 240 Hz		
Viewable size, horizontal	59.8 cm		

Display		Operational conditions	
Viewable size, vertical	33.6 cm	Operating relative humidity (H-H)	20 - 80%
Display diagonal (metric)	68.5 cm	Operating altitude	0 - 3658 m
DDC/CI	✓	Non-operating altitude	0 - 12192 m
Haze rate	25%	Weight & dimensions	
Surface hardness	3H	Width (with stand)	611 mm
Colour depth	8 bit	Depth (with stand)	236 mm
sRGB coverage (typical)	121%	Height (with stand)	544 mm
NTSC coverage (typical)	98%	Weight (with stand)	5.61 kg
Display sRGB	✓	Width (without stand)	611 mm
Performance		Depth (without stand)	83 mm
NVIDIA G-SYNC *	✗	Height (without stand)	366 mm
AMD FreeSync *	✗	Weight (without stand)	4.15 kg
VESA Adaptive Sync support	✓	Packaging data	
Component video sync	Separate sync	Package width	930 mm
Flicker-free technology	✓	Package depth	188 mm
Multimedia		Package height	508 mm
Built-in speaker(s) *	✗	Package weight	10 kg
Built-in camera *	✗	Packaging content	
Design		Stand included	✓
Market positioning *	Gaming	Manual	✓
Product colour *	Black	Sustainability	
Ports & interfaces		Doesn't contain	Mercury, PVC/BFR
HDMI *	✓	Other features	
HDMI ports quantity	2	Low input lag	✓
HDMI version	2.0	Exterior finish type	Textured
DisplayPorts quantity	1	Picture enhancement	SmartImage game
DisplayPort version	1.4	Recyclable packaging material	100%
Audio output	✓	Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV/ISO9241-307; TUV-BAUART
HDCP	✓	EasyRead mode	✓
HDCP version	1.4/2.2	LowBlue mode	✓
		Mean time between failures (MTBF)	50000 h



8712581800697

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.