

Philips 3000 series 32B1U3900/00 Monitor PC 80 cm (31.5") 3840 x 2160 Pixel 4K Ultra HD LCD Nero

Marchio : Philips Famiglia del prodotto: 3000 series Codice prodotto: 32B1U3900/00

Nome del prodotto : 32B1U3900/00

Business Monitor 32B1U3900 Monitor 4K UHD con dock USB-C

Philips 3000 series 32B1U3900/00 Monitor PC 80 cm (31.5") 3840 x 2160 Pixel 4K Ultra HD LCD Nero:

Questo monitor da 32 pollici mostra splendide immagini con risoluzione in 4K e una gamma 1,074 miliardi di colori. Inoltre, la connessione USB-C consente di collegare facilmente tutte le periferiche necessarie durante un'intensa giornata lavorativa. Philips 3000 series 32B1U3900/00. Dimensioni diagonale schermo: 80 cm (31.5"), Risoluzione del display: 3840 x 2160 Pixel, Tipologia HD: 4K Ultra HD, Tecnologia display: LCD, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Altoparlanti incorporati. Hub USB integrato, Versione dell'hub USB: 3.2 Gen 1 (3.1 Gen 1). Montaggio standard VESA, Regolazione altezza. Colore del prodotto: Nero



Display		Ports & interfaces	
Display diagonal *	80 cm (31.5")	HDMI ports quantity	2
Display resolution *	3840 x 2160 pixels	HDMI version	2.0
HD type *	4K Ultra HD	DisplayPorts quantity	1
Native aspect ratio *	16:9	DisplayPort version	1.4
Display technology *	LCD	Audio output	✓
Panel type *	VA	HDCP	✓
LED backlight	✓	HDCP version	1.4/2.2
Backlight type	W-LED	Ergonomics	
Touchscreen *	✗	VESA mounting *	✓
Display brightness (typical)	350 cd/m²	Panel mounting interface	100 x 100 mm
Response time *	4 ms	Cable lock slot *	✓
Response time measurement type	GTG (Gray to Gray)	Cable lock slot type	Kensington
Anti-glare screen	✓	Height adjustment *	✓
Screen shape *	Flat	Adjustable height (max)	18 cm
Contrast ratio (typical) *	3500:1	Pivot	✓
Contrast ratio (dynamic)	50000000:1	Pivot angle	-90 - 90°
Maximum refresh rate *	60 Hz	Swivelling	✓
Viewing angle, horizontal	178°	Swivel angle range	-180 - 180°
Viewing angle, vertical	178°	Tilt adjustment	✓
Display number of colours *	1.07 billion colours	Tilt angle range	-5 - 20°
Pixel pitch	0.18159 x 0.18159 mm	On Screen Display (OSD)	✓
Pixel density	140 ppi	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Horizontal scan range	30 - 140 kHz		
Vertical scan range	23 - 75 Hz		
Viewable size, horizontal	69.7 cm		
Viewable size, vertical	39.2 cm		
DDC/CI	✓		
Haze rate	25%		

Display		Power	
Surface hardness	3H	Energy efficiency class (SDR) *	F
Colour gamut standard	NTSC, sRGB	Power consumption (typical) *	34.8 W
sRGB coverage (typical)	122%	Power consumption (standby) *	0.3 W
NTSC coverage (typical)	106%	Power consumption (off)	0.3 W
Performance		AC input voltage	100 - 240 V
Flicker-free technology	✓	AC input frequency	50/60 Hz
Low Blue Light technology	✓	Operational conditions	
Multimedia		Operating temperature (T-T)	0 - 40 °C
Number of speakers	2	Storage temperature (T-T)	-20 - 60 °C
RMS rated power	6 W	Operating relative humidity (H-H)	20 - 80%
Built-in speaker(s) *	✓	Operating altitude	0 - 3658 m
Built-in camera *	✗	Non-operating altitude	3658 - 12192 m
Design		Weight & dimensions	
Market positioning *	Business	Width (with stand)	714 mm
Product colour *	Black	Depth (with stand)	280 mm
Ports & interfaces		Height (with stand)	631 mm
Built-in USB hub *	✓	Weight (with stand)	11.5 kg
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Width (without stand)	714 mm
Number of USB Type-C upstream ports quantity	1	Depth (without stand)	62 mm
USB Type-A downstream ports quantity	4	Height (without stand)	422 mm
USB Type-C DisplayPort Alternate Mode	✓	Weight (without stand)	7.56 kg
USB Power Delivery (USB PD)	✓	Packaging data	
USB Power Delivery up to	90 W	Package width	930 mm
HDMI *	✓	Package depth	186 mm
		Package height	563 mm
		Package weight	16.2 kg
		Packaging content	
		Stand included	✓
		Sustainability	
		Doesn't contain	Lead, Mercury, PVC/BFR



8721038001211

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-APR-2025. Prints or copies of Information are only valid on the printed Publication date