

PHILIPS

Philips 49B2U6903CH/00 Monitor PC 124,5 cm (49") 5120 x 1440 Pixel Dual QHD LCD Grigio

Marchio : Philips

Codice prodotto: 49B2U6903CH/00

Nome del prodotto : 49B2U6903CH/00

Curved Business monitor 49B2U6903CH Monitor SuperWide Thunderbolt™ 4 32:9

Philips 49B2U6903CH/00 Monitor PC 124,5 cm (49") 5120 x 1440 Pixel Dual QHD LCD Grigio:

Questo monitor Philips Thunderbolt™ 4 è stato progettato con tutto ciò che ti serve per lavorare da remoto. La webcam integra funzionalità come l'inquadratura automatica e una BusyLight per realizzare videoconferenze impareggiabili.

Philips 49B2U6903CH/00. Dimensioni diagonale schermo: 124,5 cm (49"), Risoluzione del display: 5120 x 1440 Pixel, Tipologia HD: Dual QHD, Tecnologia display: LCD, Tempo di risposta: 4 ms, Rapporto d'aspetto nativo: 32:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Altoparlanti incorporati. Hub USB integrato, Versione dell'hub USB: 3.2 Gen 2 (3.1 Gen 2). Montaggio standard VESA, Regolazione altezza. Colore del prodotto: Grigio



Display		Ports & interfaces	
Display diagonal *	124.5 cm (49")	HDMI version	2.0
Display resolution *	5120 x 1440 pixels	DisplayPorts quantity	1
HD type *	Dual QHD	DisplayPort version	1.4
Native aspect ratio *	32:9	Thunderbolt 4 ports quantity	1
Display technology *	LCD	Audio output	✓
Panel type *	VA	HDCP	✓
LED backlight	✓	HDCP version	1.4/2.2
Backlight type	W-LED	Ergonomics	
Display brightness (peak)	500 cd/m ²	VESA mounting *	✓
Display brightness (typical)	450 cd/m ²	Panel mounting interface	100 x 100 mm
Response time *	4 ms	Cable lock slot *	✓
Anti-glare screen	✓	Cable lock slot type	Kensington
Screen shape *	Curved	Height adjustment *	✓
Contrast ratio (typical) *	3000:1	Height adjustment	15 cm
Contrast ratio (dynamic)	80000000:1	Swivelling	✓
Maximum refresh rate *	100 Hz	Swivel angle range	-30 - 30°
Viewing angle, horizontal	178°	Tilt adjustment	✓
Viewing angle, vertical	178°	Tilt angle range	-5 - 20°
Display number of colours *	1.07 billion colours	On Screen Display (OSD)	✓
Pixel pitch	0.2328 x 0.2328 mm	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Turkish, Ukrainian
Pixel density	109 ppi	Power	
Horizontal scan range	30 - 200 kHz	Energy efficiency class (SDR) *	F
Vertical scan range	48 - 120 Hz	Power consumption (typical) *	41.85 W
Viewable size, horizontal	119.2 cm		
Viewable size, vertical	33.5 cm		
High Dynamic Range (HDR) supported	✓		
High Dynamic Range (HDR) technology	High Dynamic Range (HDR) 400		

Display		Power	
DDC/CI	✓	Power consumption (standby) *	0.5 W
Haze rate	25%	Power consumption (PowerSave)	37.5 W
Surface hardness	3H	AC input voltage	100 - 240 V
NTSC coverage (typical)	97%	AC input frequency	50/60 Hz
Performance		Power supply type	Internal
VESA Adaptive Sync support	✓	Operational conditions	
Multimedia		Operating temperature (T-T)	0 - 40 °C
Number of speakers	2	Storage temperature (T-T)	-20 - 60 °C
RMS rated power	10 W	Operating relative humidity (H-H)	20 - 80%
Built-in speaker(s) *	✓	Operating altitude	0 - 3658 m
Megapixel (approx.)	5 MP	Non-operating altitude	3658 - 12192 m
Built-in microphone	✓	Weight & dimensions	
Built-in camera *	✓	Width (with stand)	1193 mm
Design		Depth (with stand)	268 mm
Market positioning *	Business	Height (with stand)	586 mm
Product colour *	Grey	Weight (with stand)	15.5 kg
Ports & interfaces		Width (without stand)	1193 mm
Built-in USB hub *	✓	Depth (without stand)	164 mm
USB hub version	3.2 Gen 2 (3.1 Gen 2)	Height (without stand)	373 mm
Number of USB Type-C upstream ports quantity	1	Weight (without stand)	11.8 kg
USB Type-A downstream ports quantity	4	Packaging data	
USB Type-C downstream ports quantity	2	Package width	1290 mm
USB Power Delivery (USB PD)	✓	Package depth	300 mm
USB Power Delivery up to	100 W	Package height	475 mm
HDMI *	✓	Package weight	19.5 kg
HDMI ports quantity	2	Packaging content	
		Stand included	✓
		Cables included	DisplayPort, HDMI, Power, Thunderbolt
		Sustainability	
		Doesn't contain	Mercury, PVC/BFR
		Other features	
		HBR3 support	✓



8712581804763

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-NOV-2024. Prints or copies of Information are only valid on the printed Publication date