NEC

NEC MultiSync CB861Q Pannello piatto per segnaletica digitale 2,18 m (86") IPS 350 cd/m² 4K Ultra HD Nero Touch screen 12/7

Marchio : NEC

Famiglia del prodotto: MultiSync

Codice prodotto: 60004825

Nome del prodotto : CB861Q

86" IPS, 3840 x 2160, 350 cd/m2, 12/7
NEC MultiSync CB861Q. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 2,18 m (86"), Tecnologia display: IPS, Risoluzione del display: 3840 x 2160 Pixel, Luminosità schermo: 350 cd/m², Tipologia HD: 4K Ultra HD, Touch screen. Ore di servizio (ore/giorni): 12/7. Colore del prodotto: Nero

Display

LED backlighting type	Direct-LED
Display diagonal *	2.18 m (86")
Display technology *	IPS
Display resolution *	3840 x 2160 pixels
Display brightness *	350 cd/m²
HD type *	4K Ultra HD
Touchscreen *	✔
Number of simultaneous touchpoints	20
Multi-touch	✔
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.073 billion colours
Pixel pitch	0.4935 x 0.4935 mm
Active display area (W x H)	1895 x 1066 mm
Display diagonal (metric)	217.4 cm
Horizontal scan range	26 - 135 kHz
Vertical scan range	23 - 80 Hz

Ports & interfaces

HDMI ports quantity *	3
HDMI input ports quantity	3
DVI port *	✘
VGA (D-Sub) input ports	1
USB port *	✔
USB ports quantity	7
USB version	2.0
Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	2
Ethernet LAN data rates	10,100 Mbit/s
Wi-Fi *	✘

Design

Product colour *	Black
VESA mounting *	✔
Panel mounting interface	800 x 600 mm
Bezel width (bottom)	4.57 cm
Bezel width (side)	1.77 cm
Bezel width (top)	1.77 cm

Performance

Purpose *	Universal
Operating hours (hours/days)	12/7
HDCP	✔

Power

Energy efficiency scale	A+++ to D

Computer system

Computer system *	✘
Internal memory	2 GB
Internal storage capacity	16 GB
Windows operating systems supported	✔
Mac operating systems supported	✔
Linux operating systems supported	✔

Weight & dimensions

Width	1957.1 mm
Depth	86.8 mm
Height	1159.8 mm
Weight	67.3 kg

Packaging content

Cables included	HDMI, USB, VGA
Mounting kit	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C

Ports & interfaces

PC Audio in	✔
RS-232 interface	✔
OPS module slot	✔

Audio

Built-in speaker(s) *	✔
Number of built-in speakers	2
RMS rated power	24 W

Design

Product design *	Digital signage flat panel
Orientation	Horizontal

Operational conditions

Operating relative humidity (H-H)	10 - 90%

Certificates

Certification	BSMI; CE; EAC; EMC Class B; FCC; PSB; RCM; REACH; SASO; UL/C-UL

Logistics data

Harmonized System (HS) code	85285210

Technical details

Compliance certificates	RoHS

Other features

Energy efficiency class (old)	C

5028695116863

Publication date: 27-FEB-2025. Prints or copies of Information are only valid on the printed Publication date