

NEC MultiSync P495 Pannello piatto per segnaletica digitale 124,5 cm (49") LCD 700 cd/m² 4K Ultra HD Nero 24/7

Marchio : NEC

Famiglia del prodotto: MultiSync

Nome del prodotto : P495

Codice prodotto: 60005049



NEC MultiSync P495. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 124,5 cm (49"), Tecnologia display: LCD, Risoluzione del display: 3840 x 2160 Pixel, Luminosità schermo: 700 cd/m², Tipologia HD: 4K Ultra HD. Ore di servizio (ore/giorni): 24/7. Colore del prodotto: Nero

Display		Design	
Panel type	IPS	Bezel width (top)	1.2 cm
LED backlight	✓	Performance	
LED backlighting type	Edge-LED	Purpose *	Universal
Display diagonal *	124.5 cm (49")	Picture-in-Picture	✓
Display technology *	LCD	Ambient light sensor	✓
Display resolution *	3840 x 2160 pixels	Firmware upgradeable	✓
Display brightness *	700 cd/m²	Operating hours (hours/days)	24/7
HD type *	4K Ultra HD	HDCP	✓
Native aspect ratio	16:9	Power	
Response time	8 ms	Power consumption (typical) *	105 W
Contrast ratio (typical)	8000:1	Power consumption (standby) *	2 W
Viewing angle, horizontal	178°	Energy efficiency class (SDR)	G
Viewing angle, vertical	178°	Energy efficiency class (HDR)	G
Display number of colours	1.073 billion colours	Energy consumption (SDR) per 1000 hours	106 kWh
Display diagonal (metric)	124.5 cm	Energy consumption (HDR) per 1000 hours	98 kWh
Horizontal scan range	15 - 135 kHz	AC input voltage	100 - 240 V
Vertical scan range	23 - 76 Hz	AC input frequency	50 - 60 Hz
Native refresh rate	60 Hz	Weight & dimensions	
Haze rate	28%	Display width	1103.4 mm
Ports & interfaces		Display depth	61.1 mm
HDMI ports quantity *	3	Display height	636.2 mm
HDMI input ports quantity	2	Display weight	22.9 kg
HDMI output ports quantity	1	Packaging data	
DisplayPorts quantity *	3	Package width	1298 mm
DisplayPorts in	2	Package depth	224 mm
DisplayPorts out	1	Package height	860 mm
USB port *	✓	Package weight	29.8 kg
USB ports quantity	3	Packaging content	
USB version	2.0	Remote control included	✓
Ethernet LAN *	✓		
Ethernet LAN (RJ-45) ports	2		
Ethernet LAN data rates	100 Mbit/s		
Audio (L/R) out	1		

Ports & interfaces		Packaging content	
RS-232 interface	✓	Batteries included	✓
Design		Cables included	AC, HDMI
Product design *	Digital signage flat panel	Operational conditions	
Placement supported *	Indoor	Operating temperature (T-T)	0 - 40 °C
Orientation	Horizontal/Vertical	Operating relative humidity (H-H)	20 - 80%
Product colour *	Black	Storage temperature (T-T)	-20 - 60 °C
VESA mounting *	✓	Storage relative humidity (H-H)	10 - 90%
Panel mounting interface	300 x 300 mm	Logistics data	
Bezel width (bottom)	1.25 cm	Harmonized System (HS) code	85285210
Bezel width (side)	1.2 cm		



5028695119376



0805736072785



805736072785

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-FEB-2025. Prints or copies of Information are only valid on the printed Publication date