**NEC**

NEC MultiSync ME501 Pannello piatto per segnaletica digitale 127 cm (50") VA 400 cd/m² 4K Ultra HD Nero 18/7

Marchio : NEC

Famiglia del prodotto: MultiSync

Codice prodotto: 60005053

Nome del prodotto : ME501

NEC MultiSync ME501. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 127 cm (50"), Tecnologia display: VA, Risoluzione del display: 3840 x 2160 Pixel, Luminosità schermo: 400 cd/m², Tipologia HD: 4K Ultra HD. Ore di servizio (ore/giorni): 18/7. Colore del prodotto: Nero

Display

LED backlighting type	Direct-LED
Display diagonal *	127 cm (50")
Display technology *	VA
Display resolution *	3840 x 2160 pixels
Display brightness *	400 cd/m²
HD type *	4K Ultra HD
Touchscreen *	✘
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	8000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display diagonal (metric)	125.7 cm
Horizontal scan range	26 - 135 kHz
Vertical scan range	23 - 86 Hz
Native refresh rate	60 Hz

Ports & interfaces

HDMI ports quantity *	2
DVI port *	✘
DisplayPorts quantity *	1
Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	100 Mbit/s
Wi-Fi *	✘
Audio (L/R) out	1
RS-232 interface	✔

Audio

Built-in speaker(s) *	✔
Number of built-in speakers	2
RMS rated power	20 W

Design

Product design *	Digital signage flat panel

Performance

International Protection (IP) code	IP5X, IP2X

Power

Energy efficiency class (SDR)	G
Energy efficiency class (HDR)	G
Energy consumption (SDR) per 1000 hours	85 kWh
Energy consumption (HDR) per 1000 hours	69 kWh
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G

Computer system

Computer system *	✘
Built-in processor *	✘

Weight & dimensions

Width	1128.4 mm
Depth	62.6 mm
Height	649 mm
Weight	17.3 kg

Packaging data

Package width	1298 mm
Package depth	224 mm
Package height	860 mm
Package weight	24.1 kg

Packaging content

Remote control included	✔
Cables included	AC, HDMI

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C

Design

Orientation	Horizontal/Vertical
Product colour *	Black
VESA mounting *	✔
Panel mounting interface	400 x 400 mm

Performance

Purpose *	Universal
Operating hours (hours/days)	18/7
HDCP	✔

Operational conditions

Storage relative humidity (H-H)	10 - 90%

Logistics data

Harmonized System (HS) code	85285210

Features

Wall mountable	✔

Technical details

Sustainability certificates	ENERGY STAR

5028695119406