

# NEC MultiSync E658 165,1 cm (65") IPS 350 cd/m² 4K Ultra HD Nero 16/7

**Marchio :** NEC
 **Famiglia del prodotto:** MultiSync
 **Codice prodotto:** 60005059

**Nome del prodotto :** E658



NEC MultiSync E658. Dimensioni diagonale schermo: 165,1 cm (65"), Tecnologia display: IPS, Risoluzione del display: 3840 x 2160 Pixel, Luminosità schermo: 350 cd/m², Tipologia HD: 4K Ultra HD. Ore di servizio (ore/giorni): 16/7. Colore del prodotto: Nero

| Display                             |                        | Design                                  |                                                             |
|-------------------------------------|------------------------|-----------------------------------------|-------------------------------------------------------------|
| LED backlighting type               | Direct-LED             | Bezel width (bottom)                    | 1.44 cm                                                     |
| Display diagonal *                  | 165.1 cm (65")         | Bezel width (side)                      | 1.3 cm                                                      |
| Display technology *                | IPS                    | Bezel width (top)                       | 1.3 cm                                                      |
| Display resolution *                | 3840 x 2160 pixels     | Performance                             |                                                             |
| Display brightness *                | 350 cd/m²              | Hybrid Log-Gamma (HLG)                  | ✓                                                           |
| HD type *                           | 4K Ultra HD            | Ambient light sensor                    | ✓                                                           |
| Native aspect ratio                 | 16:9                   | Operating hours (hours/days)            | 16/7                                                        |
| Response time                       | 8 ms                   | Power                                   |                                                             |
| Contrast ratio (typical)            | 1200:1                 | Power consumption (typical) *           | 144 W                                                       |
| Viewing angle, horizontal           | 178°                   | Power consumption (standby) *           | 2 W                                                         |
| Viewing angle, vertical             | 178°                   | Energy efficiency class (SDR)           | F                                                           |
| Pixel pitch                         | 0.372 x 0.372 mm       | Energy efficiency class (HDR)           | G                                                           |
| Active display area (W x H)         | 1428.48 x 803.52 mm    | Energy consumption (SDR) per 1000 hours | 96 kWh                                                      |
| Display diagonal (metric)           | 164 cm                 | Energy consumption (HDR) per 1000 hours | 127 kWh                                                     |
| Horizontal scan range               | 15 - 136 kHz           | AC input voltage                        | 100-240 V                                                   |
| Vertical scan range                 | 24 - 75 Hz             | AC input frequency                      | 50 - 60 Hz                                                  |
| High Dynamic Range (HDR) supported  | ✓                      | Computer system                         |                                                             |
| High Dynamic Range (HDR) technology | Hybrid Log-Gamma (HLG) | Video formats supported                 | H.263, H.264, HEVC/H.265, MP4, MPEG1, MPEG2, MPEG4, MPG, TS |
| Native refresh rate                 | 60 Hz                  | Audio formats supported                 | AAC, LPCM, MP3, WMV                                         |
| Haze rate                           | 1%                     | Image formats supported                 | JPG                                                         |
| Ports & interfaces                  |                        | Weight & dimensions                     |                                                             |
| HDMI ports quantity *               | 3                      | Width                                   | 1457.5 mm                                                   |
| VGA (D-Sub) input ports             | 1                      | Depth                                   | 73 mm                                                       |
| USB port *                          | ✓                      | Height                                  | 833.9 mm                                                    |
| USB ports quantity                  | 2                      | Weight                                  | 23.8 kg                                                     |
| USB version                         | 2.0                    | Packaging content                       |                                                             |
| Ethernet LAN *                      | ✓                      | Remote control included                 | ✓                                                           |
| Ethernet LAN (RJ-45) ports          | 1                      | Batteries included                      | ✓                                                           |
| Ethernet LAN data rates             | 100 Mbit/s             | Cables included                         | AC, HDMI                                                    |
| Composite video in                  | 1                      |                                         |                                                             |
| Component video (YPbPr/YCbCr) in    | 1                      |                                         |                                                             |
| RS-232 interface                    | ✓                      |                                         |                                                             |
| RS-232C                             | ✓                      |                                         |                                                             |

| Ports & interfaces          |              | Operational conditions            |                                                                                             |
|-----------------------------|--------------|-----------------------------------|---------------------------------------------------------------------------------------------|
| Remote (IR) input           | 1            | Operating temperature (T-T)       | 0 - 40 °C                                                                                   |
| Audio                       |              | Operating relative humidity (H-H) | 10 - 80%                                                                                    |
| Built-in speaker(s) *       | ✓            | Storage temperature (T-T)         | -10 - 60 °C                                                                                 |
| Number of built-in speakers | 2            | Storage relative humidity (H-H)   | 5 - 85%                                                                                     |
| RMS rated power             | 20 W         | Certificates                      |                                                                                             |
| Design                      |              | Certification                     | CE; EAC; EMC Class B; Energy Star 8; FCC; PSB; RCM; REACH; RoHS; SASO; TÜV S; UL/C-UL; VCCI |
| Placement supported *       | Indoor       | Logistics data                    |                                                                                             |
| Orientation                 | Horizontal   | Harmonized System (HS) code       | 85285210                                                                                    |
| Product colour *            | Black        | Technical details                 |                                                                                             |
| VESA mounting *             | ✓            | Sustainability certificates       | ENERGY STAR                                                                                 |
| Panel mounting interface    | 400 x 200 mm |                                   |                                                                                             |



5028695120495



0805736073553



805736073553

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-FEB-2025. Prints or copies of Information are only valid on the printed Publication date