

NEC MultiSync M751 Pannello piatto per segnaletica digitale 190,5 cm (75") LCD 500 cd/m² 4K Ultra HD Nero 24/7

Marchio : NEC

Famiglia del prodotto: MultiSync

Codice prodotto: 60005064

Nome del prodotto : M751



NEC MultiSync M751. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 190,5 cm (75"), Tecnologia display: LCD, Risoluzione del display: 3840 x 2160 Pixel, Luminosità schermo: 500 cd/m², Tipologia HD: 4K Ultra HD. Ore di servizio (ore/giorni): 24/7. Colore del prodotto: Nero

Display		Design	
Panel type	IPS	VESA mounting *	✓
LED backlight	✓	Panel mounting interface	600 x 400 mm
LED backlighting type	Direct-LED	Bezel width (bottom)	1.48 cm
Display diagonal *	190.5 cm (75")	Bezel width (side)	1.43 cm
Display technology *	LCD	Bezel width (top)	1.43 cm
Display resolution *	3840 x 2160 pixels	Performance	
Display brightness *	500 cd/m²	Purpose *	Universal
HD type *	4K Ultra HD	Ambient light sensor	✓
Touchscreen *	✗	Operating hours (hours/days)	24/7
Native aspect ratio	16:9	HDCP	✓
Response time	8 ms	Power	
Contrast ratio (typical)	8000:1	Power consumption (typical) *	205 W
Viewing angle, horizontal	178°	Energy efficiency class (SDR)	G
Viewing angle, vertical	178°	Energy consumption (SDR) per 1000 hours	145 kWh
Display number of colours	1.073 billion colours	AC input voltage	100 - 240 V
Display diagonal (metric)	189.3 cm	AC input frequency	50 - 60 Hz
Horizontal scan range	15 - 135 kHz	Weight & dimensions	
Vertical scan range	23 - 76 Hz	Width	1682.3 mm
Haze rate	25%	Depth	83.2 mm
Ports & interfaces		Height	961.1 mm
HDMI ports quantity *	3	Weight	38 kg
HDMI input ports quantity	2	Packaging data	
HDMI output ports quantity	1	Package width	1830 mm
DVI port *	✗	Package depth	225 mm
DisplayPorts quantity *	3	Package height	1070 mm
DisplayPorts in	2	Package weight	51.5 kg
DisplayPorts out	1	Packaging content	
Ethernet LAN *	✓	Remote control included	✓
Ethernet LAN data rates	100 Mbit/s	Batteries included	✓
RS-232 interface	✓	Cables included	HDMI, Power
Audio			
Built-in speaker(s) *	✓		
Number of built-in speakers	2		
RMS rated power	10 W		

Design		Operational conditions	
Product design *	Digital signage flat panel	Operating temperature (T-T)	0 - 40 °C
Orientation	Horizontal/Vertical	Operating relative humidity (H-H)	20 - 80%
Product colour *	Black	Storage temperature (T-T)	-20 - 60 °C
		Storage relative humidity (H-H)	10 - 80%



5028695125230

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-FEB-2025. Prints or copies of Information are only valid on the printed Publication date