

NEC MultiSync M981 Pannello piatto per segnaletica digitale 2,49 m (98") LCD 500 cd/m² 4K Ultra HD Nero

Marchio : NEC

Famiglia del prodotto: MultiSync

Nome del prodotto : M981

Codice prodotto: 60005069



NEC MultiSync M981. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 2,49 m (98"), Tecnologia display: LCD, Risoluzione del display: 3840 x 2160 Pixel, Luminosità schermo: 500 cd/m², Tipologia HD: 4K Ultra HD. Colore del prodotto: Nero

Display		Design	
Panel type	IPS	Product colour *	Black
LED backlight	✓	VESA mounting *	✓
LED backlighting type	Direct-LED	Panel mounting interface	600 x 400 mm
Display diagonal *	2.49 m (98")	Bezel width (bottom)	1.43 cm
Display technology *	LCD	Bezel width (top)	1.48 cm
Display resolution *	3840 x 2160 pixels	Performance	
Display brightness *	500 cd/m²	Purpose *	Corporate
HD type *	4K Ultra HD	HDCP	✓
Touchscreen *	✗	Power	
Native aspect ratio	16:9	Power consumption (typical) *	340 W
Response time	8 ms	Power consumption (standby) *	0.5 W
Contrast ratio (typical)	8000:1	Energy efficiency class (SDR)	F
Viewing angle, horizontal	178°	Energy efficiency class (HDR)	F
Viewing angle, vertical	178°	Energy consumption (SDR) per 1000 hours	205 kWh
Display number of colours	1.073 billion colours	Energy consumption (HDR) per 1000 hours	180 kWh
Display diagonal (metric)	248 cm	AC input voltage	100 - 240 V
Horizontal scan range	15 - 135 kHz	AC input frequency	50 - 60 Hz
Vertical scan range	23 - 76 Hz	Energy efficiency scale	A to G
Native refresh rate	60 Hz	Weight & dimensions	
Ports & interfaces		Display width	1250.2 mm
HDMI ports quantity *	3	Display depth	84.3 mm
HDMI input ports quantity	2	Display height	1250.2 mm
HDMI output ports quantity	1	Display weight	67 kg
DVI port *	✗	Packaging data	
DisplayPorts quantity *	3	Package width	2350 mm
DisplayPorts in	2	Package depth	310 mm
DisplayPorts out	1	Package height	1400 mm
USB port *	✓	Package volume	98700 cm³
USB ports quantity	2	Packaging content	
USB version	2.0	Remote control included	✓
USB connector type	USB Type-B	Batteries included	✓
Ethernet LAN *	✓		
Ethernet LAN (RJ-45) ports	1		
Ethernet LAN data rates	100,1000 Mbit/s		
RS-232 interface	✓		

Ports & interfaces		Packaging content	
PC Audio out	✓	Cables included	AC, HDMI
Audio		Operational conditions	
Built-in speaker(s) *	✓	Operating temperature (T-T)	0 - 40 °C
Number of built-in speakers	2	Operating relative humidity (H-H)	20 - 80%
RMS rated power	20 W	Storage temperature (T-T)	-20 - 60 °C
Design		Storage relative humidity (H-H)	10 - 80%
Product design *	Digital signage flat panel	Features	
Placement supported *	Indoor	Base material	Metal
Orientation	Horizontal/Vertical		



5028695125919

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-FEB-2025. Prints or copies of Information are only valid on the printed Publication date