NEC MultiSync E328 Pannello piatto per segnaletica digitale 81,3 cm (32") LCD 350 cd/m² Full HD Nero 16/7

Marchio: NEC Famiglia del prodotto: Codice prodotto: 60005270

MultiSync

Nome del prodotto: E328

NEC MultiSync E328. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 81,3 cm (32"), Tecnologia display: LCD, Risoluzione del display: 1920 x 1080 Pixel, Luminosità schermo: 350 cd/m², Tipologia HD: Full HD. Ore di servizio (ore/giorni): 16/7. Colore del prodotto: Nero





Panel type IPS Product colour * Black LED backlight / VESA mounting * / LED backlighting type Direct-LED Panel mounting interface 100 x 100 mm Display diagonal * 81.3 cm (32") Bezel width (side) 1.25 cm Display resolution * 1920 x 1080 pixels Bezel width (top) 1.25 cm Display brightness * 350 cd/m² Performance HD type * Full HD Purpose * Universal Native aspect ratio 16:9 Ambient light sensor ✓ Response time 8 ms Operating hours (hours/days) 16/7 Octortast ratio (typical) 1200:1 Operating hours (hours/days) 16/7 Viewing angle, horizontal 178° Power Verive (and panel) 33 W Viewing angle, vertical 16.78 million colours Power consumption (typical)* 23 W Display number of colours 16.78 million colours Power consumption (standby)* 2 W Pixel pitch 0.364 x 0.364 mm Energy consumption (standby)* 2 T kWh <t< th=""><th></th><th></th><th></th><th></th></t<>				
LED backlight V VESA mounting V LED backlighting type Direct-LED Panel mounting interface 100 x 100 mm Display diagonal 81.3 cm (32") Bezel width (bottom) 1.39 cm Display resolution * 1920 x 1080 pixels Bezel width (side) 1.25 cm Display brightness * 350 cd/m² Bezel width (top) 1.25 cm Bottle type * Full HD Purpose * Universal Native aspect ratio 16.9 Ambient light sensor * Response time 8 ms Ambient light sensor * Contrast ratio (typical) 1200:1 Operating hours (hours/days) 16/7 Viewing angle, horizontal 178" Power * Viewing angle, vertical 178" Power * Viewing angle, vertical 16.78 million colours Power consumption (typical) * 33 W Display diagonal (metric) 0.364 x 0.364 mm Energy consumption (standby) * 2 W Nexit per	Display		Design	
LED backlighting type Display diagonal * B1.3 cm (32") Bezel width (bottom) 1.39 cm Display technology * LCD Bezel width (ided) 1.25 cm Display technology * LCD Bezel width (ided) 1.25 cm Display technology * LCD Bezel width (ided) 1.25 cm Display brightness * 350 cd/m² Performance HD type * Full HD Native aspect ratio 16:9 Response time 8 ms Contrast ratio (typical) 1200:1 Viewing angle, horizontal 178° Power Display namber of colours 16.78 million colours Pixel pitch 0.364 x 0.364 mm Energy efficiency class (SDR) F Active display area (W x H) 698 x 393 mm Energy efficiency class (HDR) E Borry efficiency class (HDR) E Horizontal scan range 15 - 136 kHz hours Wertical scan range 15 - 136 kHz hours HOW hours friends 1000 hours Ports & Interface HDMI ports quantity 3 VGA (D-Sub) input ports USB port * V USB port squantity 2 USB port squantity 2 USB port squantity 4 LED backlighting type width (foot on the power on the	Panel type	IPS	Product colour *	Black
Display diagonal 81.3 cm (32") Bezel width (bottom) 1.39 cm Display rechnology LCD Bezel width (side) 1.25 cm Display resolution 1920 x 1080 pixels Bezel width (top) 1.25 cm Display resolution 1920 x 1080 pixels Bezel width (top) 1.25 cm Display brightness 350 cd/m² Performance HD type Full HD Purpose Universal Native aspect ratio 16.9 Ambient light sensor ✓	LED backlight	✓	VESA mounting *	✓
Display technology * LCD Bezel width (side) 1.25 cm 1920 x 1080 pixels Bezel width (top) 1.25 cm 1920 x 1080 pixels Bezel width (top) 1.25 cm 1920 x 1080 pixels Bezel width (top) 1.25 cm 1920 x 1080 pixels Bezel width (top) 1.25 cm 1920 x 1080 pixels Bezel width (top) 1.25 cm 1920 x 1080 pixels Bezel width (top) 1.25 cm 1920 x 1080 pixels Bezel width (top) 1.25 cm 1920 x 1080	LED backlighting type	Direct-LED	Panel mounting interface	100 x 100 mm
Display resolution * 1920 x 1080 pixels	Display diagonal *	81.3 cm (32")	Bezel width (bottom)	1.39 cm
Display brightness * 350 cd/m² Performance	Display technology *	LCD	Bezel width (side)	1.25 cm
HD type * Full HD Native aspect ratio 16:9 Assponse time 8 ms Ambient light sensor 7 Ambient light sensor 16/7 Contrast ratio (typical) 1200:1 Viewing angle, horizontal 178° Power Viewing angle, vertical 178° Display number of colours 16.78 million colours Power consumption (typical) 33 W Display number of colours 16.78 million colours Power consumption (standby) 2 W Pixel pitch 0.364 x 0.364 mm Energy efficiency class (SDR) F Active display area (W x H) 698 x 393 mm Energy efficiency class (SDR) F Display diagonal (metric) 80 cm Energy consumption (SDR) per 1000 77 kWh Horizontal scan range 15 - 136 kHz hours 1000 hour	Display resolution *	1920 x 1080 pixels	Bezel width (top)	1.25 cm
Native aspect ratio Response time Response Re	Display brightness *	350 cd/m ²	Performance	
Native aspect ratio Response time Response t	HD type *	Full HD	Purnose *	Universal
Response time 8 ms Contrast ratio (typical) 1200:1 Viewing angle, horizontal 178° Viewing angle, vertical 178° Display number of colours 16.78 million colours Power consumption (typical) * 33 W Display number of colours 16.78 million colours Power consumption (standby) * 2 W Pixel pitch 0.364 x 0.364 mm Energy efficiency class (SDR) F Active display area (W x H) 698 x 393 mm Energy efficiency class (HDR) E Display diagonal (metric) 80 cm Energy consumption (SDR) per 1000 Vertical scan range 15 - 136 kHz hours 27 kWh Horizontal scan range 24 - 75 Hz Energy consumption (HDR) per 1000 hours 27 kWh Native refresh rate 60 Hz AC input voltage 100 - 240 V AC input requency 50 - 60 Hz HDMI ports quantity 3 VGA (D-Sub) input ports quantity 3 VGA (D-Sub) input ports quantity 4 USB port * ✓ Audio formats supported MP4, MPG, TS LUSB version 2.0 Ethernet LAN * ✓ Meight & dimensions Ethernet LAN (RJ-45) ports 1 Ethernet LAN (RJ-45) ports 1 Ethernet LAN (RJ-45) ports 1 Component video (YPbPr/YCbCr) in 1 Display weight 422.3 mm Display weight 53.8 kg	Native aspect ratio	16:9	•	
Viewing angle, horizontal 178° Power Viewing angle, vertical 178° Power consumption (typical)* 33 W Display number of colours 16.78 million colours Power consumption (standby)* 2 W Pixel pitch 0.364 x 0.364 mm Energy efficiency class (SDR) F Active display area (W x H) 698 x 393 mm Energy efficiency class (HDR) E Display diagonal (metric) 80 cm Energy consumption (SDR) per 1000 27 kWh Horizontal scan range 15 - 136 kHz hours Vertical scan range 24 - 75 Hz Energy consumption (HDR) per 1000 hours Native refresh rate 60 Hz Energy consumption (HDR) per 1000 hours AC input voltage 100 - 240 V AC input frequency 50 - 60 Hz HDMI ports quantity AC input refrequency 50 - 60 Hz HDMI ports quantity 3 Computer system VIGA (D-Sub) input ports 1 Video formats supported MP4, MPG, TS AUGio formats supported MP4, MPG, TS AUGio formats supported MWW USB port quantity 2 Image formats supported MWW USB ports quantity 2 Image formats supported MWW USB version 2.0 Weight & dimensions Ethernet LAN * Image formats supported Pipe File File File File File File File Fil	Response time	8 ms	3	
Wiewing angle, vertical 178° Power consumption (typical) * 33 W Display number of colours 16.78 million colours Power consumption (standby) * 2 W Pixel pitch 0.364 x 0.364 mm Energy efficiency class (SDR) F Active display area (W x H) 698 x 393 mm Energy efficiency class (HDR) E Display diagonal (metric) 80 cm Energy consumption (SDR) per 1000 PHorizontal scan range 15 - 136 kHz hours 27 kWh Active display area (B x H) Energy consumption (HDR) per 1000 PHORIZON (SDR) per 1000 PHORI			, , , , , ,	10//
Display number of colours 16.78 million colours Power consumption (standby) * 2 W Pixel pitch 0.364 x 0.364 mm Energy efficiency class (SDR) Energy efficiency class (SDR) Energy efficiency class (HDR) Energy efficiency class (HDR) Energy efficiency class (HDR) Energy efficiency class (HDR) Energy consumption (SDR) per 1000 27 kWh Energy consumption (HDR) per 1000 Energy class (HDR) Energy consumption (HDR) per 1000 Energy consumption (HDR) per 1000 Energy consumption (HDR) per 1000 Energy class (HDR) Energy	Viewing angle, horizontal		Power	
Pixel pitch 0.364 x 0.364 mm Energy efficiency class (SDR) F Active display area (W x H) 698 x 393 mm Energy efficiency class (HDR) E Energy deficiency class (HDR) E Energy deficiency class (HDR) E Energy consumption (SDR) per 1000 27 kWh hours 28 kinterfaces 24 - 75 Hz Energy consumption (HDR) per 1000 hours 27 kWh 27 kWh 28 kinterfaces 24 - 75 Hz Energy consumption (HDR) per 1000 hours 27 kWh 28 kinterfaces 27 kWh 28 kinterfaces 28 kinterfaces 29 kC input voltage 20 consumption (HDR) per 20 consumption (HDR) per 20 consumption (HDR) per 20 kWh 29			Power consumption (typical) *	33 W
Active display area (W x H) Active display area (W x H) Bossplay diagonal (metric) Bossplay weight Bo	• •			2 W
Display diagonal (metric) 80 cm Horizontal scan range 15 - 136 kHz Vertical scan range 24 - 75 Hz Native refresh rate 60 Hz Ports & interfaces HDMI ports quantity 3 VGA (D-Sub) input ports 1 USB ports quantity 2 USB ports quantity 2 USB version 2.0 Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Ethernet LAN data rates 100 Mbit/s Component video (YPbPr/YCbCr) in 1 Energy consumption (SDR) per 1000 27 kWh Energy consumption (HDR) per 1000 40 27 kWh Energy consumption (HDR) per 1000 27 kWh Energy consumption (SDR) per 1000 27 kWh Computer System 200 - 240 V AC input voltage 200 - 200 For per 1000 hours 200 - 240 V AC input voltage 200 - 200 - 200 For per 1000 hours 200 - 240 V AC input voltage 200 - 200 - 200 For per 1000 hours 200 Fo			Energy efficiency class (SDR)	F
Horizontal scan range 15 - 136 kHz hours 27 kWh Native refresh rate 60 Hz Energy consumption (HDR) per 1000 hours AC input voltage 100 - 240 V Ports & interfaces AC input voltage 50 - 60 Hz HDMI ports quantity 3 Computer system VGA (D-Sub) input ports 1 Video formats supported MP4, MPG, TS USB port 4 V USB ports quantity 2 Image formats supported MWW USB version 2.0 Ethernet LAN * V Ethernet LAN (RJ-45) ports 1 Display width 726.6 mm Ethernet LAN data rates 100 Mbit/s Component video (YPbPr/YCbCr) in 1	• • • • • • • • • • • • • • • • • • • •		Energy efficiency class (HDR)	E
Vertical scan range Native refresh rate 60 Hz AC input voltage AC input frequency AC input requency AC input system Formula supported WPA, MPG, TS WAC, LPCM, MP3, WMA, WMA-PRO, WMV WAC input supported WMV WAC input system Video formats supported Wideo formats supported Display width Wideo formats supported Wideo formats supported Wideo formats supported Wideo formats supported Display width Wideo formats supported Wideo formats supported Wideo formats supported Display width Wideo formats supported Wideo formats supported Wideo formats supported Display width Wideo formats supported Wideo formats supported Wideo formats supported Display width Wideo formats supported MP4, MPG, TS AAC, LPCM, MP3, WMA, WMA-PRO, WMV Wideo formats supported Wideo formats su				27 kWh
Native refresh rate 60 Hz 1000 hours AC input voltage 100 - 240 V AC input frequency 50 - 60 Hz	-			
AC input voltage 100 - 240 V AC input frequency 50 - 60 Hz HDMI ports quantity * 3 HDMI input ports quantity 3 VGA (D-Sub) input ports 1 USB port * ✓ Audio formats supported MP4, MPG, TS USB ports quantity 2 USB version 2.0 Ethernet LAN * ✓ Weight & dimensions Ethernet LAN (RJ-45) ports 1 Ethernet LAN data rates 100 Mbit/s Component video (YPbPr/YCbCr) in 1 AC input voltage 100 - 240 V AC input frequency 50 - 60 Hz Computer system Video formats supported MP4, MPG, TS AAC, LPCM, MP3, WMA, WMA-PRO, WMV Weight & dimensions Display width 726.6 mm 67.1 mm 422.3 mm Display height 422.3 mm Display weight 5.3 kg	•			27 kWh
HDMI ports quantity * 3 HDMI input ports quantity 3 VGA (D-Sub) input ports 1 USB port * ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓	Native refresh rate	60 HZ	AC input voltage	100 - 240 V
HDMI input ports quantity VGA (D-Sub) input ports 1 Video formats supported MP4, MPG, TS AAC, LPCM, MP3, WMA, WMA-PRO, WMV USB ports quantity USB version Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Ethernet LAN data rates 100 Mbit/s Composite video in Component video (YPbPr/YCbCr) in 1 Video formats supported MP4, MPG, TS AAC, LPCM, MP3, WMA, WMA-PRO, WMV Weight & dimensions Final Display width 726.6 mm 67.1 mm Display height 422.3 mm Display weight 5.3 kg	Ports & interfaces		, ,	50 - 60 Hz
VGA (D-Sub) input ports 1 Video formats supported MP4, MPG, TS AAC, LPCM, MP3, WMA, WMA-PRO, WMV USB ports quantity USB version Ethernet LAN * Ethernet LAN (RJ-45) ports Ethernet LAN data rates 100 Mbit/s Composite video in Component video (YPbPr/YCbCr) in 1 Video formats supported AAC, LPCM, MP3, WMA, WMA-PRO, WMV Weight & dimensions PG Weight & dimensions Display width 726.6 mm 67.1 mm Display height 422.3 mm Display weight 5.3 kg	HDMI ports quantity *		Computer system	
USB port * ✓ Audio formats supported AAC, LPCM, MP3, WMA, WMA-PRO, WMV USB ports quantity 2 Image formats supported JPG USB version 2.0 Weight & dimensions Ethernet LAN * Display width 726.6 mm Ethernet LAN (RJ-45) ports 1 Display depth 67.1 mm Composite video in 1 Display weight 5.3 kg			Video formats supported	MP4, MPG, TS
USB version 2.0 Weight & dimensions Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Ethernet LAN data rates 100 Mbit/s Composite video in 1 Component video (YPbPr/YCbCr) in 1 Weight & dimensions Display width 726.6 mm Display depth 67.1 mm Display height 422.3 mm Display weight 5.3 kg	USB port *		Audio formats supported	
USB version 2.0 Ethernet LAN * ✓ Ethernet LAN (RJ-45) ports 1 Ethernet LAN data rates 100 Mbit/s Composite video in 1 Component video (YPbPr/YCbCr) in 1 Ethernet LAN defensions Display width 726.6 mm Display depth 67.1 mm Display height 422.3 mm Display weight 5.3 kg	USB ports quantity	2	Image formats supported	JPG
Ethernet LAN * Ethernet LAN (RJ-45) ports 1 Ethernet LAN data rates 100 Mbit/s Display width 67.1 mm Composite video in 1 Component video (YPbPr/YCbCr) in 1 Display weight 422.3 mm Display weight 5.3 kg	USB version	2.0	Weight & dimensions	
Ethernet LAN (RJ-45) ports 1 Ethernet LAN data rates 100 Mbit/s Display depth 67.1 mm Composite video in 1 Component video (YPbPr/YCbCr) in 1 Display weight 422.3 mm Display weight 5.3 kg	Ethernet LAN *	✓	•	70.0
Component video (YPbPr/YCbCr) in 1 Display height 422.3 mm Display weight 5.3 kg	Ethernet LAN (RJ-45) ports	1		
Component video (YPbPr/YCbCr) in 1 Display weight 5.3 kg	Ethernet LAN data rates	100 Mbit/s		
Component video (YPDPr/YCbCr) in 1	Composite video in	1		
	Component video (YPbPr/YCbCr) in	1	Display weight	э. э ку
Audio (L/R) out 1	Audio (L/R) out	1		

Ports & interfaces		Packaging content	
PC Audio in	✓	Remote control included	✓
Number of speaker outputs	1	Batteries included	✓
RS-232 interface	✓	Cables included	AC, HDMI
Remote (IR) input	1	Operational conditions	
Audio		Operating temperature (T-T)	0 - 40 °C
Built-in speaker(s) *	✓	Operating relative humidity (H-H)	10 - 80%
Number of built-in speakers	2	Storage temperature (T-T)	-10 - 60 °C
RMS rated power	10 W	Storage relative humidity (H-H)	5 - 85%
Design		Logistics data	
Product design *	Digital signage flat panel	Harmonized System (HS) code	85285210
Placement supported *	Indoor	Technical details	
Orientation	Horizontal	Sustainability certificates	ENERGY STAR





5028695120839

0805736073515



805736073515

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.