NEC MultiSync M321 Pannello piatto per segnaletica digitale 81,3 cm (32") LCD 450 cd/m 2 Full HD Nero

Marchio: NEC Famiglia del prodotto: Codice prodotto: 60005288

MultiSync

Nome del prodotto: M321

NEC MultiSync M321. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 81,3 cm (32"), Tecnologia display: LCD, Risoluzione del display: 1920 x 1080 Pixel, Luminosità schermo: 450 cd/m², Tipologia HD: Full HD. Colore del prodotto: Nero





Display		Design	
Panel type	IPS	Product colour *	Black
LED backlight	✓	VESA mounting *	✓
Display diagonal *	81.3 cm (32")	Panel mounting interface	100 x 100,200 x 200 mm
Display technology *	LCD	Bezel width (bottom)	1.72 cm
Display resolution *	1920 x 1080 pixels	Bezel width (side)	1.19 cm
Display brightness *	450 cd/m ²	Bezel width (top)	1.19 cm
HD type *	Full HD	Performance	
Touchscreen *	×	Purpose *	Universal
Response time	8 ms	Power	
Contrast ratio (typical)	1100:1		
Viewing angle, horizontal	178°	Power consumption (typical) *	40 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.5 W
Display number of colours	16.78 million colours	AC input voltage	100 - 240 V
Pixel pitch	0.364 x 0.364 mm	Computer system	
Active display area (W x H)	698.4 x 392.9 mm	Computer system *	×
Horizontal scan range	15 - 136 kHz 23 - 76 Hz	Built-in processor *	×
Vertical scan range High Dynamic Range (HDR)	23 - 76 HZ	Weight & dimensions	
supported	✓	-	6.3 kg
Haze rate	28%	Weight Width (with stand)	726.6 mm
Ports & interfaces		Depth (with stand)	267.7 mm
HDMI ports quantity *	2	Height (with stand)	476.3 mm
DVI port *	X	Weight (with stand)	8.2 kg
VGA (D-Sub) input ports	1		
DisplayPorts quantity *	1	Packaging data	
USB port *	·	Package width	870 mm
•	-	Package depth	160 mm
Ethernet LAN (DL 45) ports	1	Package height	527 mm
Ethernet LAN (RJ-45) ports	1	Package weight	9.8 kg
Number of speaker outputs	1	Packaging content	
RS-232C	1	Remote control included	✓
Remote (IR) input	1	Batteries included	✓
Audio		Cables included	AC, HDMI
Built-in speaker(s) *	✓		

Audio		Operational conditions	
Number of built-in speakers	2	Operating temperature (T-T)	0 - 40 °C
RMS rated power	10 W	Operating relative humidity (H-H)	20 - 80%
Design		Storage temperature (T-T)	-20 - 60 °C
Product design *	Digital signage flat panel	Storage relative humidity (H-H)	10 - 80%
Placement supported *	Indoor	Logistics data	
Orientation	Horizontal/Vertical	Harmonized System (HS) code	85285210









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.