



## Canon PGI-550XL PGBK w/sec cartuccia d'inchiostro 1 pz Originale Resa elevata (XL)

**Marchio :** Canon

**Codice prodotto:** 6431B004

**Nome del prodotto :** PGI-550XL PGBK w/sec

PGI-550XL PGBK

Canon PGI-550XL PGBK w/sec cartuccia d'inchiostro 1 pz Originale Resa elevata (XL):

Questo inchiostro nero a pigmenti dalla resa elevata permette di stampare fino a 1,6 volte in più rispetto al suo equivalente standard. L'inchiostro nero a pigmenti viene utilizzato per stampare documenti e assicura un testo nitido e chiaro a lungo. Il serbatoio d'inchiostro da 22 ml consente di stampare fino a 500 pagine di documenti A4.

Canon PGI-550XL PGBK w/sec. Tipo di cartuccia: Resa elevata (XL), Tipo di inchiostro nero: Inchiostro a base di pigmento, Quantità per pacco: 1 pz



| Caratteristiche                   |                               | Condizioni ambientali                   |               |
|-----------------------------------|-------------------------------|---|---------------|
| Tipo di inchiostro nero           | Inchiostro a base di pigmento | Intervallo temperatura di funzionamento | 15 - 35 °C    |
| Tecnologia di stampa              | Stampa inkjet                 | Umidità                                 | 5 - 95%       |
| Compatibilità *                   | Canon PIXMA MG5450            | Dimensioni e peso                       |               |
| Quantità per pacco *              | 1 pz                          | Tipo di imballo                         | Blister       |
| Tipo *                            | Originale                     | Dati logistici                          |               |
| Tipo di cartuccia                 | Resa elevata (XL)             | Codice del Sistema Armonizzato (SA)     | 84439990      |
| A colori                          | ✗                             | Altre caratteristiche                   |               |
| Condizioni ambientali             |                               | Produzione pagine note a piè di pagina  | ISO/IEC 24734 |
| Range di umidità di funzionamento | 5 - 95%                       |   |               |
| Intervallo di temperatura         | 10 - 35 °C                    |   |               |



8714574584287

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2024. Prints or copies of Information are only valid on the printed Publication date