



## HP Testina di stampa originale 6ZA17AE, nero

**Marchio :** HP

**Codice prodotto:** 6ZA17AE

**Nome del prodotto :** Testina di stampa originale HP 6ZA17AE, nero

Testina di stampa originale HP 6ZA17AE, nero

[HP Testina di stampa originale 6ZA17AE, nero:](#)

Le testine di stampa HP lavorano in sinergia con il sistema con serbatoi di inchiostro HP e gli inchiostri originali HP.<sup>[1]</sup> Continua a stampare con testine di stampa a rapida installazione e ottieni l'affidabilità e la qualità professionale HP.

HP Testina di stampa originale 6ZA17AE, nero. Compatibilità: Le testine di stampa originali HP GT sono compatibili con: HP Smart Tank 5100, 555, 559, 570, 655,...., Tecnologia di stampa: Getto termico d'inchiostro, Colori di stampa: Nero. Larghezza: 113 mm, Profondità: 37 mm, Altezza: 115 mm. Larghezza imballo: 116,3 mm, Profondità imballo: 36,5 mm, Altezza imballo: 100,9 mm. Numero di cartoni per pallet: 40 pz, Quantità per pallett: 2400 pz, Numero di livelli per pallet: 5 pz



Performance		Operational conditions	
Compatibility *	HP GT Printheads work with: HP Smart Tank 5100, 555, 559, 570, 655, 7305, 7308 HP Tank 5100	Storage temperature (T-T)	-40 - 60 °C
Print technology	Thermal inkjet	Logistics data	
Printing colours	Black	Master (outer) cases per pallet	40 pc(s)
Country of origin	Malaysia	Pallet dimensions (W x D x H)	1198.88 x 1016 x 845 mm
Weight & dimensions		Products per pallet	2400 pc(s)
Width	113 mm	Layers per pallet	5 pc(s)
Depth	37 mm	Pallet dimensions (W x D x H) (imperial)	1198.9 x 1016 x 845.1 mm (47.2 x 40 x 33.3")
Height	115 mm	Pallet weight (imperial)	167.3 kg (368.9 lbs)
Weight	69 g	Pallet gross weight	167.3 g
Packaging data		Products per master (outer) case	60 pc(s)
Package width	116.3 mm	Master (outer) case gross weight	3.31 g
Package depth	36.5 mm	Quantity per pack	1 pc(s)
Package height	100.9 mm	Harmonized System (HS) code	84439990
Package weight	50 g	Technical details	
Package type	Box	Box contents	2 printheads: black, tri-colour; Insert with printhead replacement instructions
Operational conditions			
Operating temperature (T-T)	15 - 30 °C		
Operating relative humidity (H-H)	20 - 80%		



0193905589869



193905589869

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.