

Lenovo ThinkSystem ST650 V3 server Tower Intel® Xeon® Silver 4509Y 2,6 GHz 32 GB DDR5-SDRAM 1100 W



Marchio : Lenovo

Famiglia del prodotto:
ThinkSystem

Codice prodotto:
7D7AA02DEA

Nome del prodotto : ST650 V3

Lenovo ThinkSystem ST650 V3. Famiglia processore: Intel® Xeon® Silver, Frequenza del processore: 2,6 GHz, Modello del processore: 4509Y. RAM installata: 32 GB, Tipo di RAM: DDR5-SDRAM, Struttura memoria: 1 x 32 GB. Collegamento ethernet LAN, Tecnologia di cablaggio: 10/100/1000Base-T(X). Alimentazione: 1100 W, Supporto Redundant power supply (RPS). Tipo di case: Tower

Processor		Design	
Processor manufacturer *	Intel	Chassis type *	Tower
Processor family *	Intel Xeon Silver	Redundant fans support	✔
Processor model *	4509Y	Performance	
Processor frequency *	2.6 GHz	Performance management	XClarity Controller Platinum
Processor boost frequency	4.1 GHz	Trusted Platform Module (TPM)	✔
Processor cores	8	Trusted Platform Module (TPM) version	2.0
Processor cache	22.5 MB	Software	
Number of processors installed	1	Operating system installed *	✖
Memory		Compatible operating systems * Microsoft Windows Server 2019 Microsoft Windows Server 2022 Red Hat Enterprise Linux 8.6 Red Hat Enterprise Linux 8.7 Red Hat Enterprise Linux 9.0 Red Hat Enterprise Linux 9.1 SUSE Linux Enterprise Server 15 SP4 SUSE Linux Enterprise Server 15 Xen SP4 Ubuntu 22.04 LTS 64-bit VMware ESXi 7.0 U3 VMware ESXi 8.0 U1	
Internal memory *	32 GB		
Internal memory type *	DDR5-SDRAM		
ECC	✔		
Memory layout (slots x size)	1 x 32 GB		
Maximum internal memory *	4 TB		
Storage		Power	
Maximum storage capacity *	320 TB	Redundant power supply (RPS) support *	✔
RAID support *	✔	Power supply *	1100 W
RAID levels	0, 1, 10, JBOD	Number of redundant power supplies installed	1
Supported RAID controllers	9350-8i	Power supply input frequency	50 - 60 Hz
Hot-swap	✔	Operational conditions	
Optical drive type *	✖	Operating temperature (T-T)	5 - 45 °C
Internal drive bays	8	Storage temperature (T-T)	-40 - 60 °C
Network		Operating relative humidity (H-H)	8 - 90%
LAN controller	Broadcom 57416	Storage relative humidity (H-H)	8 - 90%
Ethernet LAN	✔	Operating altitude	0 - 3050 m
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Ethernet interface type	10 Gigabit Ethernet	Width	175 mm
Ports & interfaces		Depth	734 mm
Ethernet LAN (RJ-45) ports *	2	Height	462 mm
USB 2.0 ports quantity	1	Weight	39.1 kg
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	5		
VGA (D-Sub) ports quantity	1		
Serial ports quantity	1		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date