Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS
Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL
Model identifier: 9290023063

Type of light source: Lighting technology used: Non-directional **LED NDLS** directional: Light source cap-type E27 (or other electric interface) Mains or non-mains: MLS Connected light No source (CLS): Colour-tuneable light source: No Envelope: High luminance light source: No Anti-glare shield: No Dimmable: No **Product parameters** Parameter Value Parameter Value **General product parameters:** F Energy consumption in on-8 Energy efficiency mode (kWh/1000 h), rounded class up to the nearest integer Useful luminous flux (фuse), 806 in Correlated 4 000 colour indicating if it refers to the flux Sphere (360°) temperature, in a sphere (360°), in a wide rounded to the cone (120º) or in a narrow cone nearest 100 Κ, (90°) or the range of correlated colour temperatures, rounded to the nearest 100 K, that

			can be set	
On-mode expressed in W	power (P _{on}), /	8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without	Height	108	Spectral power	See image
	Width	60	distribution in the	in last page
	Depth	60		
			·	Page 1

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60			
		Chromaticity coordinates (x and y)	0,382			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,93					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,55	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

