


U[⚡]power



Atlantis

 **LINE
INTERACTIVE**



750
VA

ONEPOWER X1000
Line-Interactive UPS

750 VA

ONEPOWER X1000

Line-Interactive UPS



La linea di prodotti OnePower è in grado di proteggere qualsiasi sistema elettrico o elettronico nel caso in cui si verifichi una variazione della tensione di alimentazione.

Le principali caratteristiche di questa linea di UPS sono:

- Microprocessore integrato
- Stabilizzazione del voltaggio in entrata grazie alla funzionalità AVR
- Tempo di intervento minore di 6ms
- Protezione contro il corto circuito ed il sovraccarico
- Batteria facilmente sostituibile

La facile installazione e l'uso intuitivo rendono tali prodotti adatti a qualsiasi utenza.

LINE
INTERACTIVE

375
WATT

CPU

AVR



BATTERY
12V@4.5A/h

TECHNICAL SPECIFICATIONS

POWER RATING (VA)	750
POWER RATING (W)	375
INPUT	<ul style="list-style-type: none">• Voltage: 170-280V• Frequency: 50Hz±5%
OUTPUT	<ul style="list-style-type: none">• Voltage: 230V(±10%) [AC] / 230V(±10%) [INV]• Frequency: 50Hz (±1%)• AVR: Built-in• Waveform: Simulated SineWave
TRANSFER Line/Battery	Less than 2-6 ms (typical)
EFFICIENCY	Total Efficiency Over 80%
BATTERY	<ul style="list-style-type: none">- Voltage: 12VDC- Capacity: 12V/4.5Ah- Quantity: 1- Recharge Time: 4 hours to (90%)- Type: Sealed Maintenance Free Lead Acid VRLA Type
INDICATORS	1 LED: AC Mode (Green lighting), Battery mode (Green flashing every 10 seconds), Low Battery (Green flashing every seconds)
PROTECTION	<ul style="list-style-type: none">- Overload AC Buzzer sound every 0.5 seconds then UPS shuts down after 10 sec (>110%)- Overload Inverter UPS shuts down after 10 seconds (>110%)- Short Circuit INV ICB & Electric Circuit / Short Circuit AC Electric Circuit- Battery Over-drain Two stages: Controlled Battery Low Warning & Cut Off- Spike Suppression Meets EN61000-4-5- Noise Suppression Meets EN50991-1
ALARM	<ul style="list-style-type: none">• Battery Mode (sound every 10 seconds)• Low Battery (sound every seconds)• OverLoad (sound every 0.5 seconds)• Fault (continuously sounding)
CONNECTIONS	Output 2xSchuko (Battery Power Supplied)
BACKUP TIME	5 to 10 mins for typical PC Load
DIMENSIONS (WxHxD)	101 x 142 x 280 mm
NET WEIGHT	3,7 Kg (with Battery)
ENVIRONMENTS	<ul style="list-style-type: none">• Temperature 0°-40° C• Humidity 0-95% (non-condensing)
CERTIFICATION	CE

PUNTI DI FORZA

- Microprocessor Based Design a tecnologia Line-Interactive
- Lo stabilizzatore di tensione multistadio integrato (AVR) garantisce ai carichi collegati un'alimentazione adeguata
- Tempo di intervento 2-6 ms
- Batteria (12V@4.5A/h) per una lunga durata in assenza di rete elettrica
- Gestione avanzata delle Batterie ed estrema semplicità nella sostituzione

Backup Outlets

MAIN POWER



CONTENUTO CONFEZIONE: OnePower X1000 - Manuale utente - Garanzia e documento RAEE

UPS

Code: A03-X1000

EAN: 8026974021430



Atlantis

www.atlantis-land.com

750 VA

ONEPOWER X1000

Line-Interactive UPS



La linea di prodotti OnePower è in grado di proteggere qualsiasi sistema elettrico o elettronico nel caso in cui si verifichi una variazione della tensione di alimentazione.

Le principali caratteristiche di questa linea di UPS sono:

- Microprocessore integrato
- Stabilizzazione del voltaggio in entrata grazie alla funzionalità AVR
- Tempo di intervento minore di 6ms
- Protezione contro il corto circuito ed il sovraccarico
- Batteria facilmente sostituibile

La facile installazione e l'uso intuitivo rendono tali prodotti adatti a qualsiasi utenza.



TECHNICAL SPECIFICATIONS

POWER RATING (VA)	750
POWER RATING (W)	375
INPUT	<ul style="list-style-type: none">• Voltage: 170-280V• Frequency: 50Hz±5%
OUTPUT	<ul style="list-style-type: none">• Voltage: 230V(±10%) [AC] / 230V(±10%) [INV]• Frequency: 50Hz (±1%)• AVR: Built-in• Waveform: Simulated SineWave
TRANSFER Line/Battery	Less than 2-6 ms (typical)
EFFICIENCY	Total Efficiency Over 80%
BATTERY	<ul style="list-style-type: none">- Voltage: 12VDC- Capacity: 12V/4.5Ah- Quantity: 1- Recharge Time: 4 hours to (90%)- Type: Sealed Maintenance Free Lead Acid VRLA Type
INDICATORS	1 LED: AC Mode (Green lighting), Battery mode (Green flashing every 10 seconds), Low Battery (Green flashing every seconds)
PROTECTION	<ul style="list-style-type: none">- Overload AC Buzzer sound every 0.5 seconds then UPS shuts down after 10 sec (>110%)- Overload Inverter UPS shuts down after 10 seconds (>110%)- Short Circuit INV ICB & Electric Circuit / Short Circuit AC Electric Circuit- Battery Over-drain Two stages: Controlled Battery Low Warning & Cut Off- Spike Suppression Meets EN61000-4-5- Noise Suppression Meets EN50991-1
ALARM	<ul style="list-style-type: none">• Battery Mode (sound every 10 seconds)• Low Battery (sound every seconds)• OverLoad (sound every 0.5 seconds)• Fault (continuously sounding)
CONNECTIONS	Output 2xSchuko (Battery Power Supplied)
BACKUP TIME	5 to 10 mins for typical PC Load
DIMENSIONS (WxHxD)	101 x 142 x 280 mm
NET WEIGHT	3,7 Kg (with Battery)
ENVIRONMENTS	<ul style="list-style-type: none">• Temperature 0°-40° C• Humidity 0-95% (non-condensing)
CERTIFICATION	CE

STRENGTHS

- Microprocessor Based Design Line Interactive Topology
- Wide input range application without using battery power (AVR)
- Transfer time 2-6 ms
- Long time backup (12V@4.5A/h)
- Advanced Battery Management & Easy Swappable Battery Function

Backup Outlets

MAIN POWER



PACKAGE CONTENTS: OnePower X1000 - User Manual - Warranty and WEEE document

UPS
Code: A03-X1000
EAN: 8026974021430



Atlantis
www.atlantis-land.com