

OLD68-2D



2D HANDFREE

Barcode Reader



QR CODE
reader



1,5m Drop
resistance



lettura
continua

SUPPORTA

Codici tradizionali

Codici bidimensionali

SPEEDSCAN

OLD68-2D

SPEEDSCAN

2D HANDFREE

Barcode Reader

CODICI A BARRE SUPPORTATI

(1D) UPC/EAN/(UPCA/UPCE/UPCE1/EAN-8/EAN-13/JAN-8/JAN-13 plus supplemental, ISBN, ISSN, Coupon Code), Code 39, Code 39 Full ASCII, Trioptic, Code 32 (Italian Pharmacode), Code 128, (Standard, Full ASCII, UCC/EAN-128, ISBT-128 Concatenated), Code 93, Codeabar/NW7, Interleaved 2 of 5, Discrete 2 of 5, IATA Chinese 2 of 5, Matrix 2 of 5, Code 11), MSI Plessey, GS1Databar, (Omnidirectional, Truncated, Stacked, Stacked Omnidirectional, Limited, Expanded, Expanded Stacked), (PDF417 var) PDF417 (Standard, Macro), MicroPDF417 (Standard, Marco), Composite Code (CC-A, CC-B, CC-C)

(2D) MaxiCode, Data Matrix, Data Matrix inverse, QR Code, QR Inverse, Micro QR Code, Aztec Code, Aztec Inverse, Postal Code, (Postal) U.S. Posnet and Planet, U.K. Post, Japan Post, Australian Post, Netherlands KIX Code, Royal Mail 4 State Customer, UPU FICS 4 State Postal, USPS 4CB



FEATURES

Optical	Optical sensor	Optical Sensor 752(H) x 480(V) Wide VGA
	Light source	625 nm Aiming LED
	+ Illumination	+ illumination 630nm LED
	Resolution	4 mil (code39), 7,5 mil (Datamatrix), 5 mil (PDF 417)
	Depth of Field	up to 267mm
Electrical	Field of view	46.1° Horiz - 30,4° Vertical
	Voltage	+5V±5%
	Scanning currents	<260 mA
Environment	Standby currents	<150 mA
	Power Consumption	1,4 wats
	Operating temperature	0°C to 40°C / 32°F to 104°F
	Storage temperature	-40° to 70° C (-40° to 158°F)
	Light level	Maximum 86,100 Lux. (direct sunlight)
	Operating humidity	95% RH, non-condensing at 122° F/50° C
	Storage humidity	85% RH, non-condensing at 158° F/70° C
Physical	Shock resistance	1.5m drops
	Weight	300g(w/cable)
	Dimensions	140mm(L)x73mm(W)x70mm(H)
	Housing Material	ABS plastic
	Cable Length	~ 150 cm



senore laser
752x480



QR CODE
reader



1,5m Drop
resistance



lettura
continua

BARCODE READER

Codice: A08-OLD68-2D

EAN: 8026974018379



LA CONFEZIONE CONTIENE:

- Lettore di codice a barre
- CD ROM Utility and Manual
- WEEE & Warranty Card

