



**APC AP7821B unità di distribuzione dell'energia (PDU) 8 presa(e)
AC 0U/1U Nero**

Marchio : APC

Codice prodotto: AP7821B

Nome del prodotto : AP7821B



208/230 V, 8x IEC 320 C13, IEC-320 C20, 1U, 444 x 102 x 44 mm, 1740 g
APC AP7821B. Tipi di PDU: Monitorata, Capacità di rack: 0U/1U, Montaggio: Orizzontale/Verticale.
Quantità prese AC: 8 presa(e) AC, Tipo di uscita AC: Accoppiatore C13, Presa di corrente: Accoppiatore C20. Monitoraggio: Corrente, Potenza, Tension. Voltaggio nominale di entrata: 200-230 V, Corrente massima: 20 A, Frequenza di ingresso AC: 50 - 60 Hz. Certificati di conformità: RoHS, Certificazione: cUL, C-tick, CE, CSA, FCC 15 A, GOST, ICES-003, UL 60950, UL Listed, VCCI, VDE

Design		Certificates	
PDU types *	Metered	Certification	cUL, C-tick, CE, CSA, FCC 15 A, GOST, ICES-003, UL 60950, UL Listed, VCCI, VDE
Rack capacity *	0U/1U		
Mounting	Horizontal/Vertical		
Product colour	Black		
Ports & interfaces		Operational conditions	
AC outlets quantity *	8 AC outlet(s)	Operating temperature (T-T)	-5 - 45 °C
Power plug	C20 coupler	Storage temperature (T-T)	-25 - 65 °C
AC outlet types *	C13 coupler	Operating relative humidity (H-H)	5 - 95%
Input connection type	IEC-320 C20	Storage relative humidity (H-H)	5 - 95%
Features		Operating altitude	0 - 3000 m
LED indicators	✓	Non-operating altitude	0 - 15000 m
Management features		Weight & dimensions	
Monitoring	Current, Power, Voltage	Width	444 mm
Power		Depth	102 mm
Nominal input voltage *	200-230 V	Dimensions (WxDxH)	444 x 102 x 44 mm
AC input frequency	50 - 60 Hz	Height	44 mm
Maximum current *	20 A	Weight	1.74 kg
Output voltage	230 V	Packaging content	
Load capacity	3680 VA	Packaging content	Cord Retention Bracket(s), Installation Guide, Rack Mounting Brackets, User Manual
Maximum input current per phase	16 A	Packaging data	
Maximum total current draw per phase	16 A	Package dimensions (WxDxH)	470 x 337 x 64 mm
Maximum power	3680 W	Package weight	2.92 kg
Certificates		Package width	470 mm
Compliance certificates	RoHS	Package depth	337 mm
		Package height	64 mm



0731304331513



731304331513

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-JAN-2025. Prints or copies of Information are only valid on the printed Publication date