



APC BR1600MI gruppo di continuità (UPS) A linea interattiva 1,6 kVA 960 W 8 presa(e) AC

Marchio : APC

Codice prodotto: BR1600MI

Nome del prodotto : BR1600MI

APC BR1600MI. Topologia UPS: A linea interattiva, Potenza in uscita: 1,6 kVA, Potenza in uscita: 960 W. Tipo di uscita AC: Accoppiatore C13, Presa di corrente: Accoppiatore C14, Quantità prese AC: 8 presa(e) AC. Tecnologia batteria: Acido piombo (VRLA), Durata della batteria (max): 5 anno/i, Tempo di ricarica: 16 h. Fattore di forma: Tower, Colore del prodotto: Nero, Lunghezza cavo: 1,83 m. Larghezza: 250 mm, Profondità: 382 mm, Altezza: 100 mm



Features		Battery	
UPS topology *	Line-Interactive	Cold start	✓
Output power capacity *	1.6 kVA	Design	
Output power *	960 W	Form factor *	Tower
Waveform *	Sine	Cable length	1.83 m
Input operation voltage (min) *	176 V	Cooling type	Passive
Input operation voltage (max) *	294 V	Product colour *	Black
Input frequency *	50/60 Hz	Display type	LCD
Output frequency	50/60 Hz	LED indicators	✓
Automatic Voltage Regulation (AVR)	✓	Certification	A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI
Maximum current	10 A	Operational conditions	
Surge energy rating	509 J	Operating temperature (T-T)	0 - 40 °C
ECO mode	✓	Storage temperature (T-T)	-15 - 45 °C
Noise level	45 dB	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	Storage relative humidity (H-H)	0 - 95%
Surge protection features	Network	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Weight & dimensions	
Ports & interfaces		Width	250 mm
AC outlet types	C13 coupler	Depth	382 mm
Power plug	C14 coupler	Height	100 mm
AC outlets quantity	8 AC outlet(s)	Weight	10.9 kg
USB port	✓	Package width	485 mm

Ports & interfaces		Weight & dimensions	
USB 2.0 ports quantity	1	Package depth	225 mm
Ethernet LAN (RJ-45) ports	2	Package height	330 mm
Cabling technology	10/100/1000Base-T(X)	Package weight	11.7 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Cables included	USB cable
Battery life (max)	5 year(s)	Manual	✓
Battery recharge time	16 h		
Hot-swap battery	✓	Logistics data	
Automatic battery test	✓	Harmonized System (HS) code	85078000
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304346913



731304346913

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.