D-Link

D-Link DAP-3711 ponte e ripetitore Bridge di rete 867 Mbit/s Bianco

Marchio : D-Link   **Codice prodotto:** DAP-3711

Nome del prodotto : DAP-3711

D-Link DAP-3711. Velocità massima di trasferimento dati: 867 Mbit/s, Distanza massima di trasferimento: 5000 m. Design dell'antenna: Interno, Livello di guadagno dell'antenna (max): 15 dBi. Banda Wi-Fi: Singola banda (5 GHz), Intervallo di trasferimento dei dati WLAN (max): 867 Mbit/s, Banda di frequenza: 5.180 - 5.825 GHz. Tipo di interfaccia LAN Ethernet: Gigabit Ethernet, Velocità trasferimento Ethernet LAN: 100,1000 Mbit/s, Standard di rete: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11n. Tecnologia di connessione: Con cavo e senza cavo

Data transmission

Maximum data transfer rate *	867 Mbit/s
Maximum transfer distance	5000 m

Antenna

Antenna design	Internal
Antenna gain level (max)	15 dBi

Wireless LAN features

Wi-Fi	✔
Wi-Fi band	Single-band (5 GHz)
WLAN data transfer rate (max)	867 Mbit/s
Frequency band	5.180 - 5.825 GHz
Signal strength	27 dBm
Channels quantity	2 channels

Network

Ethernet LAN	✔
Ethernet LAN interface type	Gigabit Ethernet
Ethernet LAN data rates	100,1000 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11n
Cabling technology	10/100/1000Base-T(X)
Wireless Distribution System (WDS) bridge	✔

Ports & interfaces

Connectivity technology	Wired & Wireless
Ethernet LAN (RJ-45) ports	2

Security

Security algorithms	128-bit AES
MAC address filtering	✔

Management features

Web-based management	✔

Features

Product type *	Network bridge

Features

Material	Acrylonitrile butadiene styrene (ABS)
Mounting type	Pole
Product colour	White
LED indicators	LAN, Power, Signal strength, WLAN
Reset button	✔
International Protection (IP) code	IP66
Surge protection	✔

Power

Power source type	PoE
Power consumption (typical)	15 W
Power over Ethernet (PoE)	✔
Power over Ethernet (PoE) voltage	24 V

Operational conditions

Operating temperature (T-T)	-40 - 65 °C
Operating relative humidity (H-H)	0 - 90%
Storage temperature (T-T)	-40 - 85 °C
Storage relative humidity (H-H)	0 - 90%

Certificates

Certification	CE, FCC

Weight & dimensions

Width	288 mm
Depth	45 mm
Height	88 mm
Weight	600 g

Packaging data

Quantity per pack	1 pc(s)

Logistics data

Harmonized System (HS) code	85176990

0790069457272

790069457272