

## DELL E Series E2225H Monitor PC 54,5 cm (21.4") 1920 x 1080 Pixel Full HD LCD Nero

Marchio : DELL

Famiglia del prodotto: E Series Codice prodotto: E2225H

Nome del prodotto : E2225H

DELL E Series E2225H. Dimensioni diagonale schermo: 54,5 cm (21.4"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Tempo di risposta: 8 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Montaggio standard VESA. Colore del prodotto: Nero





## Display

Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type *	54.5 cm (21.4") 1920 x 1080 pixels Full HD 16:9 LCD VA	Tilt adjustment Tilt angle range On Screen Display (OSD) Plug and Play LED indicators	✓ -5 - 21° ✓
LED backlight		Power	
Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen Screen shape * Supported graphics resolutions	<ul> <li>✓</li> <li>✓</li> <li>Edge LED</li> <li>×</li> <li>250 cd/m<sup>2</sup></li> <li>8 ms</li> <li>✓</li> <li>Flat</li> <li>640 x 480 (VGA), 720 x 400, 800 x</li> <li>600 (SVGA), 1024 x 768 (XGA),</li> <li>1152 x 864 (XGA+), 1280 x 1024</li> <li>(SXGA), 1280 x 720 (HD 720), 1600</li> <li>x 900, 1920 x 1080 (HD 1080)</li> <li>480p, 576p, 720p, 1080p</li> </ul>	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Power supply type Energy efficiency scale	D Not available 12 kWh 11.9 W 0.3 W 19 W 0.3 W 100 - 240 V 50/60 Hz Internal A to G
Contrast ratio (typical) * Maximum refresh rate *	3000:1 75 Hz	Operational conditions	
Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density	178° 178° 16.7 million colours 5 ms 0.2493 x 0.241 mm 103 ppi	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
Horizontal scan range	30 - 84 kHz	Weight & dimensions	
Vertical scan range Viewable size, horizontal Viewable size, vertical Display diagonal (metric)	50 - 76 Hz 47.9 cm 26 cm 544.85 cm	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand)	504.3 mm 171 mm 384.2 mm 2.67 kg

Display		Weight & dimensions	
High Dynamic Range (HDR)		Width (without stand)	504.3 mm
supported	×	Depth (without stand)	49.6 mm
Surface hardness	3H	Height (without stand)	295.4 mm
NTSC coverage (typical)	83%	Weight (without stand)	2.34 kg
Performance		Bezel width (side)	1.28 cm
NVIDIA G-SYNC *	×	Bezel width (top)	1.28 cm
AMD FreeSync *	×	Bezel width (bottom)	1.69 cm
Flicker-free technology	1	Packaging data	
Low Blue Light technology	1	Package weight	4.18 kg
Multimedia		Packaging content	
Built-in speaker(s) *	x	Stand included	1
Built-in camera *	×	Cables included	AC, DisplayPort, VGA
		Quick start guide	<ul> <li>Image: A set of the set of the</li></ul>
Design	11	Power cable length	1.8 m
Market positioning * Product colour *	Home Black	Sustainability	
Front bezel colour	Black	Sustainability certificates	ENERGY STAR, TCO
Detachable stand	1	Doesn't contain	Arsenic, Mercury, PVC/BFR
Feet colour	Black	Carbon footprint	
Ports & interfaces		Total carbon footprint (kg of CO2e)	124
Built-in USB hub *	×	Carbon emissions, manufacturing (kg of CO2e)	56
VGA (D-Sub) ports quantity HDMI *	1 ×	Carbon emissions, logistics (kg of CO2e)	8
DisplayPorts quantity	1	Carbon emissions, energy usage (kg of CO2e)	59
DisplayPort version	1.2	Carbon emissions, end-of-life (kg of	_
Headphone out *	×	CO2e)	1
HDCP	<ul> <li>Image: A set of the set of the</li></ul>	Total carbon emissions, w/o use phase (kg of CO2e)	65
HDCP version	1.4	PAIA version	GaBi version 1, 2024
Network		Other features	
Wi-Fi	×	Compliance certificates	RoHS
Ergonomics			
VESA mounting *	1		
Panel mounting interface	100 x 100 mm		
Wall mountable	1		
Cable lock slot *	1		
Cable lock slot type	Kensington		
Height adjustment *	×		
Pivot	×		
Swivelling	×		



5397184822173

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.