

## **DELL E Series Monitor 27 - E2723HN**

## Marchio : DELL

Famiglia del prodotto: E Series Codice prodotto: DELL-E2723HN

Nome del prodotto : Monitor Dell 27 - E2723HN

- 68.6cm (27") Full HD 1920 x 1080 LED IPS - 8ms, 16:9, 300cd/m<sup>2</sup>, 1000:1 - VGA, HDMI 68.6cm (27") Full HD 1920 x 1080 LED IPS, 16:9, 300cd/m<sup>2</sup>, 16.7M, 8ms, 178°/178°, 1000:1

## DELL E Series Monitor 27 - E2723HN:

Monitor Full HD da 27 pollici con un ampio angolo di visione e un design eco-consapevole a un prezzo accessibile.


DELL E Series Monitor 27 - E2723HN. Dimensioni diagonale schermo: 68,6 cm (27"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LCD, Tempo di risposta: 8 ms, Rapporto d'aspetto nativo: 16:9, Angolo di visualizzazione (orizzontale): 178°, Angolo di visualizzazione (verticale): 178°. Montaggio standard VESA. Colore del prodotto: Nero





Display		Power	
Display diagonal * Display resolution * HD type *	68.6 cm (27") 1920 x 1080 pixels Full HD	Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours *	Not available 17 kWh
Native aspect ratio *	16:9	Power consumption (typical) *	14.8 W
Display technology *	LCD	Power consumption (standby) *	0.3 W
Panel type *	IPS	Power consumption (max)	30 W
Backlight type	LED	Power consumption (off)	0.25 W
Touchscreen *	×	AC input voltage	100 - 240 V
Display brightness (typical)	300 cd/m <sup>2</sup>	AC input frequency	50 - 60 Hz
Response time *	8 ms	Input current	1.5 A
Anti-glare screen	1	Power supply type	Internal
Screen shape *	Flat	Energy efficiency scale	A to G
Contrast ratio (typical) *	1000:1	European Product Registry for Energy Labelling (EPREL) code	1004223
Maximum refresh rate *	60 Hz	Operational conditions	
Viewing angle, horizontal	178°	Operating temperature (T-T)	0 - 40 °C
Viewing angle, vertical	178° 16.7 million colours	Storage temperature (T-T)	-20 - 60 °C
Display number of colours * Response time (fast)	5 ms	Operating relative humidity (H-H)	10 - 80%
Pixel pitch	0.3114 x 0.3114 mm	Storage relative humidity (H-H)	5 - 90%
Pixel density	81 ppi	Operating altitude	0 - 5000 m
Horizontal scan range	30 - 85 kHz	Non-operating altitude	5000 - 12192 m
Vertical scan range	48 - 75 Hz	Weight & dimensions	
Viewable size, horizontal	59.8 cm	5	623.3 mm
Viewable size, vertical	33.6 cm	Width (with stand) Depth (with stand)	188.3 mm
Viewable size diagonal	68.6 cm	Height (with stand)	458.9 mm
High Dynamic Range (HDR) supported	×	Weight (with stand)	5.59 kg
sRGB coverage (typical)	72%	Width (without stand)	623.3 mm
NTSC coverage (typical)	83%	Depth (without stand)	50.4 mm
Performance		Height (without stand) Weight (without stand)	370.9 mm 4.86 kg
NVIDIA G-SYNC *	×	Bezel width (side)	1.27 cm
AMD FreeSync *	×	Bezel width (top)	1.29 cm
,		Bezel width (bottom)	1.61 cm

Multimedia		Packaging data	
Built-in speaker(s) *	×	Package width	716.2 mm
Built-in camera *	×	Package depth	454.6 mm
Design		Package height Package weight	134.6 mm 6.81 kg
Market positioning *	Business		0.01 KY
Product colour *	Black	Packaging content	
Front bezel colour	Black	Stand included	✓
Detachable stand	<ul> <li>Image: A set of the set of the</li></ul>	Cables included	AC, HDMI, VGA
Feet colour	Black	Quick start guide	J
Ports & interfaces		Sustainability	
Built-in USB hub *	×	Sustainability certificates	ENERGY STAR
VGA (D-Sub) ports quantity	1	Doesn't contain	PVC/BFR
HDMI *	✓	Carbon footprint	
HDMI ports quantity	1	Total carbon footprint (kg of CO2e)	526
HDMI version Headphone out *	1.4 ×	Total carbon emissions, standard deviation (kg of CO2e)	130
AC (power) in	<b>v</b>	Carbon emissions, manufacturing (kg of CO2e)	299
Network		Carbon emissions, logistics (kg of	63
Wi-Fi	×	CO2e) Carbon emissions, energy usage (kg	
Ergonomics		of CO2e)	160
VESA mounting *	1	Carbon emissions, end-of-life (kg of CO2e)	4
Panel mounting interface Cable lock slot *	100 x 100 mm	Total carbon emissions, w/o use phase (kg of CO2e)	366
Height adjustment *	×	PAIA version	1.3.0
Pivot	×	Other features	
Swivelling	×	Heavy metals free	Hg (mercury)
Tilt adjustment	1	Compliance certificates	RoHS
Tilt angle range	-5 - 21°	Logistics data	
On Screen Display (OSD)	✓	Harmonized System (HS) code	85285210
Plug and Play	✓	- · ·	
LED indicators	Image: A start of the start		
Power			
Energy efficiency class (SDR) *	D		



5397184656822

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.