

Hikvision DS-3E0310P-E/M switch di rete Non gestito L2 Fast Ethernet (10/100) Supporto Power over Ethernet (PoE) Nero



Marchio : Hikvision

Codice prodotto: DS-3E0310P-E/M

Nome del prodotto : DS-3E0310P-E/M

Hikvision DS-3E0310P-E/M. Tipo interruttore: Non gestito, Livello del commutatore: L2. Tipo di porte RJ-45: Fast Ethernet (10/100), Quantità di porte RJ-45: 10. Full duplex. Dimensioni tavola MAC: 16000 voci, Capacità di commutazione: 5,6 Gbit/s. Standard di rete: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Supporto Power over Ethernet (PoE)

Caratteristiche di gestione		Design	
Tipo interruttore *	Non gestito		FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010 +A1: 2015); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016) UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CELVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013)
Livello del commutatore	L2		
Connettività		Certificazione	
Quantità di porte RJ-45 *	10		
Tipo di porte RJ-45 *	Fast Ethernet (10/100)		
Quantità di porte Fast Ethernet (rame)	8		
Quantità di porte Gigabit Ethernet (rame)	2		
Collegamento in rete		Gestione energetica	
Standard di rete *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Fonte di alimentazione inclusa *	✓
Supporto 10G *	✗	Consumo energetico (max)	65 W
Tecnologia Ethernet su cavi in rame	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE)	
Full duplex	✓	Supporto Power over Ethernet (PoE) *	✓
Auto MDI/MDI-X	✓	Quantità di porte Power over Ethernet plus (PoE+)	8
Velocità trasferimento Ethernet LAN	10,100,1000 Mbit/s	Bilancio energetico totale del PoE	60 W
Trasmissione dati		Condizioni ambientali	
Capacità di commutazione *	5,6 Gbit/s	Intervallo temperatura di funzionamento	-10 - 40 °C
tasso di inoltrò	4,1664 Mpps	Intervallo di temperatura	-40 - 85 °C
Dimensioni tavola MAC *	16000 voci	Range di umidità di funzionamento	5 - 95%
Store-and-forward	✓	Umidità	5 - 95%
Design		Dimensioni e peso	
Colore del prodotto	Nero	Larghezza	217,6 mm
Materiale della scocca	Metallo	Profondità	103,3 mm
Indicatori LED	✓	Altezza	27,8 mm
		Peso	555 g
		Dati su imballaggio	
		Peso dell'imballo	1,2 kg
		Sostenibilità	
		Conformità alla sostenibilità	✓
		Certificati di sostenibilità	CE, RoHS



6941264044413

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.