

## Hikvision DS-3T0506HP-E/HS switch di rete Non gestito Gigabit Ethernet (10/100/1000) Supporto Power over Ethernet (PoE) Nero

**Marchio :** Hikvision

**Codice prodotto:** DS-3T0506HP-E/HS

**Nome del prodotto :** DS-3T0506HP-E/HS

Hikvision DS-3T0506HP-E/HS. Tipo interruttore: Non gestito. Tipo di porte RJ-45: Gigabit Ethernet (10/100/1000), Quantità di porte RJ-45: 4. Full duplex. Dimensioni tavola MAC: 4000 voci, Capacità di commutazione: 22 Gbit/s. Standard di rete: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Voltaggio input DC: 48 - 57 V. Supporto Power over Ethernet (PoE)



Caratteristiche di gestione		Design	
Tipo interruttore *	Non gestito		
<b>Connettività</b>			
Quantità di porte RJ-45 *	4		
Tipo di porte RJ-45 *	Gigabit Ethernet (10/100/1000)		
Porte Fibre Channel	2	Certificazione	FCC (47 CFR 15, B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010 +A1: 2015); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: 6, 2016) UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CELVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013) CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach ((EC) 1907/2006)
Connettore a fibra ottica	SFP		
<b>Collegamento in rete</b>			
Standard di rete *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z		
Supporto 10G *	✗	<b>Gestione energetica</b>	
Full duplex	✓	Voltaggio input DC	48 - 57 V
Auto MDI/MDI-X	✓	Consumo energetico (max)	65 W
<b>Trasmissione dati</b>			
Capacità di commutazione *	22 Gbit/s	<b>Power over Ethernet (PoE)</b>	
tasso di inoltrò	8,928 Mpps	Supporto Power over Ethernet (PoE) *	✓
Dimensioni tavola MAC *	4000 voci	Quantità porte Power over Ethernet (PoE)	3
Store-and-forward	✓	Bilancio energetico totale del PoE	60 W
<b>Design</b>			
Montaggio rack *	✗	<b>Condizioni ambientali</b>	
Colore del prodotto	Nero	Intervallo temperatura di funzionamento	-30 - 65 °C
Materiale della scocca	Metallo	Intervallo di temperatura	-40 - 85 °C
		Range di umidità di funzionamento	5 - 95%
		Umidità	5 - 95%
		<b>Dimensioni e peso</b>	
		Larghezza	158 mm
		Profondità	101,2 mm
		Altezza	31,6 mm
		Peso	380 g
		<b>Dati su imballaggio</b>	
		Peso dell'imballo	940 g



6941264038351



0842571132960



842571132960

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.