# NETGEAR GS724Tv6 Gestito L2+/L3 Gigabit Ethernet (10/100/1000) 1U Blu, Grigio

Marchio : NETGEAR

Nome del prodotto : GS724Tv6

Codice prodotto: GS724T-600EUS

NETGEAR GS724Tv6. Tipo interruttore: Gestito, Livello del commutatore: L2+/L3. Tipo di porte RJ-45: Gigabit Ethernet (10/100/1000), Quantità di porte RJ-45: 24. Full duplex. Dimensioni tavola MAC: 16000 voci, Capacità di commutazione: 52 Gbit/s. Standard di rete: IEEE 802.1D, IEEE 802.1ab, IEEE 802.1as, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE.... Connettore di alimentazione: Jack DC-ingresso. Montaggio rack, Fattore di forma: 1U

Management features

Switch type *	Managed
Switch layer	L2+/L3
Quality of Service (QoS) support	✔
Web-based management	✔
System event log	✔

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	24
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
SFP module slots quantity	2
Power connector	DC-in jack

Network

Networking standards *	IEEE 802.1D, IEEE 802.1ab, IEEE 802.1as, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3z
10G support *	✔
Port mirroring	✔
Full duplex	✔
IP routing	✔
Flow control support	✔
Broadcast storm control	✔
Spanning tree protocol	✔
VLAN support	✔
Number of VLANs	256

Data transmission

Switching capacity *	52 Gbit/s
MAC address table *	16000 entries
Number of queues	8
Number of static routes	32
Jumbo frames support	✔

Security

SSH/SSL support	✔

Multicast features

Multicast support	✔
Number of multicast groups filtered	512

Protocols

Management protocols	SNMP v1/v2

Design

Rack mounting *	✔
Form factor	1U
Product colour	Blue, Grey
LED indicators	Activity, Link
Number of fans	0 fan(s)

Performance

Noise level	0 dB
Firmware upgradeable	✔
Mean time between failures (MTBF)	1999946 h

Power

AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (typical)	13.5 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✘

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 90%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 3000 m

Data transmission

Jumbo frames	9000
Packet buffer memory	2 MB

Security

DHCP features	DHCP client, DHCP snooping
Access Control List (ACL)	✔
IGMP snooping	✔
Security algorithms	HTTPS, SSL/TLS
MAC address filtering	✔

Weight & dimensions

Width	328 mm
Depth	169 mm
Height	43 mm
Weight	1.62 kg

0606449169119

606449169119