



itek ICY-4HLA Processore Refrigeratore 12 cm Nero, Bianco

Marchio : itek

Codice prodotto: ITACI4HLA

Nome del prodotto : ICY-4HLA

Dissipatore ad aria ICY-4HLA - Skt universale, 150W TDP, 4 HP, ventola 12cm, full black, ARGB

itek ICY-4HLA Processore Refrigeratore 12 cm Nero, Bianco:

itek ICY 4HLA, è un dissipatore CPU ad aria con socket universale, compatibile con la maggior parte delle piattaforme Intel® e AMD®. E' dotato di tecnologia HDT (HeatPipe Direct Touch) con quattro HeatPipes in rame da 6mm di diametro in grado di offrire la massima dissipazione possibile oltre che un'ottima silenziosità. Ha un TDP da 150W che lo rende ideale per nuovi sistemi performanti oppure in sostituzione di dissipatori "stock" danneggiati o con prestazioni non adeguate. La qualità costruttiva, la silenziosità e la facilità di installazione sono i punti di forza dell'ICY 4HLA. La struttura è "full black" e il logo e la ventola sono dotati di illuminazione RGB Addressable.



Prestazione		Design	
Ambiente di utilizzo *	Processore	Numero di pale del ventilatore	9
Tipo *	Refrigeratore	Numero dei condotti termici	4
Diametro del ventilatore	12 cm	Illuminazione a LED	✓
	LGA 1150 (Socket H3), LGA 1151 (Socket H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1366 (Socket B), LGA 2011 (Socket R), LGA 2066, LGA 775 (Socket T), Socket AM2, Socket AM2+, Socket AM3, Socket AM3+, Socket AM4, Socket FM1, Socket FM2	colore d'illuminazione	Blu, Verde, Rosso
Socket Processori supportati		Connettore ventilatore	4 piedini
	AMD Ryzen™ 3, AMD Ryzen™ 5, AMD Ryzen™ 7, 3rd Generation AMD Ryzen™ 9, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9	Gestione energetica	
Processori compatibili		Voltaggio	12 V
		Tensione stimata	12 V
		Tensione di avvio	6 V
		Corrente limitata	0,3 A
		Thermal Design Power (TDP)	150 W
		Dimensioni e peso	
Velocità (massima) di rotazione	1800 Giri/min	Dimensione della ventola (L x P x A)	120 x 25 x 120 mm
flusso d'aria minimo	48,45 pdc/min	Lunghezza cavo	0,25 m
pressione dell'aria massima	1,67 mmH2O		
Supporto per modulazione di larghezza di impulso (PWM)	✓		
Tempo medio tra guasti (MTBF)	20000 h		
Design			
Colore del prodotto *	Nero, Bianco		
Numero di ventole	1 ventola(e)		



8056157881797

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-APR-2024. Prints or copies of Information are only valid on the printed Publication date