



FEATURES

Alimentatore BS750 - 750W, 80Plus Bronze, PFC Attivo, Ventola HDB 12cm, Semi Modulare

SPECIFICATIONS

Power	750W
Version	ATX V2.31
Certification	80Plus® Bronze
PFC	Active
Input voltage	100-240Vac
Efficiency	Load Efficiency 20% 82% 50% 85% 100% 82%
CE EMI compliance	Yes
Compliance	ErP Lot 6
It supports	ATX12V V2.3 and backwards compatible
ERP	<0.5W
MTBF	100000 hours
Protections	Over current, short circuit, electric shock, over power, over voltage and under voltage for the safety of critical system components (OVP, SCP, OPP, OVP, UVP, SIP)
On / off switch	Yes
Connectors	24Pin; 3x Molex 4Pin; MOBO 4 + 4Pin, [6 + 2] + [6 + 2] Pin, 7xSATA
Type of cables	Semi modular black flat

Cable length (from PCB)

Alimentation cable
Capacitors
Fan

Chassis
12v
Dimensions
Weight

1x24P 700MM
1x [4P + 4P] 800MM
1x [6 + 2/6 + 2] Pin 550 + 150MM
(modular cable)
2x 3SATA 550 + 150 + 150MM
(modular cable)
1x [3IDE + 1SATA] 550 + 150 + 150 + 150MM (modular cable)
1,5m included
Taiwanese TEAPO 105c
120mm silent hydraulic bearing with thermal control
Rough black anti scratch
Single rail
160 * 150 * 86mm
2.24Kg (2.7Kg with box)

PACKING INFORMATION

Code: ITPSEBS750
EAN: 8056157881025
Warranty: 36 months

SOCIAL MEDIA COMMUNICATION

