



AOC Porsche PD27S LED display 68,6 cm (27") 2560 x 1440 Pixel Quad HD LCD Nero, Grigio

Marchio : AOC

Famiglia del prodotto:
Porsche

Codice prodotto: PD27S

Nome del prodotto : PD27S

Screen size (inch) 27, Panel resolution 2560x1440, Refresh rate 170 Hz, Response time MPRT 1 ms, Panel type IPS, HDMI HDMI 2.0 x 2, Display Port DisplayPort 1.4 x 2, Sync technology (VRR) Adaptive Sync

AOC Porsche PD27S. Dimensioni diagonale schermo: 68,6 cm (27"), Risoluzione del display: 2560 x 1440 Pixel, Tipologia HD: Quad HD, Tecnologia display: LCD, Tempo di risposta: 1 ms, Rapporto d'aspetto nativo: 16:9. Altoparlanti incorporati. Hub USB integrato, Versione dell'hub USB: 3.2 Gen 1 (3.1 Gen 1). Montaggio standard VESA, Regolazione altezza. Colore del prodotto: Nero, Grigio



Display		Ergonomics	
Display diagonal *	68.6 cm (27")	Height adjustment *	✓
Display resolution *	2560 x 1440 pixels	Adjustable height (max)	15 cm
HD type *	Quad HD	Pivot	✓
Native aspect ratio *	16:9	Swivelling	✓
Display technology *	LCD	Swivel angle range	-20 - 20°
Panel type *	IPS	Tilt adjustment	✓
Backlight type	W-LED	Tilt angle range	-5 - 21°
Touchscreen *	✗	On Screen Display (OSD)	✓
Display brightness (typical)	350 cd/m²	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Response time *	1 ms		
Anti-glare screen	✓		
Screen shape *	Flat	Number of OSD languages	19
Contrast ratio (typical) *	1000:1	Power	
Maximum refresh rate *	170 Hz	Energy efficiency class (SDR) *	G
Display number of colours *	1.07 billion colours	Energy efficiency class (HDR) *	G
Pixel density	109 ppi	Energy consumption (SDR) per 1000 hours *	32 kWh
Display diagonal (metric)	68.6 cm	Energy consumption (HDR) per 1000 hours *	60 kWh
High Dynamic Range (HDR) supported	✓	Power consumption (typical) *	36 W
High Dynamic Range (HDR) technology	High Dynamic Range (HDR) 400	Power consumption (standby) *	0.5 W
sRGB coverage (typical)	100%	Power consumption (max)	120 W
DCI-P3 coverage	97%	Power consumption (off)	0.3 W
Performance		AC adapter output voltage	20 V
VESA Adaptive Sync support	✓	Power supply type	External
Flicker-free technology	✓	Energy efficiency scale	A to G
Low Blue Light technology	✓		
Game mode	✓		

Multimedia		Power	
Number of speakers	2	European Product Registry for Energy Labelling (EPREL) code	1229018
RMS rated power	10 W	Operational conditions	
Built-in speaker(s) *	✓	Operating temperature (T-T)	0 - 40 °C
Built-in camera *	✗	Storage temperature (T-T)	-25 - 55 °C
Design		Operating relative humidity (H-H)	10 - 85%
Market positioning *	Gaming	Storage relative humidity (H-H)	5 - 93%
Product colour *	Black, Grey	Operating altitude	0 - 5000 m
Frameless design	✓	Non-operating altitude	0 - 12192 m
Front bezel colour	Black	Weight & dimensions	
Detachable stand	✓	Width (with stand)	614 mm
Feet colour	Grey	Depth (with stand)	281.8 mm
Ports & interfaces		Height (with stand)	555.5 mm
Built-in USB hub *	✓	Weight (with stand)	7.65 kg
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Width (without stand)	614 mm
USB upstream port type	USB Type-B	Depth (without stand)	63 mm
Number of upstream ports	1	Height (without stand)	369.2 mm
Number of USB Type-B upstream ports quantity	1	Packaging data	
USB Type-A downstream ports quantity	4	Package width	691 mm
HDMI *	✓	Package depth	378 mm
HDMI ports quantity	2	Package height	570 mm
HDMI version	2.0	Package weight	12.2 kg
DisplayPorts quantity	2	Package type	Box
DisplayPort version	1.4	USB cable length	1.8 m
Headphone out *	✓	Packaging content	
Headphone outputs	1	Stand included	✓
Headphone connectivity	3.5 mm	Cables included	DisplayPort, HDMI
Microphone in	✓	Power adapter included	✓
PC Audio in	✓	DisplayPort cable length	1.8 m
DC-in jack	✓	HDMI cable length	1.8 m
Ergonomics		Other features	
VESA mounting *	✓	Low input lag	✓
Panel mounting interface	100 x 100 mm	FPS counter	✓
Wall mountable	✓	Dial point	✓
Cable lock slot *	✓	Shadow control	✓
Cable lock slot type	Kensington	Motion blur reduction	✓
		Exterior finish type	Matt
		Certification	ISO 9241-307



4056487038599

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAR-2025. Prints or copies of Information are only valid on the printed Publication date