


## StarTech.com Scheda controller RAID PCI Express 2.0 SATA III 6 Gbps a 4 porte con tiering SSD HyperDuo

**Marchio :** StarTech.com

**Codice prodotto:** PEXSAT34RH

**Nome del prodotto :** Scheda controller RAID PCI Express 2.0 SATA III 6 Gbps a 4 porte con tiering SSD HyperDuo



StarTech.com Scheda controller RAID PCI Express 2.0 SATA III 6 Gbps a 4 porte con tiering SSD HyperDuo

StarTech.com Scheda controller RAID PCI Express 2.0 SATA III 6 Gbps a 4 porte con tiering SSD HyperDuo. Interfacce dell'unità di archiviazione supportate: SATA, Serial ATA III, Interfaccia host: PCI Express. Livelli RAID: 0, 1, 10, JBOD, Velocità di trasferimento dati: 6 Gbit/s, Chipset: Marvell - 88SE9230. Sistema operativo Windows supportato: Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64,...., Compatibilità sistema operativo Mac: Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High..., Sistemi operativi server supportati: Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows.... Larghezza: 120 mm, Profondità: 70 mm, Altezza: 20 mm. Larghezza scatola principale: 381 mm, Lunghezza del cartone principale: 488 mm, Altezza scatola principale: 321 mm



Connettività		Condizioni ambientali	
Interfacce dell'unità di archiviazione supportate *	SATA, Serial ATA III	Intervallo temperatura di funzionamento	5 - 50 °C
Interfaccia host *	PCI Express	Intervallo di temperatura	-25 - 70 °C
Versione degli slot PCI Express	2.0	Range di umidità di funzionamento	20 - 80%
Quantità di porte SATA interne	4	<b>Dimensioni e peso</b>	
<b>Prestazione</b>		Larghezza	120 mm
Livelli RAID *	0, 1, 10, JBOD	Profondità	70 mm
Velocità di trasferimento dati	6 Gbit/s	Altezza	20 mm
Supporto SSD	✓	Peso	49 g
Chipset	Marvell - 88SE9230	Larghezza imballo	145 mm
Supporto di Logical block addressing (LBA)	48 bit	Profondità imballo	175 mm
<b>Dettagli tecnici</b>		Altezza imballo	32 mm
Conformità alla sostenibilità	✓	Peso dell'imballo	141 g
Certificati di sostenibilità	CE, RoHS	<b>Dati logistici</b>	
		Larghezza scatola principale	381 mm
		Lunghezza del cartone principale	488 mm
		Altezza scatola principale	321 mm
		Quantità per cartone principale	60 pz
		Codice del Sistema Armonizzato (SA)	84733080
		<b>Altre caratteristiche</b>	
		Manuale dell'utente	✓
		Drivers inclusi	✓
		Fattore di forma della Scheda PCI	Altezza intera (profilo basso)

## Requisiti di sistema

Sistema operativo Windows supportato	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Compatibilità Mac	✓
Compatibilità sistema operativo Mac	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Sistema operativo Linux supportato	✓
Sistemi operativi server supportati	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019



0065030849951



065030849951



0731215166419



731215166419

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.