

StarTech.com Scheda Espansione PCI Express USB 3.0 a 4 porte - 2 interne, 2 esterne - Adattatore PCIe alimentato SATA

Marchio : StarTech.com

Codice prodotto: PEXUSB3S2EI

Nome del prodotto : Scheda Espansione PCI Express USB 3.0 a 4 porte - 2 interne, 2 esterne - Adattatore PCIe alimentato SATA



StarTech.com Scheda Espansione PCI Express USB 3.0 (5Gbps) a 4 porte - 2 interne, 2 esterne - Adattatore PCIe alimentato SATA

StarTech.com Scheda Espansione PCI Express USB 3.0 a 4 porte - 2 interne, 2 esterne - Adattatore PCIe alimentato SATA. Interfaccia host: PCIe, Interfaccia di uscita: SATA, USB 3.2 Gen 1 (3.1 Gen 1), Fattore di forma della scheda di espansione: Piena altezza/Basso profilo. Colore del prodotto: Metallico, Rosso, lunghezza massima cavo: 3 m, Tempo medio tra guasti (MTBF): 1920042 h. Chipset: Renesas / NEC - µPD720201, Velocità massima di trasmissione: 5 Gbit/s. Sistema operativo Windows supportato: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Sistemi operativi server supportati: Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows.... Larghezza: 18 mm, Profondità: 92 mm, Altezza: 120 mm



Connettività		Requisiti di sistema	
Interfaccia host *	PCIe	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64 Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019	
Interfaccia di uscita *	SATA, USB 3.2 Gen 1 (3.1 Gen 1)		
Fattore di forma della scheda di espansione	Piena altezza/Basso profilo		
Scheda di espansione standard	PCI 2.0		
Quantità di porte USB 3.2 Gen 1 (3.1 Gen 1) di tipo A	2		
Quantità di porte SATA interne	1		
Design		Sistema operativo Windows supportato	
Interno *	✓		
Colore del prodotto	Metallico, Rosso		
lunghezza massima cavo	3 m		
Tempo medio tra guasti (MTBF)	1920042 h		
Caratteristiche			
Chipset	Renesas / NEC - µPD720201		
Velocità massima di trasmissione	5 Gbit/s		
Supporto UASP	✓		
Condizioni ambientali			
Intervallo temperatura di funzionamento	5 - 50 °C		
Intervallo di temperatura	-25 - 70 °C		
Range di umidità di funzionamento	20 - 80%		
		Sistemi operativi server supportati	

Dettagli tecnici

Certificati di conformità CE, RoHS

Dimensioni e peso

Larghezza 18 mm
Profondità 92 mm
Altezza 120 mm
Peso 53 g

Dati su imballaggio

Staffe di montaggio incluse ✓
Drivers inclusi ✓
Manuale dell'utente ✓
Larghezza imballo 174 mm
Profondità imballo 143 mm
Altezza imballo 33 mm
Peso dell'imballo 143 g

Dati logistici

Codice del Sistema Armonizzato (SA) 84733020
Quantità per cartone principale 60 pz
Larghezza scatola principale 383 mm
Lunghezza del cartone principale 495 mm
Altezza scatola principale 316 mm

Altre caratteristiche

Massima distanza di funzionamento 3 m



0065030860338



065030860338



0723856593525



723856593525

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.