



Articol	PP2209
Descrizione prodotto	ADATTATORE UNIVERSALE VIAGGIO
Ean	8008225022014

Caratteristiche tecniche

Prese	<table border="1"> <tr> <td>USA/Japan, 2-pole Type A</td> <td>USA, 3-pole Type B</td> <td>Euro, 2-pole Type C</td> <td>French Schuko, 3-pole Type E</td> <td>Schuko, 3-pole Type F</td> <td>UK, 3-pole Type G</td> </tr> <tr> <td>Australia/China, 3-pole Type I</td> <td>Switzerland, 3-pole Type J</td> <td>Italy, 3-pole Type L</td> <td>Brazil, 3-pole Type N</td> <td>India, 3-pole Type D</td> <td>Israel, 3-pole Type H</td> </tr> <tr> <td>Denmark, 3-pole Type K</td> <td colspan="5"></td> </tr> </table>	USA/Japan, 2-pole Type A	USA, 3-pole Type B	Euro, 2-pole Type C	French Schuko, 3-pole Type E	Schuko, 3-pole Type F	UK, 3-pole Type G	Australia/China, 3-pole Type I	Switzerland, 3-pole Type J	Italy, 3-pole Type L	Brazil, 3-pole Type N	India, 3-pole Type D	Israel, 3-pole Type H	Denmark, 3-pole Type K					
	USA/Japan, 2-pole Type A	USA, 3-pole Type B	Euro, 2-pole Type C	French Schuko, 3-pole Type E	Schuko, 3-pole Type F	UK, 3-pole Type G													
	Australia/China, 3-pole Type I	Switzerland, 3-pole Type J	Italy, 3-pole Type L	Brazil, 3-pole Type N	India, 3-pole Type D	Israel, 3-pole Type H													
Denmark, 3-pole Type K																			
SPINE	<p>Australia / Cina Inghilterra Europa (europlug 2 poli) Italia (P11 10A 2P+T) Stati Uniti Europe (Germany , France)</p>																		
USB	<p>Le 2 prese USB erogano, distribuiti su entrambe, al massimo 2.1 A. 5 V DC / Max. 2.4 A (shared), Max. 12.0 W in total</p>																		

SCHEDA DI PRODOTTO**POLYPOOL**
elettricità a libero servizio**MODULO**Modulo **MQ10**
Rev. **00**
Data **16/01/2018**
Pagina **2 di 2**

TENSIONE	100 V – 250 V, 50/60 Hz
POTENZA	100 V – 250 W / 250 V – 625 W
Custodia	In tecnopolimero
COLORE	BIANCO
Altro	Fusibile protezione L'adattatore non è un trasformatore di tensione

Norme e Marchi**CE**