




## TP-Link PSM900-AC alimentatore per computer 900 W Metallico

**Marchio :** TP-Link

**Codice prodotto:** PSM900-AC

**Nome del prodotto :** PSM900-AC

TP-Link PSM900-AC. Potenza totale: 900 W, Tensione di ingresso AC: 100 - 240 V, Frequenza di ingresso AC: 50/60 Hz. Prodotti compatibili: SG6428XHP, SG6654XHP, S6500-24GP4XF, S6500-48GP6XF, S6500-24MPP4Y, S6500-48MPP6Y. Colore del prodotto: Metallico. Larghezza: 95,8 mm, Profondità: 259,5 mm, Altezza: 40,1 mm. Quantità per pacco: 1 pz



|   |  |   |                  |
|---|--|---|------------------|
| <b>Gestione energetica</b>                    |  | <b>Condizioni ambientali</b>            |                  |
| Potenza totale *                              | 900 W  | Intervallo temperatura di funzionamento | 0 - 45 °C        |
| Tensione di ingresso AC *                     | 100 - 240 V  | Intervallo di temperatura               | -40 - 70 °C      |
| Frequenza di ingresso AC                      | 50/60 Hz   | Range di umidità di funzionamento       | 10 - 90%         |
| Corrente di ingresso massima (@110V)          | 12 A   | Umidità                                 | 5 - 90%          |
| Corrente di ingresso massima (@220V)          | 10 A   | <b>Dimensioni e peso</b>                |                  |
| Funzionalità di protezione dell'alimentazione | Sovraccorrente, Sovraccarico, Cortocircuito, Sotto carico                        | Larghezza                               | 95,8 mm          |
| <b>Prestazione</b>                            |  | Profondità                              | 259,5 mm         |
| Prodotti compatibili                          | SG6428XHP, SG6654XHP, S6500-24GP4XF, S6500-48GP6XF, S6500-24MPP4Y, S6500-48MPP6Y | Altezza                                 | 40,1 mm          |
| <b>Design</b>                                 |  | <b>Dati logistici</b>                   |                  |
| Colore del prodotto                           | Metallico  | Quantità per pacco                      | 1 pz             |
| Indicatori LED                                | ✓  | <b>Altre caratteristiche</b>            |                  |
|   |  | Tipo di montaggio                       | Montaggio a rack |



4895252502718



0840030709241



840030709241

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.