

StarTech.com Cavo di Ricarica USB-C a 90° da 30cm - Cavetto di Ricarica Veloce USB Tipo-C per uso intensivo - Cavo Dati USB 2.0 Type-C a C in Resistente Fibra Aramidica - PD 60W 3A - Nero




Marchio : StarTech.com

Codice prodotto: R2CCR-30C-USB-CABLE

Nome del prodotto : Cavo di Ricarica USB-C a 90° da 30cm - Cavetto di Ricarica Veloce USB Tipo-C per uso intensivo - Cavo Dati USB 2.0 Type-C a C in Resistente Fibra Aramidica - PD 60W 3A - Nero

StarTech.com Cavo di Ricarica USB-C a 90° da 30cm - Cavetto di Ricarica Veloce USB Tipo-C per uso intensivo, Cavo Dati USB 2.0 Type-C a C in Resistente Fibra Aramidica, PD 60W 3A (R2CCR-30C-USB-CABLE)

StarTech.com Cavo di Ricarica USB-C a 90° da 30cm - Cavetto di Ricarica Veloce USB Tipo-C per uso intensivo - Cavo Dati USB 2.0 Type-C a C in Resistente Fibra Aramidica - PD 60W 3A - Nero. Lunghezza cavo: 0,3 m. Connettore 1: USB B, Connettore 2: USB C, Versione USB: USB 2.0, Massima velocità di trasferimento: 0,48 Gbit/s, Colore del prodotto: Nero



Features		Weight & dimensions	
USB version *	USB 2.0	Cable diameter	3.1 mm
Connector 1 *	USB B	Weight	12 g
Connector 2 *	USB C	Packaging data	
Connector 1 gender *	Male	Package width	220 mm
Connector 2 gender *	Male	Package depth	128 mm
Connector 1 form factor	Straight	Package height	30 mm
Connector 2 form factor	Angled	Package weight	10.8 g
AWG wire size	32/22	Packaging content	
Cable jacket material	Thermoplastic elastomer (TPE)	Quantity per pack *	1 pc(s)
Cable shielding	Aluminum mylar foil	Sustainability	
Maximum data transfer rate	480 Mbit/s	Sustainability compliance	✓
Maximum data transfer rate	0.48 Gbit/s	Operational conditions	
Product colour *	Black	Operating temperature (T-T)	0 - 50 °C
Cable type	Round cable	Storage temperature (T-T)	0 - 50 °C
Plug and Play	✓	Logistics data	
Fast charging	✓	Products per master (outer) case	400 pc(s)
USB Power Delivery (USB PD)	✓	Master (outer) case width	430 mm
USB Power Delivery up to	60 W	Master (outer) case length	380 mm
Power		Master (outer) case height	290 mm
Output current (max)	3 A	Other features	
Weight & dimensions		Compliance certificates	RoHS
Cable length *	0.3 m		



0065030895835



065030895835

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-NOV-2024. Prints or copies of Information are only valid on the printed Publication date