DELL PowerEdge T350 server 8 TB Tower Intel Xeon E E-2336 2,9 GHz 16 GB DDR4-SDRAM 700 W

Marchio : DELL

Famiglia del prodotto: PowerEdge

Codice prodotto: RW9J2

Nome del prodotto : T350

- No OS
- Intel Xeon E-2336 (12MB Cache, 2.9GHz)
- 16GB DDR4-SDRAM (1 x 16) & 8000GB HDD
- iDRAC9, Enterprise 15G

Intel Xeon E-2336 (12MB Cache, 2.9GHz), 16GB DDR4-SDRAM, 8000GB HDD, LAN (Broadcom 5720), PERC H755, iDRAC9, Enterprise 15G, 700W, No OS

DELL PowerEdge T350 server 8 TB Tower Intel Xeon E E-2336 2,9 GHz 16 GB DDR4-SDRAM 700 W:

Server potente con processore singolo
Soddisfa le esigenze di elaborazione in continua evoluzione con un server tower facile da gestire, progettato per le aziende alla ricerca di funzionalità enterprise convenienti.
DELL PowerEdge T350. Famiglia processore: Intel Xeon E, Frequenza del processore: 2,9 GHz, Modello del processore: E-2336. RAM installata: 16 GB, Tipo di RAM: DDR4-SDRAM, Struttura memoria: 1 x 16 GB. Capacità totale di archiviazione: 8 TB, Dimensione hard disk: 3.5", Interfaccia hard disk: SATA III. Collegamento ethernet LAN, Tecnologia di cablaggio: 10/100/1000Base-T(X). Alimentazione: 700 W. Tipo di case: Tower

Processor

Processor manufacturer *	Intel
Processor family *	Intel Xeon E
Processor model *	E-2336
Processor frequency *	2.9 GHz
Processor boost frequency	4.8 GHz
Processor cores	6
Processor cache	12 MB
Number of processors installed	1
Processor threads	12

Memory

Internal memory *	16 GB
Internal memory type *	DDR4-SDRAM
Buffered memory type	Unregistered (unbuffered)
Memory slots	4x DIMM
ECC	✔
Memory layout (slots x size)	1 x 16 GB
Memory data transfer rate	3200 MT/s
Maximum internal memory *	128 GB

Storage

Total storage capacity *	8 TB
Number of HDDs installed	2
HDD capacity	4 TB
HDD interface	SATA III
HDD speed	7200 RPM
HDD size	3.5"
Number of HDDs supported	8
Supported HDD sizes	3.5"
RAID support *	✘

Performance

Trusted Platform Module (TPM)	✔
Trusted Platform Module (TPM) version	2.0

Software

Operating system installed *	✘
Compatible operating systems *	Canonical Ubuntu Server LTS Citrix Hypervisor Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server

Power

Redundant power supply (RPS) support *	✘
Power supply *	700 W
Number of main power supplies	1
Power supply input voltage	200 - 240 V
Power cable length	2 m
Power cable connector 1	C13 coupler
Power cable current	10 A

Operational conditions

Operating temperature (T-T)	10 - 35 °C
Storage temperature (T-T)	-40 - 65 °C
Storage relative humidity (H-H)	5 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 12000 m

Carbon footprint

Total carbon footprint (kg of CO2e)	2310
Total carbon emissions, standard deviation (kg of CO2e)	999

Storage

Supported RAID controllers	PERC H755
Hot-Plug support	✔
Optical drive type *	✘

Network

LAN controller	Broadcom 5720
Ethernet LAN	✔
Cabling technology	10/100/1000Base-T(X)
Ethernet interface type	Gigabit Ethernet

Ports & interfaces

Ethernet LAN (RJ-45) ports *	2
USB 2.0 ports quantity	5
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
VGA (D-Sub) ports quantity	1
Parallel ports quantity	1
Power cables quantity	1

Design

Chassis type *	Tower
Product colour	Black
Bezel	✔

Performance

Remote administration	iDRAC9, Enterprise 15G

Carbon footprint

Carbon emissions, manufacturing (kg of CO2e)	452.64
Carbon emissions, logistics (kg of CO2e)	198
Carbon emissions, energy usage (kg of CO2e)	1630
Carbon emissions, end-of-life (kg of CO2e)	31.3
Total carbon emissions, w/o use phase (kg of CO2e)	680
PAIA version	1.3.2, 2022

Weight & dimensions

Width	175 mm
Depth	581.1 mm
Height	369.5 mm
Weight	25.3 kg

Packaging content

Packaging content	European Power Cord 220V

Other features

Data transfer rate	6 Gbit/s
Bytes per sector	512n

5397184760376