



APC SMC1000IC gruppo di continuità (UPS) A linea interattiva 1 kVA 600 W 8 presa(e) AC

Marchio : APC

Codice prodotto: SMC1000IC

Nome del prodotto : SMC1000IC

APC SMC1000IC. Topologia UPS: A linea interattiva, Potenza in uscita: 1 kVA, Potenza in uscita: 600 W. Tipo di uscita AC: Accoppiatore C13, Presa di corrente: Accoppiatore C14, Quantità prese AC: 8 presa(e) AC. Tecnologia batteria: Acido piombo (VRLA), Durata della batteria (max): 5 anno/i, Tempo di ricarica: 3 h. Fattore di forma: Mini Tower, Colore del prodotto: Nero, Tipo di display: LCD. Larghezza: 171 mm, Profondità: 439 mm, Altezza: 219 mm




Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	3 h
Output power capacity *	1 kVA	Hot-swap battery	✓
Output power *	600 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	170 V	Design	
Input operation voltage (max) *	300 V	Form factor *	Mini Tower
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	✓
Output frequency	50/60 Hz	Certification	CE, CSA, GOST, UL 1778, VDE
Automatic Voltage Regulation (AVR)	✓	Operational conditions	
Surge energy rating	455 J	Operating temperature (T-T)	0 - 40 °C
Output voltage Total Harmonic Distortion (THD)	5%	Storage temperature (T-T)	-15 - 45 °C
Noise level	41 dB	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Operating altitude	0 - 3000 m
Web-based management	✓	Non-operating altitude	0 - 15000 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Technical details	
Auto-restart	✓	Sustainability certificates	Green Premium
Temperature voltage compensation	✓	Total carbon footprint (kg of CO2e)	853.59
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler	Width	171 mm
Power plug	C14 coupler	Depth	439 mm
AC outlets quantity	8 AC outlet(s)	Height	219 mm

Ports & interfaces		Weight & dimensions	
USB port	✓	Weight	17.3 kg
USB 2.0 ports quantity	1	Package width	328 mm
Serial ports quantity	1	Package depth	595 mm
Ethernet LAN (RJ-45) ports	1	Package height	376 mm
Battery		Package weight	19.6 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
Battery life (max)	5 year(s)	Cables included	USB cable
		Resource CD	✓
		Software CD	✓
		Logistics data	
		Products per pallet	18 pc(s)
		Harmonized System (HS) code	85078000



0731304332947



731304332947

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-JAN-2025. Prints or copies of Information are only valid on the printed Publication date