



## APC SMT3000RM12UC gruppo di continuità (UPS) A linea interattiva 3 kVA 2700 W 9 presa(e) AC

Marchio : APC

Codice prodotto: SMT3000RM12UC

Nome del prodotto : SMT3000RM12UC



APC SMT3000RM12UC. Topologia UPS: A linea interattiva, Potenza in uscita: 3 kVA, Potenza in uscita: 2700 W. Tipo di uscita AC: Accoppiatore C13, Accoppiatore C19, Presa di corrente: Accoppiatore C20, Quantità prese AC: 9 presa(e) AC. Tecnologia batteria: Acido piombo (VRLA), Capacità della batteria: 547 VAh, Tempo di salvataggio minimo a pieno carico: 3,2 min. Fattore di forma: Montaggio a rack, Colore del prodotto: Nero, Capacità di rack: 2U. Larghezza: 432 mm, Profondità: 683 mm, Altezza: 86 mm




Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	3 kVA	Rack capacity	2U
Output power *	2700 W	Cable length	2 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	151 V	Display type	LCD
Input operation voltage (max) *	302 V	LED indicators	Status
Input frequency *	50/60 Hz	Certification	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Automatic Voltage Regulation (AVR)	✓	<b>Operational conditions</b>	
Surge energy rating	320 J	Operating temperature (T-T)	0 - 40 °C
Hold time (min)	4 ms	Storage temperature (T-T)	-15 - 45 °C
Hold time (max)	8 ms	Operating relative humidity (H-H)	0 - 95%
Efficiency	98.9%	Storage relative humidity (H-H)	0 - 95%
Noise level	55 dB	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 15000 m
Auto-restart	✓	<b>Technical details</b>	
<b>Ports &amp; interfaces</b>		Sustainability certificates	Green Premium
AC outlet types	C13 coupler, C19 coupler	Total carbon footprint (kg of CO2e)	2968.55
Power plug	C20 coupler	Compliance certificates	RoHS
AC outlets quantity	9 AC outlet(s)	<b>Weight &amp; dimensions</b>	
Number of output IEC jumpers	3	Width	432 mm
USB port	✓	Depth	683 mm
Serial interface	✓	Height	86 mm
Serial interface type	RJ-45	Weight	44.3 kg
Ethernet LAN (RJ-45) ports	1	Package width	600 mm
SmartSlot	✓	Package depth	980 mm
		Package height	254 mm

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package weight	51.7 kg
Battery capacity	547 VAh	<b>Packaging data</b>	
Typical backup time at full load	3.2 min	Rack mount kit	✓
Typical backup time at half load	11.5 min	Cables included	RS-232, USB cable
Battery life (max)	5 year(s)	Quick installation guide	✓
Battery recharge time	3 h	Software CD	✓
Hot-swap battery	✓	Bundled software	Powershute Business Edition
Automatic battery test	✓	<b>Logistics data</b>	
Cold start	✓	Harmonized System (HS) code	85078000
		<b>Other features</b>	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304337348



731304337348

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.