iiyama

iiyama ProLite TF1634MC-B8X Monitor PC 39,6 cm (15.6") 1920 x 1080 Pixel Full HD LED Touch screen Multi utente Nero

Marchio : iiyama

Famiglia del prodotto: ProLite

Codice prodotto: TF1634MC-B8X

Nome del prodotto :
TF1634MC-B8X

iiyama ProLite TF1634MC-B8X. Dimensioni diagonale schermo: 39,6 cm (15.6"), Risoluzione del display: 1920 x 1080 Pixel, Tipologia HD: Full HD, Tecnologia display: LED, Tempo di risposta: 25 ms, Rapporto d'aspetto nativo: 16:9. Montaggio standard VESA. Colore del prodotto: Nero

Display

Display diagonal *	39.6 cm (15.6")
Display resolution *	1920 x 1080 pixels
HD type *	Full HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Touchscreen *	✔
Touchscreen type	Multi-user
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness	450 cd/m²
Response time *	25 ms
Response time measurement type	GTG (Gray to Gray)
Screen shape *	Flat
Contrast ratio (typical) *	700:1
Display number of colours *	16.2 million colours
Pixel pitch	0.179 x 0.179 mm
Horizontal scan range	30 - 84 kHz
Display diagonal (metric)	39.5 cm
Surface hardness	7H

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘

Multimedia

Built-in microphone	✘
Built-in camera *	✘

Ports & interfaces

HDCP	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Wall mountable	✔
On Screen Display (OSD)	✔
Number of OSD languages	7

Power

Energy efficiency class (SDR) *	F
Energy consumption (SDR) per 1000 hours *	12 kWh
Power consumption (typical) *	18 W
Power consumption (standby) *	1.5 W
Power consumption (off)	0.3 W
European Product Registry for Energy Labelling (EPREL) code	391713

Weight & dimensions

Width (without stand)	381 mm
Depth (without stand)	46 mm
Height (without stand)	230.5 mm
Weight (without stand)	2 kg

Packaging data

Package width	455 mm
Package depth	290 mm
Package height	365 mm
Package weight	6.6 kg

Packaging content

Cables included	AC, DisplayPort, HDMI, USB

Design

Product colour *	Black
Glass thickness	2.4 mm

Ports & interfaces

USB Touch port	✔
VGA (D-Sub) ports quantity	1
HDMI *	✔
HDMI ports quantity	1
DisplayPorts quantity	1

Sustainability

Sustainability certificates	ErP

Other features

International Protection (IP) code	IP65
Display viewable area (HxV)	344.2 x 193.5 mm
Placement supported	Horizontal/Vertical
Compliance certificates	CE, REACH, RoHS, WEEE

Logistics data

Harmonized System (HS) code	85285210

4948570118342