



TP-Link TL-SG116P switch di rete Non gestito Gigabit Ethernet (10/100/1000) Supporto Power over Ethernet (PoE) Nero

Marchio : TP-Link

Codice prodotto: TL-SG116P

Nome del prodotto : TL-SG116P



TP-Link TL-SG116P. Tipo interruttore: Non gestito. Tipo di porte RJ-45: Gigabit Ethernet (10/100/1000), Quantità di porte RJ-45: 16. Full duplex. Dimensioni tavola MAC: 8000 voci, Capacità di commutazione: 32 Gbit/s. Standard di rete: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Voltaggio input DC: 9 V. Supporto Power over Ethernet (PoE). Montabile a parete



Management features		Security	
Switch type *	Unmanaged	IGMP snooping	✓
Quality of Service (QoS) support	✓	Loop protection	✓
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	16	Stackable *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Product colour	Black
Gigabit Ethernet (copper) ports quantity	16	Housing material	Metal
Network		LED indicators	✓
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u	Wall mountable	✓
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Power	
Cable types supported	Cat3, Cat4, Cat5, Cat5e, Cat6	Power supply included *	✓
Port mirroring	✓	AC input voltage	220 V
Full duplex	✓	AC input frequency	50 Hz
Flow control support	✓	DC input voltage	9 V
Link aggregation	✓	Input current	0.6 A
Broadcast storm control	✓	Power consumption (typical)	11.72 W
Rate limiting	✓	Power consumption (max)	144.28 W
Auto MDI/MDI-X	✓	Power over Ethernet (PoE)	
Auto-negotiation	✓	Power over Ethernet (PoE) *	✓
Cable length detection	✓	Operational conditions	
VLAN support	✓	Operating temperature (T-T)	0 - 40 °C
Virtual LAN features	Protocol-based VLAN, Tagged VLAN	Storage temperature (T-T)	-40 - 70 °C
Number of VLANs	32	Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	5 - 90%
		Heat dissipation	490.55 BTU/h
		Weight & dimensions	
		Width	286 mm

Data transmission		Weight & dimensions	
Switching capacity *	32 Gbit/s	Depth	111.7 mm
Forwarding rate	23.81 Mpps	Height	25.4 mm
MAC address table *	8000 entries	Packaging content	
Store-and-forward	✓	Quick start guide	✓
Number of queues	4	Packaging data	
Jumbo frames support	✓	Package width	227 mm
Jumbo frames	9000	Package depth	434 mm
Packet buffer memory	4.1 MB	Package height	70 mm
		Package weight	2 kg



4895252500318



0840030708398



840030708398



4895252500301

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.