

ZYXEL

## Zyxel USG FLEX 700 firewall (hardware) 5,4 Gbit/s

**Marchio :** Zyxel

**Codice prodotto:** USGFLEX700-EU0102F

**Nome del prodotto :** USG FLEX 700

Zyxel USG FLEX 700. Velocità di trasmissione del firewall: 5,4 Gbit/s, Portata VPN: 1,1 Gbit/s, Rendimento VPN (IMIX): 550 Mbit/s. Dissipazione del calore: 120,1 BTU/h. Numero di utenti: 150 utente(i). Algoritmi di sicurezza supportati: HTTPS, IPSec, SSL/TLS, Supporto VPN: IKEv2, IPSec, SSL, L2TP/IPSec. Tecnologia di connessione: Cablato, Velocità trasferimento Ethernet LAN: 10,100,1000 Mbit/s, Console port: RJ-45



<b>Data transmission</b>		<b>Power</b>	
Firewall throughput *	5.4 Gbit/s	Input current	2.5 A
VPN throughput	1.1 Gbit/s	Power consumption (max)	46 W
VPN (IMIX) throughput	550 Mbit/s	<b>Certificates</b>	
<b>Performance</b>		Certification	FCC 15 (A), CE EMC (A), C-Tick (A), BSMI
Heat dissipation	120.1 BTU/h	<b>Operational conditions</b>	
<b>Network</b>		Operating temperature (T-T)	0 - 40 °C
VPN tunnels quantity	500	Storage temperature (T-T)	-30 - 70 °C
Number of users	150 user(s)	Operating relative humidity (H-H)	10 - 90%
Number of VLANs	128	Storage relative humidity (H-H)	10 - 90%
Active TCP connections (max)	1600000	<b>Weight &amp; dimensions</b>	
<b>Security</b>		Width	430 mm
Security algorithms	HTTPS, IPSec, SSL/TLS	Depth	250 mm
VPN support	IKEv2, IPSec, SSL, L2TP/IPSec	Height	44 mm
<b>Management features</b>		Weight	3.3 kg
LED indicators	✓	<b>Packaging data</b>	
Web-based management	✓	Package width	519 mm
<b>Ports &amp; interfaces</b>		Package height	392 mm
Connectivity technology	Wired	Package depth	163 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Package weight	4.8 kg
Ethernet LAN (RJ-45) ports	12	<b>Packaging content</b>	
Ethernet LAN data rates	10,100,1000 Mbit/s	Cables included	AC
Console port	RJ-45	Rack mount kit	✓
SFP module slots quantity	2	<b>Other features</b>	
<b>Design</b>		Firewall throughput	5400 Mbit/s
Rack mounting	✓	VPN throughput	1100 Mbit/s
<b>Power</b>		<b>Logistics data</b>	
AC input voltage	100-240 V	Harmonized System (HS) code	85176990
AC input frequency	50 - 60 Hz		



4718937614851



0760559127350



760559127350

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.