

NETGEAR Insight Cloud Managed WiFi 6 AX1800 Dual Band Access Point (WAX610) 1800 Mbit/s Bianco Supporto Power over Ethernet (PoE)

Marchio : NETGEAR

Codice prodotto: WAX610-100EUS

Nome del prodotto : Insight Cloud Managed WiFi 6 AX1800 Dual Band Access Point (WAX610)

NETGEAR Insight Cloud Managed WiFi 6 AX1800 Dual Band Access Point (WAX610). 2.4 GHz, 5 GHz, Velocità massima di trasferimento dati: 1800 Mbit/s. Algoritmi di sicurezza supportati: EAP-PEAP, EAP-TLS, EAP-TTLS, PEAP, SSH, SSL/TLS, WPA, WPA2, WPA2-Enterprise, WPA3. Velocità trasferimento Ethernet LAN: 10,100,1000,2500 Mbit/s. Supporto Power over Ethernet (PoE). Colore del prodotto: Bianco



Features		Power	
2.4 GHz *	✓	Power over Ethernet (PoE) *	✓
5 GHz *	✓	AC input voltage	12 V
Maximum data transfer rate *	1800 Mbit/s	Input current	2.5 A
Maximum data transfer rate (2.4 GHz)	600 Mbit/s	Design	
Maximum data transfer rate (5 GHz)	1200 Mbit/s	Placement *	Ceiling, Wall
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Product colour *	White
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11i, IEEE 802.11n, IEEE 802.1x, IEEE 802.3af, IEEE 802.3at	Reset button	✓
Number of users	250 user(s)	LED indicators	LAN, Power, Status
Auto MDI/MDI-X	✓	Antenna	
MIMO	✓	Antenna type *	Internal
MIMO type	Multi User MIMO	Antenna gain level (max)	4.5 dBi
Spread spectrum method	OFDM, OFDMA	Weight & dimensions	
Wi-Fi Multimedia (WMM)/(WME)	✓	Width	160.9 mm
VLAN support	✓	Depth	160.9 mm
Security		Height	33.2 mm
Security algorithms *	EAP-PEAP, EAP-TLS, EAP-TTLS, PEAP, SSH, SSL/TLS, WPA, WPA2, WPA2-Enterprise, WPA3	Weight	412 g
MAC address filtering	✓	Packaging data	
Service Set Identifier (SSID) features	Multiple SSIDs, SSID broadcast, SSID broadcast on/off	Package width	220 mm
Number of SSID supported	8	Package depth	455 mm
Auto Wireless Distribution System (WDS)	✓	Package height	235 mm
		Package weight	3.98 kg
		Packaging content	
		Quantity per pack	1 pc(s)
		Mounting kit	✓
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C

Security

Remote Authentication Dial-In User Service (RADIUS) ✓

Ports & interfaces

Ethernet LAN (RJ-45) ports * 1

DC-in jack ✓

Logistics data

Harmonized System (HS) code 85176990



0606449149227



606449149227



(01)10606449149224



0606449148299



606449148299

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.