iiyama

iiyama ProLite XUB2797HSN-B2 Monitor PC 68,6 cm (27") 1920 x 1080 Pixel Full HD LED Nero

Marchio: iiyama Famiglia del prodotto: ProLite Codice prodotto: XUB2797HSN-B2

Nome del prodotto:

XUB2797HSN-B2

27", 68.5cm, 16:9, 1920 x 1080, 300 cd/m², 611.5 x 400.5 (550.5) x 209.5mm

iiyama ProLite XUB2797HSN-B2 Monitor PC 68,6 cm (27") 1920 x 1080 Pixel Full HD LED Nero:

Monitor da 27" con tecnologia pannello IPS, dock USB-C e RJ45 (LAN)

Dotato di un connettore dock USB-C, il modello XUB2797HSN consente di semplificare lo spazio di lavoro utilizzando un unico cavo per inviare il segnale dal notebook al monitor e per alimentare e caricare il notebook dal monitor. Inoltre, se il monitor è collegato a Internet con un cavo LAN, anche il notebook sarà automaticamente connesso alla rete. Grazie all'uscita DisplayPort è possibile estendere facilmente la scrivania creando una configurazione a doppio monitor. Fornito con un supporto regolabile in altezza di 150 mm, con funzioni di rotazione e di orientamento, il XUB2797HSN consente di regolare facilmente la posizione dello schermo in base alle proprie preferenze.





| Display | | Ports & interfaces | |
|--|-----------------------|---------------------------------------|--------------------------------|
| Display diagonal * | 68.6 cm (27") | HDCP | 1 |
| Display resolution * | 1920 x 1080 pixels | Network | |
| HD type * | Full HD | Ethernet LAN | 1 |
| Native aspect ratio * | 16:9 | Ethernet LAN | • |
| Display technology * | LED | Ergonomics | |
| Panel type * | IPS | VESA mounting * | ✓ |
| Touchscreen * | × | Panel mounting interface | 100 x 100 mm |
| Display brightness (typical) | 300 cd/m ² | Cable management | ✓ |
| Response time * | 1 ms | Cable lock slot * | / |
| Response time (MPRT) | 1 ms | Cable lock slot type | Kensington |
| Display surface | Matt | Height adjustment * | ✓ |
| Screen shape * Contrast ratio (typical) * | Flat 1000:1 | Adjustable height (max) | 15 cm |
| Contrast ratio (typical) ** Contrast ratio (dynamic) | 80000000:1 | Pivot | 1 |
| Maximum refresh rate * | 100 Hz | Pivot angle | 0 - 90° |
| Viewing angle, horizontal | 178° | Swivelling | 1 |
| Viewing angle, vertical | 178° | Swivel angle range | 45 - 90° |
| Display number of colours * | 16.7 million colours | Tilt adjustment | √ |
| Pixel pitch | 0.311 x 0.311 mm | Tilt angle range | 5 - 23° |
| Horizontal scan range | 30 - 110 kHz | On Screen Display (OSD) | ✓ 23 |
| Viewable size, horizontal | 59.8 cm | on screen bisplay (03b) | Czech, German, Dutch, English, |
| Viewable size, vertical | 33.6 cm | On Screen Display (OSD) languages | |
| Display diagonal (metric) | 69 cm | | Polish, Russian |
| DDC/CI | ✓ | Power | |
| Colour gamut standard | NTSC, sRGB | Energy efficiency class (SDR) * | E |
| sRGB coverage (typical) | 99% | Energy efficiency class (HDR) * | Not available |
| NTSC coverage (typical) | 72% | , , , , , , , , , , , , , , , , , , , | |

| Performance | | Power | |
|-----------------------------|-----------------------|---|----------------------|
| VESA Adaptive Sync support | 1 | Energy consumption (SDR) per 10 hours * | ⁰⁰ 22 kWh |
| Flicker-free technology | • | Power consumption (typical) * | 24 W |
| Low Blue Light technology | ✓ | Power consumption (standby) * | 0.5 W |
| Multimedia | | Power consumption (off) | 0.3 W |
| Number of speakers | 2 | AC input voltage | 100 - 240 V |
| RMS rated power | 4 W | AC input frequency | 50/60 Hz |
| Built-in speaker(s) * | ✓ | Power supply type | Internal |
| Built-in camera * | × | Energy efficiency scale | A to G |
| Design | | Weight & dimensions | |
| • | Duninger | Width (with stand) | 611.5 mm |
| Market positioning * | Business | Depth (with stand) | 209.5 mm |
| Product colour * | Black | Height (with stand) | 550.5 mm |
| Ports & interfaces | | Weight (with stand) | 6 kg |
| Built-in USB hub * | ✓ | Width (without stand) | 611.5 mm |
| USB hub version | 3.2 Gen 1 (3.1 Gen 1) | Depth (without stand) | 209.5 mm |
| USB Power Delivery (USB PD) | ✓ | Height (without stand) | 400.5 mm |
| USB Power Delivery up to | 65 W | Packaging data | |
| HDMI * | ✓ | Package width | 679 mm |
| HDMI ports quantity | 1 | Package depth | 130 mm |
| HDMI version | 1.4 | Package height | 427 mm |
| DisplayPorts quantity | 1 | Package weight | 8.7 kg |
| DisplayPort out version | 1.2 | Package type | Box |
| Headphone out * | ✓ | Other features | |
| | | Warranty period | 5 year(s) |



4948570124978

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.